

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date: 19.12.2023	MAT000417936 AU/EN	Date of first issue: 16.11.2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MOBIHEL 3:1 FILLER UNIVERSAL

Product code : 41793602

Manufacturer or supplier's details

Details of the supplier of the safety data sheet

Company : Helios Coatings Australia Pty Ltd
50 Clapham Road
SEFTON NSW 2162
Australia

Telephone : 61 2 9645 3188
E-mail address Responsible/issuing person : 61 2 9645 3188
info@helioscoatings.com.au

Emergency telephone number

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Skin sensitisation : Category 1
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date: 19.12.2023	MAT000417936 AU/EN	Date of first issue: 16.11.2023

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
talc	14807-96-6	>= 10 -< 30
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	>= 20 -< 30
n-butyl acetate	123-86-4	>= 10 -< 20
titanium dioxide	13463-67-7	< 10
reaction product: bisphenol a (epichlorohydrin); M<700	25068-38-6	>= 1 -< 10
Hexanoic acid, 2-ethyl-, zinc salt, basic	85203-81-2	< 3

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date: 19.12.2023	MAT000417936 AU/EN	Date of first issue: 16.11.2023

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3Y
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of
-

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

ignition.

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Talc	14807-96-6	TWA	2.5 mg/m ³	AU OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	STEL	150 ppm 655 mg/m ³	AU OEL
		TWA	80 ppm 350 mg/m ³	AU OEL
		TWA	20 ppm	ACGIH
n-butyl acetate	123-86-4	STEL	200 ppm	AU OEL

MOBIHEL 3:1 FILLER UNIVERSAL

Version 1.1
 Revision Date: 19.12.2023
 SDS Number: MAT000417936
 AU/EN

Date of last issue: 16.11.2023
 Date of first issue: 16.11.2023

			950 mg/m ³	
		TWA	150 ppm 713 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
titanium dioxide	13463-67-7	TWA	10 mg/m ³	AU OEL
		TWA (Respirable particulate matter)	0.2 mg/m ³ (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

Hand protection

Gloves : | Viton® (> 0,6 mm; < 240 min); DIN EN374 |
 | PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166
 Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : grey

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : -78.0 °C
(calculation method (principal components, lowest value))

Boiling point/boiling range : 126 °C
(calculation method (principal components, lowest value))

Flash point : 29 °C
Method: ISO 3679, closed cup

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper flammability limit : 7.5 %(V)

Lower explosion limit / Lower flammability limit : 1.1 %(V)

Vapour pressure : < 1,100 hPa (50 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 1.252 g/cm³

Solubility(ies)
Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date: 19.12.2023	MAT000417936 AU/EN	Date of first issue: 16.11.2023

Auto-ignition temperature	:	425 °C
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C)
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion
VOC	:	(Directive 2004/42/EC) 540 g/l

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Incompatible with strong acids and bases.
Hazardous decomposition products	:	Adequate ventilation is required. Heating can release vapours which can be ignited. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

Acute oral toxicity : LD50 Oral (Rat): $\geq 8,700$ mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): $\geq 10,760$ mg/kg

Acute dermal toxicity : LD50 (Rabbit): $\geq 5,000$ mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Result : irritating

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Result : Eye irritation

Hexanoic acid, 2-ethyl-, zinc salt, basic:

Result : Eye irritation

MOBIHEL 3:1 FILLER UNIVERSAL

Version 1.1
Revision Date: 19.12.2023
SDS Number: MAT000417936
AU/EN

Date of last issue: 16.11.2023
Date of first issue: 16.11.2023

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Result : Probability or evidence of skin sensitisation in humans

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Hexanoic acid, 2-ethyl-, zinc salt, basic:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

May cause respiratory irritation.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date: 19.12.2023	MAT000417936 AU/EN	Date of first issue: 16.11.2023

Aspiration toxicity

Not classified based on available information.

Components:**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): $\geq 1 - 10$ mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): $\geq 1 - 10$ mg/l

Toxicity to microorganisms : EC50 (Bacteria): $\geq 1 - 100$ mg/l

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): ≥ 647.7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish : LC50 : 1.3 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50: 2.1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : LC50: > 11 mg/l
Exposure time: 72 h

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Hexanoic acid, 2-ethyl-, zinc salt, basic:**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d pH: 8
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Biodegradability : Kinetic:
28 d: 5 %
Method: OECD Test Guideline 301F

Bioaccumulative potential**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n- : log Pow: 1.81

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

octanol/water

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Partition coefficient: n- : log Pow: 2.64 - 3.78
octanol/water

Mobility in soil**Components:**

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environ- : Koc: 537, log Koc: 2.73
mental compartments : Remarks: Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

Other adverse effects**Product:**

Additional ecological infor- : No data available
mation

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemi-
cal or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

IATA-DGR

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

UN/ID No. : UN 1263
 Proper shipping name : Paint
 Class : 3
 Packing group : III
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 366
 Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
 Proper shipping name : PAINT

 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : UN 1263
 Proper shipping name : PAINT
 Class : 3
 Packing group : III
 Labels : 3
 Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform : Schedule 7
 Scheduling of Medicines and
 Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

SECTION 16. OTHER INFORMATION

Revision Date : 19.12.2023

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

AU OEL / TWA : Exposure standard - time weighted average

AU OEL / STEL : Exposure standard - short term exposure limit

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET



MOBIHEL 3:1 FILLER UNIVERSAL

Version	Revision	SDS Number:	Date of last issue: 16.11.2023
1.1	Date:	MAT000417936	Date of first issue: 16.11.2023
	19.12.2023	AU/EN	

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN