

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH
Product code : 40026402

Manufacturer or supplier's details**Details of the supplier of the safety data sheet**

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
Domžale 1230
Slovenia

Telephone : 386 (1) 722 4383
Telefax : 386 (1) 722 4310
E-mail address Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

Emergency telephone number

Ambulance: 103 (General: 112 or 911)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings and paints, thinners, paint removers
Restrictions on use : Reserved for industrial and professional use.

2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure : Category 2
Long-term (chronic) aquatic hazard : Category 3

GHS-Labeling

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Components

Chemical name	CAS-No.	Classification	MAC value mg/m ³ / TSEL value	Concentration (% w/w)
reaction mixture of ethylbenzene, m-xylene and p-xylene	-	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 (Respiratory	TWA: 50 ppm 221 mg/m ³ Identifies the possibility of significant uptake through the skin, Indicative Data Source: 2000/39/EC STEL: 100 ppm 442 mg/m ³ Identifies the	>= 30 - < 50

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0
 Revision Date: 19.07.2023
 SDS Number: MAT000400264
 AM/EN

Date of last issue: -
 Date of first issue: 19.07.2023

		system) STOT RE2; H373 Asp. Tox.1; H304	possibility of significant uptake through the skin, Indicative Data Source: 2000/39/EC TWA: 50 ppm 221 mg/m3 Identifies the possibility of significant uptake through the skin, Indicative Data Source: 2000/39/EC STEL: 100 ppm 442 mg/m3 Identifies the possibility of significant uptake through the skin, Indicative Data Source: 2000/39/EC	
acetone	67-64-1	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336 (Central nervous system)	TWA: 500 ppm 1.210 mg/m3 Indicative Data Source: 2000/39/EC TWA: 500 ppm 1.210 mg/m3 Indicative Data Source: 2000/39/EC	>= 10 - < 20
n-butyl acetate	123-86-4	Flam. Liq.3; H226 STOT SE3; H336 (Central nervous system)	STEL: 150 ppm 723 mg/m3 Indicative Data Source: 2019/1831/EU TWA: 50 ppm 241 mg/m3 Indicative Data Source: 2019/1831/EU STEL: 150 ppm 723 mg/m3 Indicative	>= 1 - < 10

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version
1.0Revision Date: 19.07.2023
SDS Number: MAT000400264
AM/ENDate of last issue: -
Date of first issue: 19.07.2023

			Data Source: 2019/1831/EU TWA: 50 ppm 241 mg/m ³ Indicative Data Source: 2019/1831/EU	
mixture of benzotriazole	104810-48-2	Skin Sens.1; H317 Aquatic Chronic2; H411	No data available	>= 0,25 - < 1
mixture of sterically composed sebacates	1065336-91-5	Skin Sens.1; H317 Repr.2; H361f Aquatic Acute1; H400 Aquatic Chronic1; H410	No data available	>= 0,25 - < 1

For explanation of abbreviations see section 16.

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and : None known.

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version: 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

delayed

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

7. HANDLING AND STORAGE

- Advice on protection against : Do not spray on a naked flame or any incandescent material.
-

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version: 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

- fire and explosion Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

Hand protection

Gloves : | Viton® (> 0,6 mm; < 240 min); DIN EN374 |
| PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
-

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : solvent-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : -94,7 °C
(calculation method (principal components, lowest value))
- Boiling point/boiling range : 56 °C
(calculation method (principal components, lowest value))
- Flash point : -18 °C
- Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids
- Upper explosion limit / Upper flammability limit : 13 %(V)
- Lower explosion limit / Lower : 1,1 %(V)
-

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

flammability limit

Vapour pressure : 233 hPa (20 °C)

Relative vapour density : 2
(Air = 1.0)

Relative density : 0,95

Density : 0,944 g/cm³

Solubility(ies)

Water solubility : partly miscible

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

Auto-ignition temperature : 465 - 525 °C

Decomposition temperature : No decomposition if stored and applied as directed.
Hazardous decomposition products formed under fire conditions.

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Flow time : 22 - 27 s (20 °C)
Cross section: 4 mm
Method: DIN 53211

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2004/42/EC)
540 g/l

10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition : Adequate ventilation is required.

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

products Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

11. TOXICOLOGICAL INFORMATION**Skin corrosion/irritation****Product:**

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitisation**Product:**

Remarks : Causes sensitisation.

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version: 1.0 Revision Date: 19.07.2023 SDS Number: MAT000400264 AM/EN Date of last issue: -
Date of first issue: 19.07.2023

13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
-

14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : 3

IATA-DGR

- UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1263
Proper shipping name : PAINT
- Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 AM/EN	Date of first issue: 19.07.2023

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture****16. OTHER INFORMATION****Full text of H-Statements****Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET



MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 AM/EN	Date of first issue: 19.07.2023

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AM / EN