

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K HARDENER 1500

Product code : 41672703

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Coatings and paints, thinners, paint removers

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892  
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK  
SI 2019/720, and UK SI 2020/1567)**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758





## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:	 
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer  
n-butyl acetate  
isobutyl acetate  
reaction mixture of ethylbenzene, m-xylene and p-xylene

### Additional Labelling

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 20 - < 30
isobutyl acetate	110-19-0 203-745-1 607-026-00-7 01-2119488971-22	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 1 - < 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

	01-2119475791-29	system)	
solvent naphtha (petroleum), light aromatic	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 1 - < 2,5$
Substances with a workplace exposure limit :			
ethyl 3-ethoxypropionate	763-69-9 212-112-9 01-2119463267-34	Flam. Liq. 3; H226	$\geq 1 - < 10$

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                         |   |
|-------------------------|---|
| General advice          | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Do not leave the victim unattended.  |
| If inhaled              | : Consult a physician after significant exposure.<br>If unconscious, place in recovery position and seek medical advice.  |
| In case of skin contact | : If skin irritation persists, call a physician.<br>If on skin, rinse well with water.<br>If on clothes, remove clothes.  |
| In case of eye contact  | : Flush eyes with water as a precaution.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.                                   |
| If swallowed            | : Keep respiratory tract clear.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician.<br>Take victim immediately to hospital. |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |       |  |
|-------|--|
| Risks | : May cause an allergic skin reaction. |
|-------|--|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : No smoking. Keep container tightly closed in a dry and well-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

areas and containers                      ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability                      : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s)                      : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene-diisocyanate, polymer	28182-81-2	TWA	0,02 mg/m <sup>3</sup> (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL	0,07 mg/m <sup>3</sup> (NCO)	GB EH40
	Further information: Capable of causing occupational asthma.			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
isobutyl acetate	110-19-0	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	187 ppm 903 mg/m <sup>3</sup>	GB EH40
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		STEL	150 ppm	2019/1831/E

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

			723 mg/m3	U
	Further information: Indicative			
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hexamethylene-di-isocyanate, polymer	28182-81-2	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
2.0

Revision Date:  
07.06.2024

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 23.07.2021  
Date of first issue: 23.07.2021

reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
---	-----------	--	-------------	-------------

### Derived No Effect Level (DNEL):

according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene-diisocyanate, polymer	Workers	Inhalation	Long-term local effects	0,5 mg/m3
	Workers	Inhalation	Long-term systemic effects	1 mg/m3
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
isobutyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m3

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
2.0

Revision Date:  
07.06.2024

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 23.07.2021  
Date of first issue: 23.07.2021

	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	5 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	10 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	5 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	5 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	550 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
2.0

Revision Date:  
07.06.2024

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 23.07.2021  
Date of first issue: 23.07.2021

ethyl 3-ethoxypropionate	Workers	Inhalation	Long-term systemic effects	610 mg/m3
	Workers	Inhalation	Long-term local effects	610 mg/m3
	Consumers	Inhalation	Long-term systemic effects	72,6 mg/m3
	Consumers	Inhalation	Long-term local effects	72,6 mg/m3
	Workers	Dermal	Long-term local effects	102 mg/cm2
	Workers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	24,2 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1,2 mg/kg bw/day
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC):

according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0,01 mg/l
	Fresh water	0,1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	1 mg/l
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

		weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
isobutyl acetate	Soil	0,0755 mg/kg dry weight (d.w.)
	Marine water	0,017 mg/l
	Fresh water	0,17 mg/l
	Marine sediment	0,0877 mg/kg dry weight (d.w.)
	Fresh water sediment	0,877 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Intermittent use/release	0,34 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
2-methoxy-1-methylethyl acetate	Soil	0,29 mg/kg dry weight (d.w.)
	Marine water	0,0635 mg/l
	Fresh water	0,635 mg/l
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,00635 mg/l
ethyl 3-ethoxypropionate	Soil	0,048 mg/kg dry weight (d.w.)
	Marine water	0,00609 mg/l
	Fresh water	0,0609 mg/l
	Marine sediment	0,0419 mg/kg dry weight (d.w.)
	Fresh water sediment	0,419 mg/kg dry weight (d.w.)
	Sewage treatment plant	50 mg/l
	Intermittent use/release	0,609 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Tightly fitting safety goggles

### Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: colourless
Odour	: solvent-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: -98,8 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 117 °C (calculation method (principal components, lowest value))
Flash point	: 34 °C
Flammability (solid, gas)	: Static-accumulating flammable liquid., Combustible Solids

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

Upper explosion limit / Upper flammability limit : 10,5 %(V)  
(calculation method (principal components, highest value))

Lower explosion limit / Lower flammability limit : 1,1 %(V)  
(calculation method (principal components, highest value))

Vapour pressure : < 1.100 hPa (calculation method (principal components, highest value))  
(50 °C)

Relative vapour density : 4,6 (calculation method (principal components, highest value))  
(Air = 1.0)

Relative density : No data available

Density : 0,984 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15 (calculation method (principal components, highest value))

Ignition temperature : 315 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if stored and applied as directed.  
Hazardous decomposition products formed under fire conditions.

Viscosity  
Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Flow time : 12 s at 20 °C  
Cross section: 4 mm  
Method: DIN 53211

Explosive properties : Not applicable

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Oxidizing properties : Sustains combustion

### 9.2 Other information

No data available  
VOC : (Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control))  
60,96 %  
Volatile CMR compounds [%]: 0,02 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

### **Components:**

#### **Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

#### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

#### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

LC0 (Rat): 2000 ppm  
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

Repeated exposure may cause skin dryness or cracking.



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

#### **Serious eye damage/eye irritation**

Not classified based on available information.

Not classified due to lack of data.

### **Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Respiratory sensitisation**

Not classified due to lack of data.

### **Product:**

Remarks : Causes sensitisation.

### **Components:**

#### **Hexamethylene-di-isocyanate, polymer:**

Result : Probability or evidence of skin sensitisation in humans

#### **Germ cell mutagenicity**

Not classified based on available information.

Not classified due to lack of data.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Carcinogenicity**

Not classified based on available information.  
Not classified due to lack of data.

### Components:

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### **Reproductive toxicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

### Components:

#### **Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

#### **2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Assessment : May cause respiratory irritation.

### STOT - repeated exposure

Not classified based on available information.  
Not classified due to lack of data.

#### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

Not classified based on available information.  
Not classified due to lack of data.

#### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/l

Toxicity to daphnia and other : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l  
aquatic invertebrates

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

### 2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h

NOEC : 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : LC50 : 408 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47,5 mg/l

### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LC50 (Fish):  $> 1 - 10$  mg/l

Toxicity to daphnia and other : LC50 (Daphnia (water flea)):  $> 1 - 10$  mg/l  
aquatic invertebrates

Toxicity to microorganisms : EC50 (Bacteria):  $> 1 - 10$  mg/l

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### n-butyl acetate:

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Readily biodegradable.

## 12.3 Bioaccumulative potential

### **Components:**

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-  
octanol/water : log Pow: 1,81

#### **isobutyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,72

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Bioaccumulation is unlikely.

Partition coefficient: n-  
octanol/water : log Pow: 2,77 - 3,15

### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8

### **ethyl 3-ethoxypropionate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,35

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

---

### 12.4 Mobility in soil

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

### SECTION 14: Transport information

#### 14.1 UN number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

#### 14.2 UN proper shipping name

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
IATA	:	Paint

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

<b>ADN</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
<b>ADR</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
<b>RID</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:  
Number on list 3



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS
	34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 60,96 %  
Volatile CMR compounds: 0,02 %

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

### SECTION 16: Other information

#### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2021
2.0	07.06.2024	MAT000416727	Date of first issue: 23.07.2021
		GB/EN	

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.