

**MOBIHEL 2K hardener 1300**

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	13.12.2024	MAT000416726 JO/EN	Date of first issue: 28.11.2023

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : MOBIHEL 2K hardener 1300

Product code : 416726

**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-  
stance/Mixture : Coatings and paints, thinners, paint removersRecommended restrictions  
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si**1.4 Emergency telephone number**

Emergency telephone number: 911

---

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single ex-  
posure, Category 3, Central nervous  
system H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single ex- H335: May cause respiratory irritation.

**MOBIHEL 2K hardener 1300**

Version            Revision Date:            SDS Number:  
2.0                13.12.2024                MAT000416726  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

posure, Category 3, Respiratory system

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms            :



Signal word                        :    Warning

Hazard statements                :    H226            Flammable liquid and vapour.  
    H317            May cause an allergic skin reaction.  
    H335            May cause respiratory irritation.  
    H336            May cause drowsiness or dizziness.  
    H412            Harmful to aquatic life with long lasting effects.

Precautionary statements       :

**Prevention:**

P210            Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261            Avoid breathing mist or vapours.  
P273            Avoid release to the environment.  
P280            Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353    IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P370 + P378    In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer  
2-ethoxy-1-methylethyl acetate  
n-butyl acetate  
Hydrocarbons, C9 aromatics

**Additional Labelling**

EUH204            Contains isocyanates. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## MOBIHEL 2K hardener 1300

Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

## SECTION 3: Composition/information on ingredients

## 3.2 Mixtures

## Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	$\geq 30 - < 50$
2-ethoxy-1-methylethyl acetate	54839-24-6 259-370-9 603-177-00-8 01-2119475116-39	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	$\geq 10 - < 20$
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	$\geq 10 - < 20$
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	$\geq 1 - < 10$
Hydrocarbons, C9 aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 2.5 - < 10$
solvent naphtha (petroleum), light aromatic	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 1 - < 2.5$

For explanation of abbreviations see section 16.

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**4.2 Most important symptoms and effects, both acute and delayed**

- Risks : May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.
- May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

**MOBIHEL 2K hardener 1300**

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	13.12.2024	MAT000416726	Date of first issue: 28.11.2023
		JO/EN	

---

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

**5.3 Advice for firefighters**

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

## MOBIHEL 2K hardener 1300

Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m <sup>3</sup>	2000/39/EC
		STEL	50 ppm 333 mg/m <sup>3</sup>	2000/39/EC
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene-diisocyanate, polymer	Workers	Inhalation	Long-term local effects	0.5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
ethyl 3-ethoxypropionate	Workers	Inhalation	Long-term systemic effects	610 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	610 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	72.6 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	72.6 mg/m <sup>3</sup>
	Workers	Dermal	Long-term local effects	102 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	24.2 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.2 mg/kg bw/day
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	333 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	86 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	169 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	120 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	72 mg/kg

## SAFETY DATA SHEET



## MOBIHEL 2K hardener 1300

Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

			fects	bw/day
	Consumers	Oral	Acute systemic effects	36 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Oral	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term exposure	32 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:



## MOBIHEL 2K hardener 1300

Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

Substance name	Environmental Compartment	Value
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
	Fresh water	0.1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	1 mg/l
ethyl 3-ethoxypropionate	Soil	0.048 mg/kg dry weight (d.w.)
	Marine water	0.00609 mg/l
	Fresh water	0.0609 mg/l
	Marine sediment	0.0419 mg/kg dry weight (d.w.)
	Fresh water sediment	0.419 mg/kg dry weight (d.w.)
	Sewage treatment plant	50 mg/l
	Intermittent use/release	0.609 mg/l
2-butoxyethyl acetate	Soil	0.415 mg/kg dry weight (d.w.)
	Marine water	0.0304 mg/l
	Fresh water	0.304 mg/l
	Marine sediment	0.203 mg/kg dry weight (d.w.)
	Fresh water sediment	2.03 mg/kg dry weight (d.w.)
	Sewage treatment plant	90 mg/l
	Intermittent use/release	0.56 mg/l
n-butyl acetate	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l

## 8.2 Exposure controls

## Personal protective equipment

Eye/face protection : Equipment should conform to EN 166  
 Eye wash bottle with pure water  
 Tightly fitting safety goggles

Hand protection

**MOBIHEL 2K hardener 1300**

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	13.12.2024	MAT000416726 JO/EN	Date of first issue: 28.11.2023

---

Gloves	:	Viton® (> 0,6 mm; < 240 min); ISO EN374   PE laminate (> 0,1 mm; < 240 min); ISO EN374
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic vapour type (A)

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	:	liquid
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	-89.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	126 °C (calculation method (principal components, lowest value))
Flash point	:	37 °C
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	10.1 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1 %(V) (calculation method (principal components, highest value))

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

Vapour pressure : < 1,100 hPa (calculation method (principal components, highest value))  
(50 °C)

Relative vapour density : 5.5 (calculation method (principal components, highest value))  
(Air = 1.0)

Relative density : 0.95 (calculation method (principal components, highest value))

Density : 1.013 g/cm<sup>3</sup>

## Solubility(ies)

Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 1.81 (calculation method (principal components, highest value))

Ignition temperature : 280 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if stored and applied as directed.  
Hazardous decomposition products formed under fire conditions.

## Viscosity

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

Flow time : 12 s at 20 °C  
Cross section: 4 mm  
Method: DIN 53211

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

**9.2 Other information**

No data available

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid : Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Incompatible with strong acids and bases.

**10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Not classified based on available information.

Not classified due to lack of data.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

**Components:****Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**2-butoxyethyl acetate:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat):  $\geq 2,400$  mg/kgAcute inhalation toxicity : LC50 (Rat):  $\geq 50$  mg/l  
Exposure time: 2 h  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

LD50 (Rabbit):  $\geq 1,500$  mg/kg**n-butyl acetate:**Acute oral toxicity : LD50 Oral (Rat):  $\geq 10,760$  mg/kgAcute dermal toxicity : LD50 (Rabbit):  $\geq 5,000$  mg/kg**Hydrocarbons, C9 aromatics:**Acute dermal toxicity : LD50 (Rabbit):  $> 3,160$  mg/kg**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Acute oral toxicity : LD50 Oral (Rat):  $> 2,000$  mg/kgAcute inhalation toxicity : LC50 (Rat):  $> 5$  mg/l  
Test atmosphere: vapourAcute dermal toxicity : LD50 (Rabbit):  $> 2,000$  mg/kg**Skin corrosion/irritation**

Not classified based on available information.

Not classified due to lack of data.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation**

Not classified based on available information.

Not classified due to lack of data.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	13.12.2024	MAT000416726	Date of first issue: 28.11.2023
		JO/EN	

## 14 / 22

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**Components:****Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

**2-ethoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

**n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**STOT - repeated exposure**

Not classified based on available information.

Not classified due to lack of data.

**Aspiration toxicity**

Not classified based on available information.

Not classified due to lack of data.

**Components:****Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## MOBIHEL 2K hardener 1300

Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

## SECTION 12: Ecological information

## 12.1 Toxicity

**Components:****2-butoxyethyl acetate:**Toxicity to fish : LC50 (Fish):  $\geq 31$  mg/l  
Exposure time: 96 hToxicity to daphnia and other : LC50 (Daphnia (water flea)):  $\geq 142.5$  mg/l  
aquatic invertebrates Exposure time: 48 hToxicity to microorganisms : EC50 (Bacteria):  $\geq 2,800$  mg/l**n-butyl acetate:**Toxicity to algae/aquatic : NOEC (Desmodesmus subspicatus (green algae)):  $> 200$  mg/l  
plantsEC50 (Desmodesmus subspicatus (green algae)):  $\geq 647.7$   
mg/l  
Exposure time: 72 hToxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h**Hydrocarbons, C9 aromatics:**Toxicity to fish : LC50 (Fish):  $\geq 9.2$  mg/l  
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia (water flea)):  $\geq 3.2$  mg/l  
aquatic invertebrates Exposure time: 48 h**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Toxicity to fish : LC50 (Fish):  $> 1 - 10$  mg/lToxicity to daphnia and other : LC50 (Daphnia (water flea)):  $> 1 - 10$  mg/l  
aquatic invertebratesToxicity to microorganisms : EC50 (Bacteria):  $> 1 - 10$  mg/l**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.



**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023**12.2 Persistence and degradability****Components:****2-butoxyethyl acetate:**

Biodegradability : Result: Biodegradable

**n-butyl acetate:**Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301DStability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

**12.3 Bioaccumulative potential****Components:****2-ethoxy-1-methylethyl acetate:**Partition coefficient: n-  
octanol/water : log Pow: 0.76**2-butoxyethyl acetate:**Partition coefficient: n-  
octanol/water : log Pow: 1.51**n-butyl acetate:**Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.Partition coefficient: n-  
octanol/water : log Pow: 1.81**Hydrocarbons, C9 aromatics:**Partition coefficient: n-  
octanol/water : log Pow: < 4**12.4 Mobility in soil****Components:****Hydrocarbons, C9 aromatics:**Mobility : Medium: Air  
Content: 92.9 %

**MOBIHEL 2K hardener 1300**Version  
2.0Revision Date:  
13.12.2024SDS Number:  
MAT000416726  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023: Medium: Water  
Content: 3.5 %: Medium: Soil  
Content: 1.9 %: Medium: Sediment  
Content: 1.8 %Distribution among environ- : Koc: 1.71 - 14.70  
mental compartments Mobile in soils

The product is insoluble and floats on water.

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects****Product:**Endocrine disrupting poten- : The substance/mixture does not contain components consid-  
tial ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.Additional ecological infor- : An environmental hazard cannot be excluded in the event of  
mation unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**Product : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemi-  
cal or used container.  
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**MOBIHEL 2K hardener 1300**

Version            Revision Date:        SDS Number:  
2.0                13.12.2024            MAT000416726  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information****14.1 UN number**

ADN                                : UN 1263  
ADR                                : UN 1263  
RID                                : UN 1263  
IMDG                               : UN 1263  
IATA                                : UN 1263

**14.2 UN proper shipping name**

ADN                                : PAINT  
ADR                                : PAINT  
RID                                : PAINT  
IMDG                               : PAINT  
IATA                                : Paint

**14.3 Transport hazard class(es)**

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

**14.4 Packing group**

**ADN**  
Packing group                    : III  
Classification Code            : F1  
Hazard Identification Number : 30  
Labels                            : 3

**ADR**  
Packing group                    : III  
Classification Code            : F1  
Hazard Identification Number : 30  
Labels                            : 3  
Tunnel restriction code        : (D/E)

**RID**  
Packing group                    : III  
Classification Code            : F1

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	13.12.2024	MAT000416726	Date of first issue: 28.11.2023
		JO/EN	

**MOBIHEL 2K hardener 1300**

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	13.12.2024	MAT000416726 JO/EN	Date of first issue: 28.11.2023

---

---

**SECTION 16: Other information****Full text of H-Statements**

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H317	: May cause an allergic skin reaction.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-

**MOBIHEL 2K hardener 1300**

Version      Revision Date:      SDS Number:  
2.0          13.12.2024      MAT000416726  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information****Classification of the mixture:**

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 3	H412

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.