

MOBIHEL AirDry FILLER ACTIVATOR

Version 1.1 Revision Date: 07.02.2025 SDS Number: MAT000480785 AU/EN Date of last issue: 16.11.2023
Date of first issue: 16.11.2023

SECTION 1: IDENTIFICATION

Product name : MOBIHEL AirDry FILLER ACTIVATOR

Product code : 48078501

Manufacturer or supplier's details

Details of the supplier of the safety data sheet

Company : Helios Coatings Australia Pty Ltd
50 Clapham Road
SEFTON NSW 2162
Australia

Telephone : 61 2 9645 3188
E-mail address Responsible/issuing person : 61 2 9645 3188
info@helioscoatings.com.au

Emergency telephone number

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Skin corrosion/irritation : Sub-category 1B

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Germ cell mutagenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity - single exposure : Category 2


Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

MOBIHEL AirDry FILLER ACTIVATOR

Version 1.1 Revision Date: 07.02.2025 SDS Number: MAT000480785 AU/EN Date of last issue: 16.11.2023
Date of first issue: 16.11.2023

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	<p>H225 Highly flammable liquid and vapour. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H360 May damage fertility or the unborn child. H371 May cause damage to organs. H373 May cause damage to organs through prolonged or repeated exposure.</p>
Precautionary statements	:	<p>Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.</p> <p>Response: P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor. P333 + P313 If skin irritation or rash occurs: Get medical ad-</p>

MOBIHEL AirDry FILLER ACTIVATOR

Version
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
isobutyl acetate	110-19-0	>= 30 -< 60
blocked cycloaliphatic diamine	54914-37-3	>= 30 -< 60
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	>= 3 -< 10
dibutyltin dilaurate	77-58-7	>= 1 -< 10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.

MOBIHEL AirDry FILLER ACTIVATOR

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	07.02.2025	MAT000480785 AU/EN	Date of first issue: 16.11.2023

Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

MOBIHEL AirDry FILLER ACTIVATOR

Version
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

Methods and materials for : Contain spillage, and then collect with non-combustible ab-
containment and cleaning up sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
miculite) and place in container for disposal according to local
/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against : Do not spray on a naked flame or any incandescent material.
fire and explosion Take necessary action to avoid static electricity discharge
(which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of
ignition.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the ap-
plication area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national
regulations.
Persons susceptible to skin sensitisation problems or asthma,
allergies, chronic or recurrent respiratory disease should not
be employed in any process in which this mixture is being
used.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated
place.
Containers which are opened must be carefully resealed and
kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with
the technological safety standards.

Further information on stor- : No decomposition if stored and applied as directed.
age stability

MOBIHEL AirDry FILLER ACTIVATOR

Version
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
isobutyl acetate	110-19-0	TWA	150 ppm 713 mg/m ³	AU OEL	
		TWA	50 ppm	ACGIH	
		STEL	150 ppm	ACGIH	
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m ³ (Tin)	AU OEL	
		Further information: Skin absorption			
		STEL	0.2 mg/m ³ (Tin)	AU OEL	
		Further information: Skin absorption			
		TWA	0.1 mg/m ³ (Tin)	ACGIH	
		STEL	0.2 mg/m ³ (Tin)	ACGIH	

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

MOBIHEL AirDry FILLER ACTIVATORVersion
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Colour	: colourless
Odour	: solvent-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: -98.8 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	: 117 °C (calculation method (principal components, lowest value))
Flash point	: 17 °C Method: ISO 3679, closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	: 10.5 %(V)
Lower explosion limit / Lower flammability limit	: 1.3 %(V)
Vapour pressure	: 18 hPa (20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.886 g/cm ³
Solubility(ies)	
Water solubility	: immiscible, partly soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: log Pow: 1.72
Auto-ignition temperature	: 423 °C

MOBIHEL AirDry FILLER ACTIVATOR

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	07.02.2025	MAT000480785 AU/EN	Date of first issue: 16.11.2023

Decomposition temperature : No decomposition if used as directed.
Hazardous decomposition products formed under fire conditions.

Viscosity
Viscosity, kinematic : < 20.5 mm²/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Skin corrosion/irritation****Product:**

Remarks : Extremely corrosive and destructive to tissue.

Components:**1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine:**

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation**Product:**

Remarks : May cause irreversible eye damage.

Components:**[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

Result : Corrosive

MOBIHEL AirDry FILLER ACTIVATOR

Version
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023

dibutyltin dilaurate:

Result : Eye irritation

Respiratory or skin sensitisation**Product:**

Remarks : Causes sensitisation.

Components:**1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine:**

Result : Probability or evidence of skin sensitisation in humans

dibutyltin dilaurate:

Result : Probability or evidence of skin sensitisation in humans

Chronic toxicity**Germ cell mutagenicity****Components:****dibutyltin dilaurate:**

Germ cell mutagenicity - Assessment : In vitro tests showed mutagenic effects

Reproductive toxicity**Components:****dibutyltin dilaurate:**

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments

STOT - single exposure**Components:****isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

dibutyltin dilaurate:

Assessment : Causes damage to organs.

MOBIHEL AirDry FILLER ACTIVATOR

Version
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023**STOT - repeated exposure****Components:****dibutyltin dilaurate:**

Assessment : Causes damage to organs through prolonged or repeated exposure.

Further information**Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l
Exposure time: 96 hToxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 350 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 100 mg/l
Exposure time: 21 dToxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 3 h**dibutyltin dilaurate:****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

MOBIHEL AirDry FILLER ACTIVATOR

Version
1.1Revision Date:
07.02.2025SDS Number:
MAT000480785
AU/ENDate of last issue: 16.11.2023
Date of first issue: 16.11.2023**Bioaccumulative potential****Components:****isobutyl acetate:**Partition coefficient: n-
octanol/water : log Pow: 1.72**Mobility in soil**

No data available

Other adverse effects**Product:**Additional ecological infor- : An environmental hazard cannot be excluded in the event of
mation : unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with chemi-
cal or used container.
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**UN/ID No. : UN 3469
Proper shipping name : Paint related material, flammable, corrosive
Class : 3
Subsidiary risk : 8
Packing group : II
Labels : Flammable Liquids, Corrosive
Packing instruction (cargo : 363
aircraft)
Packing instruction (passen- : 352
ger aircraft)**IMDG-Code**UN number : UN 3469
Proper shipping name : PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE

MOBIHEL AirDry FILLER ACTIVATOR

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	07.02.2025	MAT000480785 AU/EN	Date of first issue: 16.11.2023

Class	: 3
Subsidiary risk	: 8
Packing group	: II
Labels	: 3 (8)
EmS Code	: F-E, S-C
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons : Schedule 7
Standard) Instrument

Prohibition/Licensing Requirements : dibutyltin dilaurate
Refer to model WHS Act and Regulations for prohibition, authorisation and restricted use.

SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision Date : 07.02.2025

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
AU OEL / TWA : Exposure standard - time weighted average
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

MOBIHEL AirDry FILLER ACTIVATOR

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	07.02.2025	MAT000480785 AU/EN	Date of first issue: 16.11.2023

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.