

MOBIHEL 2K HARDENER 750W

Version 1.2 Revision Date: 10.09.2025 SDS Number: MAT000477693 AU/EN Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

SECTION 1: IDENTIFICATION

Product name : MOBIHEL 2K HARDENER 750W
Product code : 47769311

Details of the supplier of the safety data sheet

Company : Helios Coatings Australia Pty Ltd
50 Clapham Road
SEFTON NSW 2162
Australia

Telephone : 61 2 9645 3188
E-mail address Responsible/issuing person : 61 2 9645 3188
info@helioscoatings.com.au

Emergency telephone number

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2
Serious eye damage/eye irritation : Category 2A
Skin sensitisation : Category 1
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**

MOBIHEL 2K HARDENER 750W

Version
1.2

Revision Date:
10.09.2025

SDS Number:
MAT000477693
AU/EN

Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MOBIHEL 2K HARDENER 750W

Version 1.2 Revision Date: 10.09.2025 SDS Number: MAT000477693
AU/EN

Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2	>= 30 -< 60
ethylacetate	141-78-6	>= 20 -< 30
n-butyl acetate	123-86-4	>= 10 -< 20
2-butanone	78-93-3	>= 10 -< 20
4-methylpentan-2-one	108-10-1	>= 10 -< 20
toluene	108-88-3	>= 3 -< 10
p-toluenesulphonyl isocyanate	4083-64-1	< 1
hexamethylene diisocyanate	822-06-0	< 10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)

MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 29.11.2023
1.2	10.09.2025	MAT000477693 AU/EN	Date of first issue: 16.11.2023

Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 29.11.2023
1.2	10.09.2025	MAT000477693 AU/EN	Date of first issue: 16.11.2023

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hexamethylene-di-isocyanate, polymer	28182-81-2	TWA	0.02 mg/m ³ (NCO)	AU OEL
	Further information: Sensitiser			
		STEL	0.07 mg/m ³ (NCO)	AU OEL
	Further information: Sensitiser			
ethyl acetate	141-78-6	STEL	400 ppm	AU OEL

MOBIHEL 2K HARDENER 750W

Version
1.2Revision Date:
10.09.2025SDS Number:
MAT000477693
AU/ENDate of last issue: 29.11.2023
Date of first issue: 16.11.2023

			1,440 mg/m ³	
		TWA	200 ppm 720 mg/m ³	AU OEL
		TWA	400 ppm	ACGIH
n-butyl acetate	123-86-4	STEL	200 ppm 950 mg/m ³	AU OEL
		TWA	150 ppm 713 mg/m ³	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
butanone	78-93-3	STEL	300 ppm 890 mg/m ³	AU OEL
		TWA	150 ppm 445 mg/m ³	AU OEL
		TWA	75 ppm	ACGIH
		STEL	150 ppm	ACGIH
4-methylpentan-2-one	108-10-1	STEL	75 ppm 307 mg/m ³	AU OEL
		TWA	50 ppm 205 mg/m ³	AU OEL
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
toluene	108-88-3	TWA	50 ppm 191 mg/m ³	AU OEL
Further information: Skin absorption				
		STEL	150 ppm 574 mg/m ³	AU OEL
Further information: Skin absorption				
		TWA	20 ppm	ACGIH
4-isocyanatosulphonyltoluene	4083-64-1	TWA	0.02 mg/m ³ (NCO)	AU OEL
Further information: Sensitiser				
		STEL	0.07 mg/m ³ (NCO)	AU OEL
Further information: Sensitiser				
hexamethylene-di-isocyanate	822-06-0	TWA	0.02 mg/m ³ (NCO)	AU OEL
Further information: Sensitiser				
		STEL	0.07 mg/m ³ (NCO)	AU OEL
Further information: Sensitiser				
		TWA	0.005 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after	2 mg/l	ACGIH BEI

MOBIHEL 2K HARDENER 750W

Version
1.2Revision Date:
10.09.2025SDS Number:
MAT000477693
AU/ENDate of last issue: 29.11.2023
Date of first issue: 16.11.2023

				exposure ceases)		
4-methylpentan-2-one	108-10-1	methyl iso-butyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
hexamethylene-diisocyanate	822-06-0	1,6-Hexamethylene diamine	Urine	End of shift	15 µg/g creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |
Viton® (> 0,6 mm; < 240 min); ISO EN374 |
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

MOBIHEL 2K HARDENER 750WVersion
1.2Revision Date:
10.09.2025SDS Number:
MAT000477693
AU/ENDate of last issue: 29.11.2023
Date of first issue: 16.11.2023

-
- Eye protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : solvent-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : -95.0 °C
(calculation method (principal components, lowest value))
- Boiling point/boiling range : 77 °C(calculation method (principal components, lowest value))
- Flash point : -4 °C
(calculation method (principal components, lowest value))
- Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids
- Upper explosion limit / Upper flammability limit : 11.5 %(V)
- Lower explosion limit / Lower flammability limit : 1.2 %(V)
- Vapour pressure : < 1,100 hPa (50 °C)
- Relative vapour density : No data available
- Relative density : No data available

MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 29.11.2023
1.2	10.09.2025	MAT000477693 AU/EN	Date of first issue: 16.11.2023

Density : 0.950 g/cm³

Solubility(ies)
Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2.65

Auto-ignition temperature : 404 °C

Decomposition temperature : No decomposition if stored and applied as directed.
Hazardous decomposition products formed under fire conditions.

Viscosity
Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

MOBIHEL 2K HARDENER 750W

Version
1.2Revision Date:
10.09.2025SDS Number:
MAT000477693
AU/ENDate of last issue: 29.11.2023
Date of first issue: 16.11.2023**Components:****Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

ethyl acetate:Acute oral toxicity : LD50 Oral (Rat): $\geq 5,620$ mg/kgAcute inhalation toxicity : LC50 (Rat): 1600 ppm
Exposure time: 8 h
Test atmosphere: vapourAcute dermal toxicity : LD50 (Rabbit): $\geq 20,000$ mg/kg**n-butyl acetate:**Acute oral toxicity : LD50 Oral (Rat): $\geq 10,760$ mg/kgAcute dermal toxicity : LD50 (Rabbit): $\geq 5,000$ mg/kg**butanone:**Acute oral toxicity : LD50 Oral (Rat): $> > 2,000$ mg/kgAcute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapourAcute dermal toxicity : LD50 (Rabbit): $> > 2,000$ mg/kg**4-methylpentan-2-one:**Acute oral toxicity : LD50 Oral (Rat): $> > 2,000$ mg/kgAcute dermal toxicity : LD50 (Rabbit): $> > 2,000$ mg/kg**toluene:**Acute oral toxicity : LD50 Oral (Rat): $> 5,000$ mg/kgAcute inhalation toxicity : LC50 (Rat): > 28 mg/l
Exposure time: 4 h
Test atmosphere: vapourAcute dermal toxicity : LD50 (Rabbit): $> 5,000$ mg/kg**hexamethylene-di-isocyanate:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

MOBIHEL 2K HARDENER 750W

Version 1.2 Revision Date: 10.09.2025 SDS Number: MAT000477693
AU/EN

Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

toluene:

Result : irritating

4-isocyanatosulphonyltoluene:

Result : irritating

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Components:

ethyl acetate:

Result : Eye irritation

butanone:

Result : Eye irritation

4-methylpentan-2-one:

Result : Eye irritation

4-isocyanatosulphonyltoluene:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

MOBIHEL 2K HARDENER 750W

Version 1.2 Revision Date: 10.09.2025 SDS Number: MAT000477693
AU/EN

Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

Components:**Hexamethylene-di-isocyanate, polymer:**

Result : Probability or evidence of skin sensitisation in humans

4-isocyanatosulphonyltoluene:

Result : Probability of respiratory sensitisation in humans based on animal testing

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:**4-methylpentan-2-one:**

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:**toluene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:**Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

butanone:

Assessment : May cause drowsiness or dizziness.

MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 29.11.2023
1.2	10.09.2025	MAT000477693 AU/EN	Date of first issue: 16.11.2023

4-methylpentan-2-one:

Assessment : May cause respiratory irritation.

toluene:

Assessment : May cause drowsiness or dizziness.

4-isocyanatosulphonyltoluene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:**toluene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:**toluene:**

May be fatal if swallowed and enters airways.

Further information**Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l
Exposure time: 72 h

MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 29.11.2023
1.2	10.09.2025	MAT000477693 AU/EN	Date of first issue: 16.11.2023

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

butanone:

Toxicity to fish : LC50 (Fish): > 1,000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

4-methylpentan-2-one:

Toxicity to fish : LC50 (Fish): >= 100 - 1,000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 100 - 1,000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 100 - 1,000 mg/l

toluene:**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability**Components:****n-butyl acetate:**

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d pH: 8
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

Bioaccumulative potential**Components:****ethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 0.6

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Remarks: Bioaccumulation is unlikely.

MOBIHEL 2K HARDENER 750W

Version
1.2Revision Date:
10.09.2025SDS Number:
MAT000477693
AU/ENDate of last issue: 29.11.2023
Date of first issue: 16.11.2023Partition coefficient: n-
octanol/water : log Pow: 1.81**butanone:**Partition coefficient: n-
octanol/water : log Pow: 0.29**4-methylpentan-2-one:**Partition coefficient: n-
octanol/water : log Pow: 1.19**toluene:**Partition coefficient: n-
octanol/water : log Pow: 2.65**Mobility in soil**

No data available

Other adverse effects**Product:**Additional ecological infor-
mation : No data available**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemi-
cal or used container.
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : 3

MOBIHEL 2K HARDENER 750W

Version 1.2 Revision Date: 10.09.2025 SDS Number: MAT000477693
AU/EN

Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : 3
Hazchem Code : •3YE
Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard) Instrument : Schedule 7
Prohibition/Licensing Requirements

: There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 29.11.2023
1.2	10.09.2025	MAT000477693 AU/EN	Date of first issue: 16.11.2023

SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision Date : 10.09.2025

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 AU OEL / TWA : Exposure standard - time weighted average
 AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

SAFETY DATA SHEET



MOBIHEL 2K HARDENER 750W

Version
1.2

Revision Date:
10.09.2025

SDS Number:
MAT000477693
AU/EN

Date of last issue: 29.11.2023
Date of first issue: 16.11.2023

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.