

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

**SECTION 1: IDENTIFICATION**

Product name : MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Product code : 40211803

**Details of the supplier of the safety data sheet**

Company : Helios Coatings Australia Pty Ltd  
50 Clapham Road  
SEFTON NSW 2162  
Australia

Telephone : 61 2 9645 3188  
E-mail address Responsible/issuing person : 61 2 9645 3188  
info@helioscoatings.com.au

**Emergency telephone number**

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Skin corrosion/irritation : Category 2

Reproductive toxicity : Category 2

**GHS label elements**

Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

P243 Take action to prevent static discharges.  
 P264 Wash skin thoroughly after handling.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Components**

Chemical name	CAS-No.	Concentration (% w/w)
calcium carbonate	471-34-1	>= 10 -< 30
talc	14807-96-6	>= 10 -< 30
n-butyl acetate	123-86-4	>= 10 -< 20
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	>= 1 -< 10
barium sulphate, natural	7727-43-7	< 10
titanium dioxide	13463-67-7	< 10
Hydrocarbons, C9 aromatics	128601-23-0	>= 1 -< 10
toluene	108-88-3	>= 3 -< 10
Hexanoic acid, 2-ethyl-, zinc salt, basic	85203-81-2	< 3

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.

**MOBIHEL 4:1 HS COMPACTPRIMER PLUS**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

---

In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	None known.
Notes to physician	:	Treat symptomatically.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	No hazardous combustion products are known
Specific extinguishing methods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Hazchem Code	:	•3Y

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
---	---	---

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version  
1.1Revision Date:  
15.10.2025SDS Number:  
MAT0GA05\_068  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

Calcium carbonate	471-34-1	TWA	10 mg/m <sup>3</sup> (Calcium carbonate)	AU OEL
Talc	14807-96-6	TWA	2.5 mg/m <sup>3</sup>	AU OEL
		TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
n-butyl acetate	123-86-4	STEL	200 ppm 950 mg/m <sup>3</sup>	AU OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	80 ppm 350 mg/m <sup>3</sup>	AU OEL
		STEL	150 ppm 655 mg/m <sup>3</sup>	AU OEL
		TWA	20 ppm	ACGIH
barium sulfate	7727-43-7	TWA	10 mg/m <sup>3</sup>	AU OEL
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
titanium dioxide	13463-67-7	TWA	10 mg/m <sup>3</sup>	AU OEL
		TWA (Respirable particulate matter)	0.2 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
toluene	108-88-3	TWA	50 ppm 191 mg/m <sup>3</sup>	AU OEL
	Further information: Skin absorption			
		STEL	150 ppm 574 mg/m <sup>3</sup>	AU OEL
	Further information: Skin absorption			
		TWA	20 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to	0.02 mg/l	ACGIH

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version  
1.1Revision Date:  
15.10.2025SDS Number:  
MAT0GA05\_068  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

				last shift of work- week		BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI

**Personal protective equipment**

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapour type
- Hand protection
- Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |  
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |  
Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Colour : white  
black

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

---

grey

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : -78.0 °C  
(calculation method (principal components, lowest value))

Boiling point/boiling range : 126 °C(calculation method (principal components, lowest value))

Flash point : 29 °C  
Method: ISO 3679, closed cup

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper flammability limit : 7.5 %(V)

Lower explosion limit / Lower flammability limit : 1.1 %(V)

Vapour pressure : < 1,100 hPa (50 °C)

Relative vapour density : 4

Relative density : 1.52

Density : 1.425 - 1.535 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: < 4

Auto-ignition temperature : 425 °C

Decomposition temperature : No decomposition if stored and applied as directed.  
Hazardous decomposition products formed under fire conditions.

Viscosity  
Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C)

Flow time : > 60 s (23 °C)

**MOBIHEL 4:1 HS COMPACTPRIMER PLUS**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

---

Cross section: 6 mm  
Method: ISO 2431

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2004/42/EC)  
540 g/l

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Incompatible with strong acids and bases.

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

**Components:****n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  5,000 mg/kg

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  8,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

---

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version 1.1      Revision Date: 15.10.2025      SDS Number: MAT0GA05\_068 AU/EN      Date of last issue: 16.11.2023  
Date of first issue: 16.11.2023

---

**Hydrocarbons, C9 aromatics:**

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

**toluene:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation****Product:**

Remarks : May cause skin irritation in susceptible persons.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

**toluene:**

Result : irritating

**Serious eye damage/eye irritation****Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

**Hexanoic acid, 2-ethyl-, zinc salt, basic:**

Result : Eye irritation

**Chronic toxicity****Reproductive toxicity****Components:****toluene:**

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version  
1.1Revision Date:  
15.10.2025SDS Number:  
MAT0GA05\_068  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments.

**Hexanoic acid, 2-ethyl-, zinc salt, basic:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure****Components:****n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

**Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**toluene:**

Assessment : May cause drowsiness or dizziness.

**STOT - repeated exposure****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**toluene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version 1.1      Revision Date: 15.10.2025      SDS Number: MAT0GA05\_068 AU/EN      Date of last issue: 16.11.2023  
Date of first issue: 16.11.2023

---

**toluene:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

**Hydrocarbons, C9 aromatics:**

Toxicity to fish : LC50 (Fish): >= 9.2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): >= 3.2 mg/l  
Exposure time: 48 h

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**toluene:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

---

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version 1.1      Revision Date: 15.10.2025      SDS Number: MAT0GA05\_068 AU/EN      Date of last issue: 16.11.2023      Date of first issue: 16.11.2023

---

**Hexanoic acid, 2-ethyl-, zinc salt, basic:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability****Components:****n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d pH: 8  
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**Bioaccumulative potential****Components:****n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

**Hydrocarbons, C9 aromatics:**

Partition coefficient: n-octanol/water : log Pow: < 4

**toluene:**

Partition coefficient: n-octanol/water : log Pow: 2.65

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version  
1.1Revision Date:  
15.10.2025SDS Number:  
MAT0GA05\_068  
AU/ENDate of last issue: 16.11.2023  
Date of first issue: 16.11.2023**Mobility in soil****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

**Hydrocarbons, C9 aromatics:**

Mobility : Medium: Air  
Content: 92.9 %

Medium: Water  
Content: 3.5 %

Medium: Soil  
Content: 1.9 %

Medium: Sediment  
Content: 1.8 %

Distribution among environmental compartments : Koc: 1.71 - 14.70  
Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

## SECTION 14. TRANSPORT INFORMATION

## International Regulations

**UNRTDG**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 Environmentally hazardous : no

**IATA-DGR**

UN/ID No. : UN 1263  
 Proper shipping name : Paint  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 Hazchem Code : •3Y  
 Environmentally hazardous : no

**Special precautions for user**

Remarks : Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3  
 Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3; "transport acc. IMDG-code 2.3.2.5"

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

**MOBIHEL 4:1 HS COMPACTPRIMER PLUS**

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard) Instrument	: Schedule 7
Prohibition/Licensing Requirements	: There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

**SECTION 16: ANY OTHER RELEVANT INFORMATION**

Revision Date	: 15.10.2025
Date format	: dd.mm.yyyy

**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
AU OEL	: Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
AU OEL / TWA	: Exposure standard - time weighted average
AU OEL / STEL	: Exposure standard - short term exposure limit

AiIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

## MOBIHEL 4:1 HS COMPACTPRIMER PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 16.11.2023
1.1	15.10.2025	MAT0GA05_068 AU/EN	Date of first issue: 16.11.2023

---

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.