

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL THINNER FOR BASE 3100

Product code : 41825904

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions
on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healthcare Professionals 01 809 2566

01 809 2566 Healthcare Professionals 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version 1.0	Revision Date: 15.05.2024	SDS Number: MAT000418259 IE/EN	Date of last issue: - Date of first issue: 15.05.2024
----------------	------------------------------	--------------------------------------	--

Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :    

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version 1.0 Revision Date: 15.05.2024 SDS Number: MAT000418259 IE/EN Date of last issue: -
Date of first issue: 15.05.2024

P331 ing. Immediately call a POISON CENTER/ doctor.
Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or
alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics
reaction mixture of ethylbenzene, m-xylene and p-xylene
butyl glycollate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 30 - < 50
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 30 - < 50
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version 1.0 Revision Date: 15.05.2024 SDS Number: MAT000418259 IE/EN Date of last issue: -
Date of first issue: 15.05.2024

		STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	
butyl glycollate	7397-62-8 230-991-7 01-2119514685-36	Eye Dam. 1; H318 Repr. 2; H361	>= 3 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version
1.0

Revision Date:
15.05.2024

SDS Number:
MAT000418259
IE/EN

Date of last issue: -
Date of first issue: 15.05.2024

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
n-butyl acetate	123-86-4	OELV - 8 hrs (TWA)	50 ppm 241 mg/m ³	IE OEL	
		OELV - 15 min (STEL)	150 ppm 723 mg/m ³	IE OEL	
		STEL	150 ppm 723 mg/m ³	2019/1831/EU	
	Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/EU	
	Further information: Indicative				
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	OELV - 8 hrs (TWA)	50 ppm 221 mg/m ³	IE OEL	
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	100 ppm 442 mg/m ³	IE OEL	
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body				
		TWA	50 ppm 221 mg/m ³	2000/39/EC	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m ³	2000/39/EC	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term systemic effects	48 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version
1.0

Revision Date:
15.05.2024

SDS Number:
MAT000418259
IE/EN

Date of last issue: -
Date of first issue: 15.05.2024

	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	12 mg/m ³
	Consumers	Inhalation	Long-term local effects	35.7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	185 mg/m ³
	Workers	Dermal	Long-term systemic effects	208 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	125 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
	Consumers	Inhalation	Long-term local effects	65.3 mg/m ³
	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Acute local effects	289 mg/m ³
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m ³
	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic	16 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version
1.0

Revision Date:
15.05.2024

SDS Number:
MAT000418259
IE/EN

Date of last issue: -
Date of first issue: 15.05.2024

			effects	bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
butyl glycollate	Workers	Inhalation	Long-term systemic effects	58.8 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	17.4 mg/m ³
	Consumers	Inhalation	Long-term local effects	17.4 mg/m ³
	Consumers	Dermal	Long-term local effects	0.11 mg/cm ²
	Consumers	Oral	Long-term systemic effects	4.2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	41.7 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	25 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Intermittent use/release	0.327 mg/l
butyl glycollate	Soil	0.0112 mg/kg dry weight (d.w.)
	Marine water	0.005 mg/l
	Fresh water	0.05 mg/l
	Marine sediment	0.0203 mg/kg dry weight (d.w.)
	Fresh water sediment	0.203 mg/kg dry weight (d.w.)
	Sewage treatment plant	232 mg/l
	Intermittent use/release	0.5 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |
Viton® (> 0,6 mm; < 240 min); ISO EN374 |
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

Melting point/freezing point	:	-78.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	80 - 110 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	7.5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1.1 %(V) (calculation method (principal components, highest value))
Flash point	:	25 °C
Ignition temperature	:	405 °C(calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if used as directed. Hazardous decomposition products formed under fire conditions.
pH	:	Not applicable
Viscosity Viscosity, kinematic	:	< 20.5 mm ² /s (40 °C)
Solubility(ies) Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	log Pow: 2.77 - 3.15(calculation method (principal components, highest value))
Vapour pressure	:	< 1,100 hPa(calculation method (principal components, highest value)) (50 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

Relative density	:	0.93(calculation method (principal components, highest value))
Density	:	0.836 g/cm ³
Relative vapour density	:	4(calculation method (principal components, lowest value))

9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Sustains combustion
Evaporation rate	:	No data available
VOC	:	(Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)) 100 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No decomposition if stored and applied as directed.
---------------------	---	---

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

10.5 Incompatible materials

Materials to avoid	:	Incompatible with strong acids and bases.
--------------------	---	---

10.6 Hazardous decomposition products

Adequate ventilation is required.
Heating can release vapours which can be ignited.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity	:	LD50 Oral (Rat): \geq 10,760 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): \geq 5,000 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity	:	LD50 Oral (Rat): \geq 8,700 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 27.14 mg/l Test atmosphere: vapour
Acute dermal toxicity	:	Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks	:	Extremely corrosive and destructive to tissue.
---------	---	--

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result	:	irritating
--------	---	------------

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks	:	May cause irreversible eye damage.
---------	---	------------------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version
1.0

Revision Date:
15.05.2024

SDS Number:
MAT000418259
IE/EN

Date of last issue: -
Date of first issue: 15.05.2024

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

butyl glycollate:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

butyl glycollate:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility ,and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): $\geq 1 - 10$ mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): $\geq 1 - 10$ mg/l

Toxicity to microorganisms : EC50 (Bacteria): $\geq 1 - 100$ mg/l

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25.9
Bioaccumulation is unlikely.

Partition coefficient: n-
octanol/water : log Pow: 2.77 - 3.15

12.4 Mobility in soil

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environ-
mental compartments : Koc: 537, log Koc: 2.73
Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-
mation : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00, wastes from MFSU and removal of paint and varnish
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal packaging waste)
15 01 10, packaging containing residues of or contaminated by hazardous substances
HP3, Flammable
HP4, Irritant - skin irritation and eye damage
HP5, Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP10, Toxic for reproduction

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version 1.0 Revision Date: 15.05.2024 SDS Number: MAT000418259 IE/EN Date of last issue: -
Date of first issue: 15.05.2024

IATA : Paint related material

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

dangerous substances.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 100 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361	: Suspected of damaging fertility or the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	15.05.2024	MAT000418259 IE/EN	Date of first issue: 15.05.2024

IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2

2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL) : Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
Repr. 2	H361

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL THINNER FOR BASE 3100

Version 1.0	Revision Date: 15.05.2024	SDS Number: MAT000418259 IE/EN	Date of last issue: - Date of first issue: 15.05.2024
----------------	------------------------------	--------------------------------------	--

STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.