



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

system

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 Use only outdoors or in a well-ventilated area.

#### Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Hazardous components which must be listed on the label:

n-butyl acetate  
Hydrocarbons, C9 aromatics  
1-methoxy-2-propanol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 30
Hydrocarbons, C9 aromatics	- 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
1-methoxy-2-propanol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9 01-2120140278-58		>= 1 - < 10

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

---

- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.
- May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
		Further information: Indicative		
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
		Further information: Indicative		
		OELV - 8 hrs (TWA)	50 ppm 241 mg/m <sup>3</sup>	IE OEL
		OELV - 15 min (STEL)	150 ppm 723 mg/m <sup>3</sup>	IE OEL
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respirable dust)	4 mg/m <sup>3</sup>	IE OEL
		OELV - 8 hrs (TWA) (inhalable)	10 mg/m <sup>3</sup>	IE OEL

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

Talc	14807-96-6	dust) OELV - 8 hrs (TWA) (Respirable dust)	0.8 mg/m <sup>3</sup>	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m <sup>3</sup>	IE OEL
		TWA (Respirable dust)	0.1 mg/m <sup>3</sup>	2004/37/EC
Further information: Carcinogens or mutagens				
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	150 ppm 568 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		OELV - 8 hrs (TWA)	100 ppm 375 mg/m <sup>3</sup>	IE OEL
		OELV - 15 min (STEL)	150 ppm 568 mg/m <sup>3</sup>	IE OEL

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic ef-	11 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Oral	Long-term systemic effects	150 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term exposure	32 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2.16 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	3.6 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	1.08 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	1.8 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term local effects	2.27 mg/cm <sup>2</sup>
	Workers	Dermal	Long-term local effects	4.54 mg/cm <sup>2</sup>
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local effects	4.26 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	1.06 mg/m <sup>3</sup>
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	553.5 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	553.5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	43.9 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
Talc	Marine water	141.26 mg/l
	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry weight (d.w.)
	Intermittent use/release	597.97 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
1-methoxy-2-propanol	Soil	4.59 mg/kg dry weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
	Marine sediment	5.2 mg/kg dry weight (d.w.)
	Fresh water sediment	52.3 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
Sulfonic acids, C10-21-alkane, Ph esters	Soil	27.1 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

---

Gloves	:	Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374   Viton® (> 0,6 mm; < 240 min); ISO EN374   PE laminate (> 0,1 mm; < 240 min); ISO EN374
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	No personal respiratory protective equipment normally required.
Protective measures	:	Wash thoroughly after handling. Avoid contact with skin, eyes and clothing. Keep away from food, drink and animal feedingstuffs.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Form	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/freezing point	:	-78.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	126 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	7.5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1.2 %(V) (calculation method (principal components, highest value))

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

---

Flash point	:	29 °C (calculation method (principal components, lowest value))
Ignition temperature	:	425 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	:	No data available
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (40 °C)
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: < 4 (calculation method (principal components, highest value))
Vapour pressure	:	13 hPa (calculation method (principal components, highest value))
Relative density	:	No data available
Density	:	1.10 - 1.25 g/cm <sup>3</sup> Method: ISO 2811
Relative vapour density	:	No data available

### 9.2 Other information

Explosives	:	Not applicable
Oxidizing properties	:	Sustains combustion
VOC	:	(Directive 2004/42/EC) 500 g/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.  
Not classified due to lack of data.

##### Components:

##### n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat):  $\geq 10,760$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq 5,000$  mg/kg

##### Hydrocarbons, C9 aromatics:

Acute dermal toxicity : LD50 (Rabbit):  $> 3,160$  mg/kg

##### 1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit):  $> 2,000$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $> 2,000$  mg/kg

##### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

---

Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Not classified based on available information.  
Not classified due to lack of data.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Skin sensitisation**

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified due to lack of data.

### **Germ cell mutagenicity**

Not classified based on available information.  
Not classified due to lack of data.

### **Carcinogenicity**

Not classified based on available information.  
Not classified due to lack of data.

### **Reproductive toxicity**

Not classified based on available information.  
Not classified due to lack of data.

### **STOT - single exposure**

May cause drowsiness or dizziness.  
May cause drowsiness or dizziness.

### **Components:**

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

#### **1-methoxy-2-propanol:**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.  
Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

### Aspiration hazard

Not classified based on available information.  
Not classified due to lack of data.

### Components:

#### Hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### Endocrine disrupting properties

Not classified due to lack of data.

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

### Components:

#### n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

#### Hydrocarbons, C9 aromatics:

Toxicity to fish : LC50 (Fish): >= 9.2 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

---

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 3.2$  mg/l  
Exposure time: 48 h

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### 1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish):  $> 1,000$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $> 1,000$  mg/l

Toxicity to algae/aquatic plants : LC50 (algae):  $> 1,000$  mg/l

## 12.2 Persistence and degradability

### Components:

#### n-butyl acetate:

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

## 12.3 Bioaccumulative potential

### Components:

#### n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

#### Hydrocarbons, C9 aromatics:

Partition coefficient: n-octanol/water : log Pow:  $< 4$

#### 1-methoxy-2-propanol:

Partition coefficient: n-octanol/water : log Pow: -0.437

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

---

### 12.4 Mobility in soil

#### Components:

#### Hydrocarbons, C9 aromatics:

Mobility	:	Medium: Air Content: 92.9 %
	:	Medium: Water Content: 3.5 %
	:	Medium: Soil Content: 1.9 %
	:	Medium: Sediment Content: 1.8 %
Distribution among environmental compartments	:	Koc: 1.71 - 14.70 Mobile in soils

The product is insoluble and floats on water.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
------------	---	--

### 12.6 Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

### 12.7 Other adverse effects

#### Product:

Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.
-----------------------------------	---	---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- |                        |   |   |
|------------------------|---|---|
| Product                | : | The product should not be allowed to enter drains, water courses or the soil.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Send to a licensed waste management company.  |
| Contaminated packaging | : | Empty remaining contents.<br>Dispose of as unused product.<br>Do not re-use empty containers.<br>Do not burn, or use a cutting torch on, the empty drum.  |
| Waste Code             | : | 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS<br>08 01 00, wastes from MFSU and removal of paint and varnish<br>08 01 11, waste paint and varnish containing organic solvents or other hazardous substances<br>15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED<br>15 01 00, packaging (including separately collected municipal packaging waste)<br>15 01 10, packaging containing residues of or contaminated by hazardous substances<br>HP3, Flammable<br>HP14, Ecotoxic |

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- |      |   |         |
|------|---|---------|
| ADN  | : | UN 1263 |
| ADR  | : | UN 1263 |
| RID  | : | UN 1263 |
| IMDG | : | UN 1263 |
| IATA | : | UN 1263 |

#### 14.2 UN proper shipping name

- |     |   |       |
|-----|---|-------|
| ADN | : | PAINT |
| ADR | : | PAINT |
| RID | : | PAINT |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

---

**IMDG** : PAINT  
**IATA** : Paint

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5)  
IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (transport acc. IMDG-code 2.3.2.5)

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:

- Number on list 3
- Number on list 40  
This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.
- Number on list 75  
If you intend to use this product as tattoo ink, please contact your vendor.
- Number on list 78:  
3909 amino

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

synthetic polymer microparticles  
(SPM) content: 0.45 %  
The synthetic polymer microparticles  
supplied is subject to conditions laid  
down by entry 78 of Annex XVII to  
Regulation (EC) No 1907/2006 of  
the European Parliament and of the  
Council

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable  
Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable  
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable  
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable  
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 500 g/l

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Liq. : Flammable liquids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version 2.0      Revision Date: 21.01.2026      SDS Number: MAT0GA00\_023IE/EN      Date of last issue: 20.07.2023  
Date of first issue: 20.07.2023

---

STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## TESSAROL enamel for tin plated sheet metal

Version	Revision Date:	SDS Number:	Date of last issue: 20.07.2023
2.0	21.01.2026	MAT0GA00_023IE/ EN	Date of first issue: 20.07.2023

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

Material codes (bulk) for which the SDS is valid	477873 , 477874, 477875, 477876, 477877, 477878, 477879, 477880
--	---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.