

TESSAROL PRIMER UNI whiteVersion
1.2Revision Date:
28.01.2026SDS Number:
MAT000419636
IL/ENDate of last issue: 30.01.2024
Date of first issue: 22.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : TESSAROL PRIMER UNI white

Product code : 41963663

1.2 Relevant identified uses of the substance or mixture and uses advised againstUse of the Sub-
stance/Mixture : SU19: Building and construction work
PROC10, PROC11: Roller application or brushing, Non indus-
trial spraying
PC9a: Coatings and paints, thinners, paint removersRecommended restrictions : Professional and consumer use of coatings
on use**1.3 Details of the supplier of the safety data sheet**Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si**1.4 Emergency telephone number**

Ambulance (972) 101

Israel Poison Information Center +972 4 854 19 00

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

posure, Category 3, Central nervous system

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics
1-methoxy-2-propanol

Additional Labelling

EUH208 Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	- 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 20 - < 30
1-methoxypropan-2-ol	107-98-2 203-539-1 603-064-00-3 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2.5
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.1 - < 0.25
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360D	>= 0.1 - < 0.3
zinc 5-nitroisophthalate	60580-61-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0.1 - < 0.25
cobalt bis(2-ethylhexanoate)	136-52-7 205-250-6 01-2119524678-29	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360D Aquatic Acute 1;	>= 0.025 - < 0.1

TESSAROL PRIMER UNI white

Version
1.2Revision Date:
28.01.2026SDS Number:
MAT000419636
IL/ENDate of last issue: 30.01.2024
Date of first issue: 22.11.2023

		H400 Aquatic Chronic 3; H412	
Substances with a workplace exposure limit :			
talc	14807-96-6 238-877-9 01-2120140278-58		>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (Respirable particulate matter)	0.2 mg/m ³ (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
barium sulfate	7727-43-7	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Talc	14807-96-6	TWA (Respirable dust)	0.1 mg/m ³	2004/37/EC
	Further information: Carcinogens or mutagens			
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH
cobalt bis(2-ethylhexanoate)	136-52-7	TLV-TWA	0.02 mg/m ³ (Cobalt)	IL OEL
		TWA (Inhalable particulate matter)	0.02 mg/m ³ (Cobalt)	ACGIH

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
cobalt bis(2-ethylhexanoate)	136-52-7	Cobalt (Cobalt): 15 µg/l	End of shift at end of workweek	ACGIH BEI

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

	(Urine)		
	Cobalt (Cobalt): (Urine)	End of shift at end of workweek	ACGIH BEI

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics	Workers	Inhalation	Long-term systemic effects	1500 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	900 mg/m ³
	Workers	Dermal	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	300 mg/kg bw/day
titanium dioxide	Consumers	Oral	Long-term systemic effects	300 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10 mg/m ³
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
Calcium carbonate	Workers	Inhalation	Long-term local effects	4.26 mg/m ³
	Consumers	Inhalation	Long-term local effects	1.06 mg/m ³
barium sulfate	Consumers	Inhalation	Long-term systemic effects	10 mg/m ³
	Workers	Inhalation	Long-term systemic effects	10 mg/m ³
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2.16 mg/m ³
	Workers	Inhalation	Acute local effects	3.6 mg/m ³
	Consumers	Inhalation	Acute systemic effects	1.08 mg/m ³
	Consumers	Inhalation	Acute local effects	1.8 mg/m ³
	Consumers	Dermal	Long-term local effects	2.27 mg/cm ²
	Workers	Dermal	Long-term local effects	4.54 mg/cm ²
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day

TESSAROL PRIMER UNI white

Version
1.2Revision Date:
28.01.2026SDS Number:
MAT000419636
IL/ENDate of last issue: 30.01.2024
Date of first issue: 22.11.2023

	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
1-methoxy-2-propanol	Workers	Inhalation	Long-term systemic effects	369 mg/m ³
	Workers	Inhalation	Acute systemic effects	553.5 mg/m ³
	Workers	Inhalation	Acute local effects	553.5 mg/m ³
	Workers	Inhalation	Long-term systemic effects	43.9 mg/m ³
	Workers	Dermal	Long-term systemic effects	183 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	78 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	33 mg/kg bw/day
trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m ³
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Inhalation	Long-term local effects	0.5 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m ³
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
strontium bis(2-ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.730 mg/m ³
	Workers	Dermal	Long-term systemic effects	0.410 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.180 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0.210 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.210 mg/kg bw/day
cobalt bis(2-ethylhexanoate)	Workers	Inhalation	Long-term systemic effects	0.2351 mg/m ³

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

	Consumers	Inhalation	Long-term local effects	0.037 mg/m ³
	Consumers	Oral	Long-term systemic effects	0.0276 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
Calcium carbonate	Sewage treatment plant	100 mg/l
barium sulfate	Soil	207.7 mg/kg dry weight (d.w.)
	Fresh water	0.115 mg/l
	Fresh water sediment	600.4 mg/kg dry weight (d.w.)
	Sewage treatment plant	62.2 mg/l
	Talc	Marine water
1-methoxy-2-propanol	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry weight (d.w.)
	Intermittent use/release	597.97 mg/l
	Soil	4.59 mg/kg dry weight (d.w.)
	Marine water	1 mg/l
	Fresh water	10 mg/l
trizinc bis(orthophosphate)	Marine sediment	5.2 mg/kg dry weight (d.w.)
	Fresh water sediment	52.3 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	100 mg/l
	Soil	35.6 mg/kg dry weight (d.w.)
	Marine water	0.0061 mg/l
trizinc bis(orthophosphate)	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry weight (d.w.)

TESSAROL PRIMER UNI white

Version
1.2Revision Date:
28.01.2026SDS Number:
MAT000419636
IL/ENDate of last issue: 30.01.2024
Date of first issue: 22.11.2023

		weight (d.w.)
	Sewage treatment plant	0.1 mg/l
zinc oxide	Soil	35.6 mg/kg dry weight (d.w.)
	Marine water	0.0061 mg/l
	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.1 mg/l
strontium bis(2-ethylhexanoate)	Fresh water	0.360 - 0.440 mg/l
	Intermittent use/release	0.493 - 0.610 mg/l
	Marine water	0.036 - 0.040 mg/l
	Sewage treatment plant	71.7 - 88.52 mg/l
	Fresh water sediment	6.37 - 7.86 mg/kg dry weight (d.w.)
	Marine sediment	0.637 - 0.790 mg/kg dry weight (d.w.)
	Soil	1.06 - 1.31 mg/kg dry weight (d.w.)
zinc 5-nitroisophthalate	Fresh water	0.0206 - 0.0808 mg/l
	Marine water	0.0061 - 0.0239 mg/l
	Sewage treatment plant	0.100 - 0.3922 mg/l
	Fresh water sediment	117.8 - 462 mg/kg dry weight (d.w.)
	Marine sediment	56.5 - 221 mg/kg dry weight (d.w.)
	Soil	56.5 - 221 mg/kg dry weight (d.w.)
cobalt bis(2-ethylhexanoate)	Soil	10.9 mg/kg dry weight (d.w.)
	Marine water	0.00236 mg/l
	Fresh water	0.0006 mg/l
	Marine sediment	9.5 mg/kg dry weight (d.w.)
	Fresh water sediment	9.5 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.37 mg/l

TESSAROL PRIMER UNI white

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2024
1.2	28.01.2026	MAT000419636 IL/EN	Date of first issue: 22.11.2023

8.2 Exposure controls**Individual protection measures, such as personal protective equipment (PPE)**

Eye/face protection	:	Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection	:	
Gloves	:	Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 Viton® (> 0,6 mm; < 240 min); ISO EN374 PE laminate (> 0,1 mm; < 240 min); ISO EN374
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Combined particulates and organic vapour type (A-P)
Protective measures	:	Wash thoroughly after handling. Avoid contact with skin, eyes and clothing. Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state	:	liquid
Form	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	-97.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	119 °C (calculation method (principal components, lowest value))
Flash point	:	29 °C

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	6 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	0.7 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	11.5 hPa (calculation method (principal components, highest value)) (20 °C)
Relative vapour density	:	3.11 (calculation method (principal components, highest value)) (Air = 1.0)
Relative density	:	1.47 (calculation method (principal components, highest value))
Density	:	1.38 - 1.42 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: -0.437 (calculation method (principal components, highest value))
Ignition temperature	:	287 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C)
Flow time	:	> 60 s at 23 °C

TESSAROL PRIMER UNI white

Version
1.2

Revision Date:
28.01.2026

SDS Number:
MAT000419636
IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

Cross section: 6 mm
Method: ISO 2431

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

9.2 Other information

No data available

VOC : (Directive 2004/42/EC)
500 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

Components:**hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:**

Acute oral toxicity : LD50 Oral: 5000 milligram per kilogram

Acute inhalation toxicity : LC50 (Rat): 5.61 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50: 2000 milligram per kilogram

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral (Rabbit): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

trizinc bis(orthophosphate):

Acute oral toxicity : LD50 (Rat): 5,000 mg/kg

strontium bis(2-ethylhexanoate):

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Skin corrosion/irritation

Not classified based on available information.
Not classified due to lack of data.

Components:**strontium bis(2-ethylhexanoate):**

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.
Not classified due to lack of data.

Components:**strontium bis(2-ethylhexanoate):**

Result : Corrosive

cobalt bis(2-ethylhexanoate):

Result : Eye irritation

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Components:

cobalt bis(2-ethylhexanoate):

Result : The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.
Not classified due to lack of data.

Carcinogenicity

Not classified based on available information.
Not classified due to lack of data.

Reproductive toxicity

Not classified based on available information.
Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.
May cause drowsiness or dizziness.

Components:

hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

1-methoxy-2-propanol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.
Not classified due to lack of data.

Aspiration hazard

Not classified based on available information.
Not classified due to lack of data.

TESSAROL PRIMER UNI white

Version
1.2Revision Date:
28.01.2026SDS Number:
MAT000419636
IL/ENDate of last issue: 30.01.2024
Date of first issue: 22.11.2023**Components:****hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics:**

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information**12.1 Toxicity****Components:****1-methoxy-2-propanol:**Toxicity to fish : LC50 (Fish): > 1,000 mg/l
Exposure time: 96 hToxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1,000 mg/l
aquatic invertebratesToxicity to algae/aquatic : LC50 (algae): > 1,000 mg/l
plants**trizinc bis(orthophosphate):****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

zinc oxide:Toxicity to fish : LC50 (Danio rerio (zebra fish)): >= 1.793 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia (water flea)): >= 2.6 mg/l
aquatic invertebrates
Exposure time: 48 hToxicity to algae/aquatic : IC50 (Desmodesmus subspicatus (green algae)): >= 0.136
plants
mg/l
Exposure time: 72 h

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636
IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

zinc 5-nitroisophthalate:**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

cobalt bis(2-ethylhexanoate):**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability**Components:****zinc oxide:**

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential**Components:****1-methoxy-2-propanol:**

Partition coefficient: n-octanol/water : log Pow: -0.437

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects**Product:**

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

-
- Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
- Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 UN number**

- ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

- ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN		
Packing group	: III	
Classification Code	: F1	
Hazard Identification Number	: 30	
Labels	: 3	
ADR		
Packing group	: III	
Classification Code	: F1	
Hazard Identification Number	: 30	
Labels	: 3	
Tunnel restriction code	: (D/E)	
RID		
Packing group	: III	
Classification Code	: F1	
Hazard Identification Number	: 30	
Labels	: 3	
IMDG		
Packing group	: III	
Labels	: 3	
EmS Code	: F-E, <u>S-E</u>	
IATA (Cargo)		
Packing instruction (cargo aircraft)	: 366	
Packing instruction (LQ)	: Y344	
Packing group	: III	
Labels	: Flammable Liquids	
IATA (Passenger)		
Packing instruction (passenger aircraft)	: 355	
Packing instruction (LQ)	: Y344	
Packing group	: III	
Labels	: Flammable Liquids	

14.5 Environmental hazards**ADN**

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (exemption ADR 2.2.3.1.5)
IMDG: Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 (transport acc. IMDG-code 2.3.2.5)

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 500 g/l

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information**Full text of H-Statements**

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

TESSAROL PRIMER UNI white

Version	Revision Date:	SDS Number:	Date of last issue: 30.01.2024
1.2	28.01.2026	MAT000419636 IL/EN	Date of first issue: 22.11.2023

H360D : May damage the unborn child.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III
ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
IL OEL : Israel. Safety at Work Regulations (Environmental monitoring and biological monitoring of workers)
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2004/37/EC / TWA : Long term exposure limit
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
IL OEL / TLV-TWA : Threshold Limit Value - Time Weighted (TLV-TWA)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation;

TESSAROL PRIMER UNI white

Version 1.2 Revision Date: 28.01.2026 SDS Number: MAT000419636 IL/EN

Date of last issue: 30.01.2024
Date of first issue: 22.11.2023

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information**Classification of the mixture:**

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.