

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL 2K HARDENER 7700

Product code : 47155401

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions
on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

SECTION 2: Hazards identification



2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| | |
|--|--|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

| | | |
|--------------------------------|---|---|
| Hazard pictograms | : |   |
| Signal word | : | Warning |
| Hazard statements | : | H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. |
| Supplemental Hazard Statements | : | EUH066 Repeated exposure may cause skin dryness or cracking. |
| Precautionary statements | : | Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate

Hexamethylene-di-isocyanate, polymer

Hydrocarbons, C9 aromatics

reaction mixture of ethylbenzene, m-xylene and p-xylene

Additional Labelling

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---------------------------------------|---|---|--------------------------|
| n-butyl acetate | 123-86-4 204-658-1 607-025-00-1 01-2119485493-29 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) | >= 30 - < 50 |
| Hexamethylene diisocyanate, oligomers | 28182-81-2 500-060-2 01-2119485796-17 | Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) | >= 30 - < 50 |
| 2-butoxyethyl acetate | 112-07-2 203-933-3 607-038-00-2 | Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 | >= 2,5 - < 10 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

| | | | |
|---|---|--|---------------|
| Hydrocarbons, C9 aromatics | 01-2119475112-47 64742-95-6 918-668-5 01-2119455851-35 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 2,5 - < 10 |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | - 905-562-9 01-2119555267-33, 01-2119488216-32 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | >= 2,5 - < 10 |
| 2-methoxy-1-methylethyl acetate | 108-65-6 203-603-9 607-195-00-7 01-2119475791-29 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) | >= 1 - < 10 |
| solvent naphtha (petroleum), light aromatic | 64742-95-6 265-199-0 649-356-00-4 01-2119455851-35 | Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 1 - < 2,5 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

- Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.
- May cause an allergic skin reaction.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from moisture.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis | |
|--------------------------------------|--|--|----------------------------------|------------------|--|
| n-butyl acetate | 123-86-4 | TWA | 150 ppm 724 mg/m ³ | GB EH40 | |
| | | STEL | 200 ppm 966 mg/m ³ | GB EH40 | |
| | | STEL | 150 ppm 723 mg/m ³ | 2019/1831/E U | |
| | Further information: Indicative | | | | |
| | | TWA | 50 ppm 241 mg/m ³ | 2019/1831/E U | |
| | Further information: Indicative | | | | |
| Hexamethylene-di-isocyanate, polymer | 28182-81-2 | TWA | 0,02 mg/m ³ (NCO) | GB EH40 | |
| | | Further information: Capable of causing occupational asthma. | | | |
| | | STEL | 0,07 mg/m ³ (NCO) | GB EH40 | |
| | Further information: Capable of causing occupational asthma. | | | | |
| | | TWA | 0,01 mg/m ³ (NCO) | 98/24/EC I | |
| | Further information: Skin, Dermal and respiratory sensitisation, Binding | | | | |
| | | STEL | 0,02 mg/m ³ (NCO) | 98/24/EC I | |
| | Further information: Skin, Dermal and respiratory sensitisation, Binding | | | | |
| 2-butoxyethyl acetate | 112-07-2 | TWA | 20 ppm 133 mg/m ³ | GB EH40 | |
| | | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 50 ppm 332 mg/m ³ | GB EH40 | |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | | |
| | | TWA | 20 ppm 133 mg/m ³ | 2000/39/EC | |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

| | | | | |
|---|--|------|----------------------------------|------------|
| | | STEL | 50 ppm 333 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | TWA | 50 ppm 220 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm 441 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | TWA | 50 ppm 221 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| 2-methoxy-1-methylethyl acetate | 108-65-6 | TWA | 50 ppm 274 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm 548 mg/m ³ | GB EH40 |
| | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | |
| | | STEL | 100 ppm 550 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | TWA | 50 ppm 275 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|-------------------|------------|--------------------|-------------------|---------|
| Hexamethylene-di- | 28182-81-2 | isocyanate-derived | At the end of the | GB EH40 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

| | | | | |
|---|-----------|--|--------------------|----------------|
| isocyanate, polymer | | diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | period of exposure | BAT |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | methyl hippuric acid: 650 Millimoles per mole creatinine (Urine) | After shift | GB EH40 BAT |

Derived No Effect Level (DNEL)

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|-------------------------------------|-----------|-----------------|----------------------------|------------------------|
| n-butyl acetate | Workers | Inhalation | Acute systemic effects | 600 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 600 mg/m ³ |
| | Workers | Inhalation | Long-term systemic effects | 48 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 300 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 300 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 300 mg/m ³ |
| | Consumers | Inhalation | Long-term systemic effects | 12 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 35,7 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 3,4 mg/kg bw/day |
| | Consumers | Dermal | Acute systemic effects | 6 mg/kg bw/day |
| Hexamethylene-diisocyanate, polymer | Consumers | Oral | Long-term systemic effects | 2 mg/kg bw/day |
| | Consumers | Oral | Acute systemic effects | 2 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 7 mg/kg bw/day |
| | Workers | Dermal | Acute systemic effects | 11 mg/kg bw/day |
| Hexamethylene-diisocyanate, polymer | Workers | Inhalation | Long-term local effects | 0,5 mg/m ³ |
| | Workers | Inhalation | Long-term systemic effects | 1 mg/m ³ |
| 2-butoxyethyl acetate | Workers | Inhalation | Long-term systemic effects | 333 mg/m ³ |
| | Consumers | Oral | Long-term systemic effects | 86 mg/kg bw/day |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

| | | | | |
|---|-----------|------------|----------------------------|------------------|
| | Workers | Dermal | Long-term systemic effects | 169 mg/kg bw/day |
| | Workers | Dermal | Acute systemic effects | 120 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 102 mg/kg bw/day |
| | Consumers | Dermal | Acute systemic effects | 72 mg/kg bw/day |
| | Consumers | Oral | Acute systemic effects | 36 mg/kg bw/day |
| Hydrocarbons, C9 aromatics | Workers | Inhalation | Long-term systemic effects | 150 mg/m3 |
| | Workers | Oral | Long-term systemic effects | 150 mg/m3 |
| | Consumers | Inhalation | Long-term exposure | 32 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 25 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 11 mg/kg bw/day |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Workers | Inhalation | Long-term systemic effects | 77 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 65,3 mg/m3 |
| | Workers | Inhalation | Acute systemic effects | 442 mg/m3 |
| | Workers | Inhalation | Acute local effects | 289 mg/m3 |
| | Consumers | Inhalation | Acute systemic effects | 260 mg/m3 |
| | Workers | Inhalation | Long-term local effects | 221 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 14,8 mg/m3 |
| | Consumers | Inhalation | Acute local effects | 260 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 108 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 16 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 180 mg/kg bw/day |
| 2-methoxy-1-methylethyl acetate | Workers | Inhalation | Long-term systemic effects | 275 mg/m3 |
| | Workers | Inhalation | Acute local effects | 550 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 33 mg/m3 |
| | Consumers | Inhalation | Long-term local effects | 33 mg/m3 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

| | | | | |
|--|-----------|------------|----------------------------|------------------|
| | Workers | Dermal | Long-term systemic effects | 796 mg/kg bw/day |
| | Consumers | Dermal | Long-term systemic effects | 320 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 36 mg/kg bw/day |
| Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified | Workers | Inhalation | Long-term systemic effects | 150 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 32 mg/m3 |
| | Consumers | Dermal | Long-term systemic effects | 11 mg/kg bw/day |
| | Workers | Dermal | Long-term systemic effects | 25 mg/kg bw/day |
| | Consumers | Oral | Long-term systemic effects | 11 mg/kg bw/day |

Predicted No Effect Concentration (PNEC)

| Substance name | Environmental Compartment | Value |
|--------------------------------------|---------------------------|--------------------------------|
| n-butyl acetate | Soil | 0,0903 mg/kg dry weight (d.w.) |
| | Marine water | 0,018 mg/l |
| | Fresh water | 0,18 mg/l |
| | Marine sediment | 0,0981 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 0,981 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 35,6 mg/l |
| | Intermittent use/release | 0,36 mg/l |
| Hexamethylene-di-isocyanate, polymer | Soil | 505 mg/kg dry weight (d.w.) |
| | Marine water | 0,01 mg/l |
| | Fresh water | 0,1 mg/l |
| | Marine sediment | 253 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 2530 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 100 mg/l |
| | Intermittent use/release | 1 mg/l |
| 2-butoxyethyl acetate | Soil | 0,415 mg/kg dry weight (d.w.) |
| | Marine water | 0,0304 mg/l |
| | Fresh water | 0,304 mg/l |
| | Marine sediment | 0,203 mg/kg dry weight (d.w.) |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version 3.0 Revision Date: 11.02.2026 SDS Number: MAT000471554 GB/EN Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

| | | |
|---|--------------------------|-------------------------------|
| | Fresh water sediment | 2,03 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 90 mg/l |
| | Intermittent use/release | 0,56 mg/l |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Soil | 2,31 mg/kg dry weight (d.w.) |
| | Marine water | 0,327 mg/l |
| | Fresh water | 0,327 mg/l |
| | Marine sediment | 12,46 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 12,46 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 6,58 mg/l |
| | Intermittent use/release | 0,327 mg/l |
| 2-methoxy-1-methylethyl acetate | Soil | 0,29 mg/kg dry weight (d.w.) |
| | Marine water | 0,0635 mg/l |
| | Fresh water | 0,635 mg/l |
| | Marine sediment | 0,329 mg/kg dry weight (d.w.) |
| | Fresh water sediment | 3,29 mg/kg dry weight (d.w.) |
| | Sewage treatment plant | 100 mg/l |
| | Intermittent use/release | 0,00635 mg/l |

8.2 Exposure controls

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
- Hand protection
- Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |
Viton® (> 0,6 mm; < 240 min); ISO EN374 |
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387
Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Appearance | : liquid |
| Colour | : colourless |
| Odour | : solvent-like |
| Odour Threshold | : No data available |
| pH | : Not applicable |
| Melting point/freezing point | : -80,0 °C (calculation method (principal components, lowest value)) |
| Boiling point/boiling range | : 126 °C (calculation method (principal components, lowest value)) |
| Flash point | : 39 °C |
| Flammability | : Static-accumulating flammable liquid., Combustible Solids |
| Upper explosion limit / Upper flammability limit | : 8,4 %(V) (calculation method (principal components, highest value)) |
| Lower explosion limit / Lower flammability limit | : 0,8 %(V) (calculation method (principal components, highest value)) |
| Vapour pressure | : < 1.100 hPa (calculation method (principal components, highest value)) (50 °C) |
| Relative vapour density | : No data available |
| Relative density | : No data available |
| Density | : 0,971 g/cm ³ |
| Solubility(ies) | |
| Water solubility | : partly miscible |
| Solubility in other solvents | : Description: miscible with most organic solvents |
| Partition coefficient: n- | : log Pow: < 4 (calculation method (principal components, high- |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

octanol/water (est value))

Ignition temperature : 280 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if stored and applied as directed.
Hazardous decomposition products formed under fire conditions.

Viscosity
Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

9.2 Other information

No data available
VOC : (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))
66,75 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.
Not classified due to lack of data.

Product:

| | | |
|---------------------------|---|---|
| Acute oral toxicity | : | Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : | Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method |
| Acute dermal toxicity | : | Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method |

Components:

n-butyl acetate:

| | | |
|-----------------------|---|--------------------------------------|
| Acute oral toxicity | : | LD50 Oral (Rat): \geq 10.760 mg/kg |
| Acute dermal toxicity | : | LD50 (Rabbit): \geq 5.000 mg/kg |

Hexamethylene-di-isocyanate, polymer:

| | | |
|---------------------------|---|--|
| Acute inhalation toxicity | : | Assessment: The component/mixture is moderately toxic after short term inhalation. |
|---------------------------|---|--|

2-butoxyethyl acetate:

| | | |
|---------------------------|---|--|
| Acute oral toxicity | : | Assessment: The component/mixture is moderately toxic after single ingestion. LD50 Oral (Rat): \geq 2.400 mg/kg |
| Acute inhalation toxicity | : | LC50 (Rat): \geq 50 mg/l Exposure time: 2 h Test atmosphere: vapour |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

LD50 (Rabbit): \geq 1.500 mg/kg

Hydrocarbons, C9 aromatics:

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): \geq 8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour

LC0 (Rat): 2000 ppm
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.
Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : May cause skin irritation and/or dermatitis.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

Serious eye damage/eye irritation

Not classified based on available information.

Not classified due to lack of data.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

Hexamethylene-di-isocyanate, polymer:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Not classified due to lack of data.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.
Not classified due to lack of data.

Components:

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.
Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

Hexamethylene-di-isocyanate, polymer:

Assessment : May cause respiratory irritation.

Hydrocarbons, C9 aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

2-methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.
Not classified due to lack of data.

Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not classified based on available information.
Not classified due to lack of data.

Components:

Hydrocarbons, C9 aromatics:

May be fatal if swallowed and enters airways.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

May be fatal if swallowed and enters airways.

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f), at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

2-butoxyethyl acetate:

Toxicity to fish : LC50 (Fish): >= 31 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 142,5 mg/l
Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria): >= 2.800 mg/l

Hydrocarbons, C9 aromatics:

Toxicity to fish : LC50 (Fish): >= 9,2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): >= 3,2 mg/l
Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l
Exposure time: 96 h

NOEC : 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : LC50 : 408 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to fish (Chronic tox- : EC10: 47,5 mg/l
icity)

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): > 1 - 10 mg/l
aquatic invertebrates

Toxicity to microorganisms : EC50 (Bacteria): > 1 - 10 mg/l

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

2-butoxyethyl acetate:

Biodegradability : Result: Biodegradable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

2-methoxy-1-methylethyl acetate:

Biodegradability : Remarks: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,51

Hydrocarbons, C9 aromatics:

Partition coefficient: n-octanol/water : log Pow: < 4

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)
pH: 6,8

12.4 Mobility in soil

Components:

Hydrocarbons, C9 aromatics:

Mobility : Medium: Air
Content: 92,9 %

: Medium: Water

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

Content: 3,5 %

: Medium: Soil
Content: 1,9 %

: Medium: Sediment
Content: 1,8 %

Distribution among environmental compartments : Koc: 1,71 - 14,70
Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73
Remarks: Moderately mobile in soils
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d
Percentage dissipation: 50 % (DT50)

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

- ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

- ADN : PAINT
ADR : PAINT
RID : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

- | | Class | Subsidiary risks |
|------|-------|------------------|
| ADN | : 3 | |
| ADR | : 3 | |
| RID | : 3 | |
| IMDG | : 3 | |
| IATA | : 3 | |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

| | | |
|---|-----|---|
| UK REACH List of restrictions (Annex 17) | : | Conditions of restriction for the following entries should be considered: Number on list 3 Number on list 40 This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes. |
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation | : | Not applicable |
| The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) | : | Not applicable |
| Regulation (EU) No 2024/590 on substances that deplete the ozone layer | : | Not applicable |
| UK REACH List of substances subject to authorisation (Annex XIV) | : | Not applicable |
| GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation | : | Not applicable |
| Control of Major Accident Hazards Regulations 2015 (COMAH) | P5c | FLAMMABLE LIQUIDS |
| Volatile organic compounds | : | Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 66,75 % |

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

| | |
|------|--|
| H226 | : Flammable liquid and vapour. |
| H302 | : Harmful if swallowed. |
| H304 | : May be fatal if swallowed and enters airways. |
| H312 | : Harmful in contact with skin. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H319 | : Causes serious eye irritation. |
| H332 | : Harmful if inhaled. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | |
|--------------------|--|
| Acute Tox. | : Acute toxicity |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Asp. Tox. | : Aspiration hazard |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitisation |
| STOT RE | : Specific target organ toxicity - repeated exposure |
| STOT SE | : Specific target organ toxicity - single exposure |
| 2000/39/EC | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2019/1831/EU | : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| 98/24/EC I | : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| GB EH40 BAT | : UK. Biological monitoring guidance values |
| 2000/39/EC / TWA | : Limit Value - eight hours |
| 2000/39/EC / STEL | : Short term exposure limit |
| 2019/1831/EU / TWA | : Limit Value - eight hours |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

| | | | |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 07.11.2023 |
| 3.0 | 11.02.2026 | MAT000471554 GB/EN | Date of first issue: 08.07.2021 |

| | | |
|---------------------|---|--|
| 2019/1831/EU / STEL | : | Short term exposure limit |
| 98/24/EC I / STEL | : | Limit values Short-term |
| 98/24/EC I / TWA | : | Limit values 8 hours |
| GB EH40 / TWA | : | Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : | Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|--------------|------|
| Flam. Liq. 3 | H226 |
| Skin Sens. 1 | H317 |
| STOT SE 3 | H336 |
| STOT SE 3 | H335 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MOBIHEL 2K HARDENER 7700

Version
3.0

Revision Date:
11.02.2026

SDS Number:
MAT000471554
GB/EN

Date of last issue: 07.11.2023
Date of first issue: 08.07.2021

Aquatic Chronic 3

H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.