

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K HS HARDENER 4100

Product code : 41958313

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Instituto Nacional de Toxicología y Ciencias Forenses Servicio de Información Toxicológica + 34  
91 562 04 20

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Central nervous H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

system

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer  
n-butyl acetate  
Hydrocarbons, C9 aromatics  
hexamethylene-di-isocyanate

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene-di-isocyanate, polymer	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 50 - < 70
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
Hydrocarbons, C9 aromatics	- 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
isobutyl acetate	110-19-0 203-745-1 607-026-00-7 01-2119488971-22	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - < 10
reaction mixture of ethylbenzene, m-xylene and p-xylene	- 905-562-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 2,5 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

	01-2119555267-33, 01-2119488216-32	Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	64742-95-6 265-199-0  649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 2,5 - < 10$
hexamethylene-di-isocyanate	822-06-0 212-485-8  615-011-00-1 01-2119457571-37	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) <hr/> specific concentration limit Resp. Sens. 1; H334 $\geq 0,5 \%$ Skin Sens. 1; H317 $\geq 0,5 \%$	$< 0,1$

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma,

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from moisture.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene-diisocyanate, polymer	28182-81-2	TWA	0,01 mg/m <sup>3</sup> (NCO)	98/24/EC I
			Further information: Skin, Dermal and respiratory sensitisation, Binding	
		STEL	0,02 mg/m <sup>3</sup> (NCO)	98/24/EC I
			Further information: Skin, Dermal and respiratory sensitisation, Binding	
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
			Further information: Indicative	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		VLA-ED	50 ppm 241 mg/m <sup>3</sup>	ES VLA
		VLA-EC	150 ppm 723 mg/m <sup>3</sup>	ES VLA
isobutyl acetate	110-19-0	TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		VLA-EC	150 ppm 723 mg/m <sup>3</sup>	ES VLA
		VLA-ED	50 ppm 241 mg/m <sup>3</sup>	ES VLA
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	VLA-EC	100 ppm 442 mg/m <sup>3</sup>	ES VLA
Further information: Skin				
		VLA-ED	50 ppm 221 mg/m <sup>3</sup>	ES VLA
Further information: Skin				
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
hexamethylene-diisocyanate	822-06-0	VLA-ED	0,005 ppm 0,035 mg/m <sup>3</sup>	ES VLA
Further information: Sensitizer agent				
		TWA	0,01 mg/m <sup>3</sup> (NCO)	98/24/EC I
Further information: Skin, Dermal and respiratory sensitisation, Binding				
		STEL	0,02 mg/m <sup>3</sup> (NCO)	98/24/EC I
Further information: Skin, Dermal and respiratory sensitisation, Binding				

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methylhippuric acids: 1 g/g creatinine (Urine)	End of workday	ES VLB

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene-di-isocyanate, polymer	Workers	Inhalation	Long-term local effects	0,5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Oral	Long-term systemic effects	150 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term exposure	32 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
isobutyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

			fects	
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	5 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	10 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	5 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	5 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	32 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
hexamethylene-diisocyanate	Workers	Inhalation	Long-term systemic effects	0,035 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	0,07 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

	Workers	Inhalation	Long-term local effects	0,035 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0,07 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0,01 mg/l
	Fresh water	0,1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
n-butyl acetate	Intermittent use/release	1 mg/l
	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
isobutyl acetate	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
	Soil	0,0755 mg/kg dry weight (d.w.)
	Marine water	0,017 mg/l
	Fresh water	0,17 mg/l
	Marine sediment	0,0877 mg/kg dry weight (d.w.)
reaction mixture of ethylbenzene, m-xylene and p-xylene	Fresh water sediment	0,877 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Intermittent use/release	0,34 mg/l
	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
hexamethylene-di-isocyanate	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	0,0026 mg/kg dry weight (d.w.)
	Marine water	0,00774 mg/l
Fresh water	0,0774 mg/l	
Marine sediment	0,001344 mg/kg	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

		dry weight (d.w.)
	Fresh water sediment	0,01334 mg/kg dry weight (d.w.)
	Sewage treatment plant	8,42 mg/l
	Intermittent use/release	0,774 mg/l

### 8.2 Exposure controls

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |  
Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Form : liquid

Colour : colourless

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

---

Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/freezing point	:	-98,8 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	117 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	10,5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1,1 %(V) (calculation method (principal components, highest value))
Flash point	:	28 °C
Ignition temperature	:	423 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	:	Not applicable
Viscosity		
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)		
Water solubility	:	partly miscible
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: < 4 (calculation method (principal components, highest value))

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

---

Vapour pressure : < 1.100 hPa (calculation method (principal components, highest value))  
(50 °C)

Relative density : No data available

Density : 1,01 g/cm<sup>3</sup>

Relative vapour density : 4 (calculation method (principal components, lowest value))

### 9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))  
45,95 %

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.  
Not classified due to lack of data.

##### Product:

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### **Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  5.000 mg/kg

##### **Hydrocarbons, C9 aromatics:**

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

##### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

##### **hexamethylene-di-isocyanate:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.  
Repeated exposure may cause skin dryness or cracking.

#### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

#### **Components:**

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

### **Serious eye damage/eye irritation**

Not classified based on available information.  
Not classified due to lack of data.

#### **Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

#### **Components:**

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Product:**

Remarks : Causes sensitisation.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

---

### **isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

Not classified based on available information.

Not classified due to lack of data.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

Not classified based on available information.

Not classified due to lack of data.

### **Components:**

#### **Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

Not classified due to lack of data.

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **Hydrocarbons, C9 aromatics:**

Toxicity to fish : LC50 (Fish): >= 9,2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): >= 3,2 mg/l  
Exposure time: 48 h

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): >= 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): >= 1 - 100 mg/l

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l  
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1 - 10 mg/l  
Toxicity to microorganisms : EC50 (Bacteria): > 1 - 10 mg/l

### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### **n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
Stability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.  
Photodegradation : Decomposes rapidly in contact with light.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Readily biodegradable.  
Photodegradation : Decomposes rapidly in contact with light.

## 12.3 Bioaccumulative potential

### Components:

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.  
Partition coefficient: n-octanol/water : log Pow: 1,81

#### **Hydrocarbons, C9 aromatics:**

Partition coefficient: n-octanol/water : log Pow: < 4

#### **isobutyl acetate:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

Partition coefficient: n-octanol/water : log Pow: 1,72

### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

### 12.4 Mobility in soil

#### Components:

#### Hydrocarbons, C9 aromatics:

Mobility : Medium: Air  
Content: 92,9 %  
: Medium: Water  
Content: 3,5 %  
: Medium: Soil  
Content: 1,9 %  
: Medium: Sediment  
Content: 1,8 %

Distribution among environmental compartments : Koc: 1,71 - 14,70  
Mobile in soils

The product is insoluble and floats on water.

### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS  
08 01 00, wastes from MFSU and removal of paint and varnish  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances  
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED  
15 01 00, packaging (including separately collected municipal packaging waste)  
15 01 10, packaging containing residues of or contaminated by hazardous substances  
HP3, Flammable  
HP13, Sensitising

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version 2.0      Revision Date: 11.02.2026      SDS Number: MAT000419583ES/EN      Date of last issue: 10.10.2025  
Date of first issue: 27.11.2023

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

ADN : PAINT  
ADR : PAINT  
RID : PAINT  
IMDG : PAINT  
IATA : Paint

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

#### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 40

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 75  
If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 45,95 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.
H317	: May cause an allergic skin reaction.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
Resp. Sens.	: Respiratory sensitisation
Skin Sens.	: Skin sensitisation
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

2019/1831/EU	:	list of indicative occupational exposure limit values Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
98/24/EC I	:	Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
ES VLA	:	Spain. Environmental Limits for exposure to Chemical agents - Table 1: Occupational Exposure Values
ES VLB	:	Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
98/24/EC I / STEL	:	Limit values Short-term
98/24/EC I / TWA	:	Limit values 8 hours
ES VLA / VLA-ED	:	Environmental Daily Limit Value
ES VLA / VLA-EC	:	Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## MOBIHEL 2K HS HARDENER 4100

Version	Revision Date:	SDS Number:	Date of last issue: 10.10.2025
2.0	11.02.2026	MAT000419583ES/ EN	Date of first issue: 27.11.2023

---

### Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.