

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K HARDENER 1500

Product code : 41672714

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892  
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

### SECTION 2: Hazards identification



#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

|  |  |
|--|--|
| Flammable liquids, Category 3  | H226: Flammable liquid and vapour.                       |
| Skin sensitisation, Category 1   | H317: May cause an allergic skin reaction.               |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.                 |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system     | H335: May cause respiratory irritation.                  |
| Long-term (chronic) aquatic hazard, Category 3                                       | H412: Harmful to aquatic life with long lasting effects. |

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

|                                |   |   |
|--------------------------------|---|---|
| Hazard pictograms              | : |     |
| Signal word                    | : | Warning   |
| Hazard statements              | : | H226 Flammable liquid and vapour.<br>H317 May cause an allergic skin reaction.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H412 Harmful to aquatic life with long lasting effects.  |
| Supplemental Hazard Statements | : | EUH066 Repeated exposure may cause skin dryness or cracking.  |
| Precautionary statements       | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P261 Avoid breathing mist or vapours.<br>P273 Avoid release to the environment.<br>P280 Wear protective gloves/ protective clothing/ eye |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

protection/ face protection/ hearing protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer

n-butyl acetate

isobutyl acetate

reaction mixture of ethylbenzene, m-xylene and p-xylene

### Additional Labelling

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

| Chemical name                         | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number     | Classification  | Concentration<br>(% w/w) |
|---------------------------------------|---|---|--------------------------|
| Hexamethylene diisocyanate, oligomers | 28182-81-2<br>500-060-2<br>01-2119485796-17               | Acute Tox. 4; H332<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>(Respiratory system) | >= 30 - < 50             |
| n-butyl acetate                       | 123-86-4<br>204-658-1<br>607-025-00-1<br>01-2119485493-29 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)                   | >= 20 - < 30             |
| isobutyl acetate                      | 110-19-0<br>203-745-1<br>607-026-00-7                     | Flam. Liq. 2; H225<br>STOT SE 3; H336<br>(Central nervous system)                   | >= 1 - < 10              |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

|   |   |  |               |
|---|---|--|---------------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 01-2119488971-22<br>-<br>905-562-9<br>01-2119555267-33,<br>01-2119488216-32 | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3;<br>H412 | >= 2,5 - < 10 |
| 2-methoxy-1-methylethyl acetate                         | 108-65-6<br>203-603-9<br>607-195-00-7<br>01-2119475791-29                   | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)  | >= 1 - < 10   |
| solvent naphtha (petroleum), light aromatic             | 64742-95-6<br>265-199-0<br>649-356-00-4<br>01-2119455851-35                 | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411  | >= 1 - < 2,5  |
| Substances with a workplace exposure limit :            |   |  |               |
| ethyl 3-ethoxypropionate                                | 763-69-9<br>212-112-9<br>01-2119463267-34                                   | Flam. Liq. 3; H226   | >= 1 - < 10   |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

| Components  | CAS-No.    | Value type (Form of exposure)  | Control parameters               | Basis            |
|---|------------|--|----------------------------------|------------------|
| Hexamethylene-di-isocyanate, polymer                    | 28182-81-2 | TWA  | 0,02 mg/m <sup>3</sup><br>(NCO)  | GB EH40          |
|   |            | Further information: Capable of causing occupational asthma.   |                                  |                  |
|   |            | STEL   | 0,07 mg/m <sup>3</sup><br>(NCO)  | GB EH40          |
|   |            | Further information: Capable of causing occupational asthma.   |                                  |                  |
|   |            | TWA  | 0,01 mg/m <sup>3</sup><br>(NCO)  | 98/24/EC I       |
|   |            | Further information: Skin, Dermal and respiratory sensitisation, Binding   |                                  |                  |
|   |            | STEL   | 0,02 mg/m <sup>3</sup><br>(NCO)  | 98/24/EC I       |
|   |            | Further information: Skin, Dermal and respiratory sensitisation, Binding   |                                  |                  |
| n-butyl acetate   | 123-86-4   | TWA  | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40          |
|   |            | STEL   | 200 ppm<br>966 mg/m <sup>3</sup> | GB EH40          |
|   |            | STEL   | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|   |            | Further information: Indicative  |                                  |                  |
|   |            | TWA  | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|   |            | Further information: Indicative  |                                  |                  |
| isobutyl acetate  | 110-19-0   | TWA  | 150 ppm<br>724 mg/m <sup>3</sup> | GB EH40          |
|   |            | STEL   | 187 ppm<br>903 mg/m <sup>3</sup> | GB EH40          |
|   |            | TWA  | 50 ppm<br>241 mg/m <sup>3</sup>  | 2019/1831/E<br>U |
|   |            | Further information: Indicative  |                                  |                  |
|   |            | STEL   | 150 ppm<br>723 mg/m <sup>3</sup> | 2019/1831/E<br>U |
|   |            | Further information: Indicative  |                                  |                  |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7  | TWA  | 50 ppm<br>220 mg/m <sup>3</sup>  | GB EH40          |
|   |            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                                  |                  |
|   |            | STEL   | 100 ppm<br>441 mg/m <sup>3</sup> | GB EH40          |
|   |            | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will                            |                                  |                  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

|                                 |  |      |                                  |            |
|---------------------------------|--|------|----------------------------------|------------|
|                                 |  |      | lead to systemic toxicity.       |            |
|                                 |  | TWA  | 50 ppm<br>221 mg/m <sup>3</sup>  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |
|                                 |  | STEL | 100 ppm<br>442 mg/m <sup>3</sup> | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |
| 2-methoxy-1-methylethyl acetate | 108-65-6   | TWA  | 50 ppm<br>274 mg/m <sup>3</sup>  | GB EH40    |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                                  |            |
|                                 |  | STEL | 100 ppm<br>548 mg/m <sup>3</sup> | GB EH40    |
|                                 | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |      |                                  |            |
|                                 |  | STEL | 100 ppm<br>550 mg/m <sup>3</sup> | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |
|                                 |  | TWA  | 50 ppm<br>275 mg/m <sup>3</sup>  | 2000/39/EC |
|                                 | Further information: Identifies the possibility of significant uptake through the skin, Indicative   |      |                                  |            |

### Biological occupational exposure limits

| Substance name  | CAS-No.    | Control parameters  | Sampling time                        | Basis          |
|---|------------|---|--------------------------------------|----------------|
| Hexamethylene-diisocyanate, polymer                     | 28182-81-2 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40<br>BAT |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7  | methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)        | After shift                          | GB EH40<br>BAT |

### Derived No Effect Level (DNEL)

| Substance name                      | End Use | Exposure routes | Potential health effects | Value                 |
|-------------------------------------|---------|-----------------|--------------------------|-----------------------|
| Hexamethylene-diisocyanate, polymer | Workers | Inhalation      | Long-term local effects  | 0,5 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

|                  |           |            |                            |                        |
|------------------|-----------|------------|----------------------------|------------------------|
|                  | Workers   | Inhalation | Long-term systemic effects | 1 mg/m <sup>3</sup>    |
| n-butyl acetate  | Workers   | Inhalation | Acute systemic effects     | 600 mg/m <sup>3</sup>  |
|                  | Workers   | Inhalation | Acute local effects        | 600 mg/m <sup>3</sup>  |
|                  | Workers   | Inhalation | Long-term systemic effects | 48 mg/m <sup>3</sup>   |
|                  | Workers   | Inhalation | Long-term local effects    | 300 mg/m <sup>3</sup>  |
|                  | Consumers | Inhalation | Acute systemic effects     | 300 mg/m <sup>3</sup>  |
|                  | Consumers | Inhalation | Acute local effects        | 300 mg/m <sup>3</sup>  |
|                  | Consumers | Inhalation | Long-term systemic effects | 12 mg/m <sup>3</sup>   |
|                  | Consumers | Inhalation | Long-term local effects    | 35,7 mg/m <sup>3</sup> |
|                  | Consumers | Dermal     | Long-term systemic effects | 3,4 mg/kg bw/day       |
|                  | Consumers | Dermal     | Acute systemic effects     | 6 mg/kg bw/day         |
|                  | Consumers | Oral       | Long-term systemic effects | 2 mg/kg bw/day         |
|                  | Consumers | Oral       | Acute systemic effects     | 2 mg/kg bw/day         |
|                  | Workers   | Dermal     | Long-term systemic effects | 7 mg/kg bw/day         |
|                  | Workers   | Dermal     | Acute systemic effects     | 11 mg/kg bw/day        |
| isobutyl acetate | Workers   | Inhalation | Long-term systemic effects | 300 mg/m <sup>3</sup>  |
|                  | Workers   | Inhalation | Acute systemic effects     | 600 mg/m <sup>3</sup>  |
|                  | Workers   | Inhalation | Long-term local effects    | 300 mg/m <sup>3</sup>  |
|                  | Workers   | Inhalation | Acute local effects        | 600 mg/m <sup>3</sup>  |
|                  | Consumers | Inhalation | Long-term systemic effects | 35,7 mg/m <sup>3</sup> |
|                  | Consumers | Inhalation | Long-term local effects    | 35,7 mg/m <sup>3</sup> |
|                  | Consumers | Inhalation | Acute local effects        | 300 mg/m <sup>3</sup>  |
|                  | Workers   | Dermal     | Long-term systemic effects | 10 mg/kg bw/day        |
|                  | Consumers | Oral       | Acute systemic effects     | 5 mg/kg bw/day         |
|                  | Workers   | Dermal     | Acute systemic effects     | 10 mg/kg bw/day        |
|                  | Consumers | Dermal     | Long-term systemic effects | 5 mg/kg                |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

|   |           |            |                            |                        |
|---|-----------|------------|----------------------------|------------------------|
|   | Consumers | Dermal     | effects                    | bw/day                 |
|   | Consumers | Dermal     | Acute systemic effects     | 5 mg/kg bw/day         |
|   | Consumers | Oral       | Long-term systemic effects | 5 mg/kg bw/day         |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Workers   | Inhalation | Long-term systemic effects | 77 mg/m <sup>3</sup>   |
|   | Consumers | Inhalation | Long-term local effects    | 65,3 mg/m <sup>3</sup> |
|   | Workers   | Inhalation | Acute systemic effects     | 442 mg/m <sup>3</sup>  |
|   | Workers   | Inhalation | Acute local effects        | 289 mg/m <sup>3</sup>  |
|   | Consumers | Inhalation | Acute systemic effects     | 260 mg/m <sup>3</sup>  |
|   | Workers   | Inhalation | Long-term local effects    | 221 mg/m <sup>3</sup>  |
|   | Consumers | Inhalation | Long-term systemic effects | 14,8 mg/m <sup>3</sup> |
|   | Consumers | Inhalation | Acute local effects        | 260 mg/m <sup>3</sup>  |
|   | Consumers | Dermal     | Long-term systemic effects | 108 mg/kg bw/day       |
|   | Consumers | Oral       | Long-term systemic effects | 16 mg/kg bw/day        |
|   | Workers   | Dermal     | Long-term systemic effects | 180 mg/kg bw/day       |
| 2-methoxy-1-methylethyl acetate                         | Workers   | Inhalation | Long-term systemic effects | 275 mg/m <sup>3</sup>  |
|   | Workers   | Inhalation | Acute local effects        | 550 mg/m <sup>3</sup>  |
|   | Consumers | Inhalation | Long-term systemic effects | 33 mg/m <sup>3</sup>   |
|   | Consumers | Inhalation | Long-term local effects    | 33 mg/m <sup>3</sup>   |
|   | Workers   | Dermal     | Long-term systemic effects | 796 mg/kg bw/day       |
|   | Consumers | Dermal     | Long-term systemic effects | 320 mg/kg bw/day       |
|   | Consumers | Oral       | Long-term systemic effects | 36 mg/kg bw/day        |
| ethyl 3-ethoxypropionate                                | Workers   | Inhalation | Long-term systemic effects | 610 mg/m <sup>3</sup>  |
|   | Workers   | Inhalation | Long-term local effects    | 610 mg/m <sup>3</sup>  |
|   | Consumers | Inhalation | Long-term systemic effects | 72,6 mg/m <sup>3</sup> |
|   | Consumers | Inhalation | Long-term local effects    | 72,6 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

|  |           |            |                            |                        |
|--|-----------|------------|----------------------------|------------------------|
|  | Workers   | Dermal     | Long-term local effects    | 102 mg/cm <sup>2</sup> |
|  | Workers   | Dermal     | Long-term systemic effects | 102 mg/kg bw/day       |
|  | Consumers | Dermal     | Long-term systemic effects | 24,2 mg/kg bw/day      |
|  | Consumers | Oral       | Long-term systemic effects | 1,2 mg/kg bw/day       |
| Solvent naphtha (petroleum), light arom.;<br>Low boiling point<br>naphtha -unspecified | Workers   | Inhalation | Long-term systemic effects | 150 mg/m <sup>3</sup>  |
|  | Consumers | Inhalation | Long-term systemic effects | 32 mg/m <sup>3</sup>   |
|  | Consumers | Dermal     | Long-term systemic effects | 11 mg/kg bw/day        |
|  | Workers   | Dermal     | Long-term systemic effects | 25 mg/kg bw/day        |
|  | Consumers | Oral       | Long-term systemic effects | 11 mg/kg bw/day        |

### Predicted No Effect Concentration (PNEC)

| Substance name                       | Environmental Compartment                          | Value                          |
|--------------------------------------|--|--------------------------------|
| Hexamethylene-di-isocyanate, polymer | Soil   | 505 mg/kg dry weight (d.w.)    |
|                                      | Marine water                                       | 0,01 mg/l                      |
|                                      | Fresh water  | 0,1 mg/l                       |
|                                      | Marine sediment                                    | 253 mg/kg dry weight (d.w.)    |
|                                      | Fresh water sediment                               | 2530 mg/kg dry weight (d.w.)   |
|                                      | Sewage treatment plant<br>Intermittent use/release | 100 mg/l<br>1 mg/l             |
| n-butyl acetate                      | Soil   | 0,0903 mg/kg dry weight (d.w.) |
|                                      | Marine water                                       | 0,018 mg/l                     |
|                                      | Fresh water  | 0,18 mg/l                      |
|                                      | Marine sediment                                    | 0,0981 mg/kg dry weight (d.w.) |
|                                      | Fresh water sediment                               | 0,981 mg/kg dry weight (d.w.)  |
|                                      | Sewage treatment plant<br>Intermittent use/release | 35,6 mg/l<br>0,36 mg/l         |
| isobutyl acetate                     | Soil   | 0,0755 mg/kg dry weight (d.w.) |
|                                      | Marine water                                       | 0,017 mg/l                     |
|                                      | Fresh water  | 0,17 mg/l                      |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

|   |                          |                                |
|---|--------------------------|--------------------------------|
|   | Marine sediment          | 0,0877 mg/kg dry weight (d.w.) |
|   | Fresh water sediment     | 0,877 mg/kg dry weight (d.w.)  |
|   | Sewage treatment plant   | 200 mg/l                       |
|   | Intermittent use/release | 0,34 mg/l                      |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Soil                     | 2,31 mg/kg dry weight (d.w.)   |
|   | Marine water             | 0,327 mg/l                     |
|   | Fresh water              | 0,327 mg/l                     |
|   | Marine sediment          | 12,46 mg/kg dry weight (d.w.)  |
|   | Fresh water sediment     | 12,46 mg/kg dry weight (d.w.)  |
|   | Sewage treatment plant   | 6,58 mg/l                      |
|   | Intermittent use/release | 0,327 mg/l                     |
| 2-methoxy-1-methylethyl acetate                         | Soil                     | 0,29 mg/kg dry weight (d.w.)   |
|   | Marine water             | 0,0635 mg/l                    |
|   | Fresh water              | 0,635 mg/l                     |
|   | Marine sediment          | 0,329 mg/kg dry weight (d.w.)  |
|   | Fresh water sediment     | 3,29 mg/kg dry weight (d.w.)   |
|   | Sewage treatment plant   | 100 mg/l                       |
|   | Intermittent use/release | 0,00635 mg/l                   |
| ethyl 3-ethoxypropionate                                | Soil                     | 0,048 mg/kg dry weight (d.w.)  |
|   | Marine water             | 0,00609 mg/l                   |
|   | Fresh water              | 0,0609 mg/l                    |
|   | Marine sediment          | 0,0419 mg/kg dry weight (d.w.) |
|   | Fresh water sediment     | 0,419 mg/kg dry weight (d.w.)  |
|   | Sewage treatment plant   | 50 mg/l                        |
|   | Intermittent use/release | 0,609 mg/l                     |

### 8.2 Exposure controls

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

|                          |   |   |
|--------------------------|---|---|
| Skin and body protection | : | Impervious clothing<br>Choose body protection according to the amount and concentration of the dangerous substance at the work place.   |
| Respiratory protection   | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.<br>Equipment should conform to EN 14387 |
| Filter type              | : | Organic vapour type (A)   |

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |   |   |
|--|---|---|
| Appearance                                       | : | liquid  |
| Colour   | : | colourless  |
| Odour  | : | solvent-like  |
| Odour Threshold                                  | : | No data available   |
| pH   | : | Not applicable  |
| Melting point/freezing point                     | : | -98,8 °C<br>(calculation method (principal components, lowest value))   |
| Boiling point/boiling range                      | : | 117 °C (calculation method (principal components, lowest value))        |
| Flash point                                      | : | 34 °C   |
| Flammability                                     | : | Static-accumulating flammable liquid., Combustible Solids               |
| Upper explosion limit / Upper flammability limit | : | 10,5 %(V)<br>(calculation method (principal components, highest value)) |
| Lower explosion limit / Lower flammability limit | : | 1,1 %(V)<br>(calculation method (principal components, highest value))  |

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Relative vapour density : 4,6 (calculation method (principal components, highest value))

(Air = 1.0)

Relative density : No data available

Density : 0,984 g/cm<sup>3</sup>

Solubility(ies)

Water solubility : immiscible, partly soluble

Solubility in other solvents : Description: miscible with most organic solvents

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15 (calculation method (principal components, highest value))

Ignition temperature : 315 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if stored and applied as directed.  
Hazardous decomposition products formed under fire conditions.

Viscosity

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Flow time

: 12 s at 20 °C  
Cross section: 4 mm  
Method: DIN 53211

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

### 9.2 Other information

No data available

VOC : (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))  
60,96 %  
Volatile CMR compounds [%]: 0,02 %

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified due to lack of data.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### Hexamethylene-di-isocyanate, polymer:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

short term inhalation.

### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 10.760$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq 5.000$  mg/kg

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 8.700$  mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $> > 2.000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 5$  mg/l  
Test atmosphere: vapour

LC0 (Rat): 2000 ppm  
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit):  $> > 2.000$  mg/kg

### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat):  $> 2.000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 5$  mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit):  $> 2.000$  mg/kg

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

### **Components:**

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Result : irritating

### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

#### Components:

##### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Product:

Remarks : Causes sensitisation.

#### Components:

##### Hexamethylene-di-isocyanate, polymer:

Result : Probability or evidence of skin sensitisation in humans

### Germ cell mutagenicity

Not classified due to lack of data.

#### Components:

##### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

Not classified due to lack of data.

#### Components:

##### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

---

ment

1272/2008, Annex VI, Part 3, Note P)

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

### **Components:**

#### **Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

#### **2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

Not classified due to lack of data.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

Not classified due to lack of data.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

### Components:

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

### **Endocrine disrupting properties**

#### Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f), at levels of 0.1% or higher.

### **Further information**

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): >= 1 - 10 mg/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### 2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h

NOEC : 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 : 408 mg/l  
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47,5 mg/l

### Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:

Toxicity to fish : LC50 (Fish):  $> 1 - 10$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $> 1 - 10$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $> 1 - 10$  mg/l

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### n-butyl acetate:

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Remarks: Readily biodegradable.

## 12.3 Bioaccumulative potential

### **Components:**

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-  
octanol/water : log Pow: 1,81

#### **isobutyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,72

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-  
octanol/water : log Pow: 2,77 - 3,15

### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8

### **ethyl 3-ethoxypropionate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,35

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

### 12.4 Mobility in soil

#### Components:

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

#### **Endocrine disrupting properties**

#### Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14: Transport information

#### 14.1 UN number

|      |   |         |
|------|---|---------|
| ADN  | : | UN 1263 |
| ADR  | : | UN 1263 |
| RID  | : | UN 1263 |
| IMDG | : | UN 1263 |
| IATA | : | UN 1263 |

#### 14.2 UN proper shipping name

|      |   |       |
|------|---|-------|
| ADN  | : | PAINT |
| ADR  | : | PAINT |
| RID  | : | PAINT |
| IMDG | : | PAINT |
| IATA | : | Paint |

#### 14.3 Transport hazard class(es)

|      | Class | Subsidiary risks |
|------|-------|------------------|
| ADN  | : 3   |                  |
| ADR  | : 3   |                  |
| RID  | : 3   |                  |
| IMDG | : 3   |                  |
| IATA | : 3   |                  |

#### 14.4 Packing group

|                              |       |
|------------------------------|-------|
| <b>ADN</b>                   |       |
| Packing group                | : III |
| Classification Code          | : F1  |
| Hazard Identification Number | : 30  |
| Labels                       | : 3   |
| <b>ADR</b>                   |       |
| Packing group                | : III |
| Classification Code          | : F1  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

|   |           |  |
|---|-----------|--|
| UK REACH List of restrictions (Annex 17)  | :         | Conditions of restriction for the following entries should be considered:<br>Number on list 3<br><br>Number on list 40<br>This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.  |
| UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation                             | :         | Not applicable   |
| The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) | :         | Not applicable   |
| Regulation (EU) No 2024/590 on substances that deplete the ozone layer  | :         | Not applicable   |
| UK REACH List of substances subject to authorisation (Annex XIV)  | :         | Not applicable   |
| GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation                           | :         | Not applicable   |
| Control of Major Accident Hazards Regulations 2015 (COMAH)  | P5c<br>34 | FLAMMABLE LIQUIDS<br><br>Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) |
| Volatile organic compounds  | :         | Directive 2010/75/EU of 24 November 2010 on industrial and   |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 60,96 %

Volatile CMR compounds: 0,02 %

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

---

## SECTION 16: Other information

### Full text of H-Statements

|      |  |
|------|--|
| H225 | : Highly flammable liquid and vapour.                                |
| H226 | : Flammable liquid and vapour.                                       |
| H304 | : May be fatal if swallowed and enters airways.                      |
| H312 | : Harmful in contact with skin.                                      |
| H315 | : Causes skin irritation.  |
| H317 | : May cause an allergic skin reaction.                               |
| H319 | : Causes serious eye irritation.                                     |
| H332 | : Harmful if inhaled.  |
| H335 | : May cause respiratory irritation.                                  |
| H336 | : May cause drowsiness or dizziness.                                 |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H411 | : Toxic to aquatic life with long lasting effects.                   |
| H412 | : Harmful to aquatic life with long lasting effects.                 |

### Full text of other abbreviations

|                 |  |
|-----------------|--|
| Acute Tox.      | : Acute toxicity                                     |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard                 |
| Asp. Tox.       | : Aspiration hazard                                  |
| Eye Irrit.      | : Eye irritation                                     |
| Flam. Liq.      | : Flammable liquids                                  |
| Skin Irrit.     | : Skin irritation                                    |
| Skin Sens.      | : Skin sensitisation                                 |
| STOT RE         | : Specific target organ toxicity - repeated exposure |
| STOT SE         | : Specific target organ toxicity - single exposure   |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

|         |                |                       |                                 |
|---------|----------------|-----------------------|---------------------------------|
| Version | Revision Date: | SDS Number:           | Date of last issue: 07.06.2024  |
| 3.0     | 12.02.2026     | MAT000416727<br>GB/EN | Date of first issue: 23.07.2021 |

---

|                     |   |  |
|---------------------|---|--|
| 2000/39/EC          | : | Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values   |
| 2019/1831/EU        | : | Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values |
| 98/24/EC I          | : | Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values                              |
| GB EH40             | : | UK. EH40 WEL - Workplace Exposure Limits   |
| GB EH40 BAT         | : | UK. Biological monitoring guidance values  |
| 2000/39/EC / TWA    | : | Limit Value - eight hours  |
| 2000/39/EC / STEL   | : | Short term exposure limit  |
| 2019/1831/EU / TWA  | : | Limit Value - eight hours  |
| 2019/1831/EU / STEL | : | Short term exposure limit  |
| 98/24/EC I / STEL   | : | Limit values Short-term  |
| 98/24/EC I / TWA    | : | Limit values 8 hours   |
| GB EH40 / TWA       | : | Long-term exposure limit (8-hour TWA reference period)   |
| GB EH40 / STEL      | : | Short-term exposure limit (15-minute reference period)   |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K HARDENER 1500

Version  
3.0

Revision Date:  
12.02.2026

SDS Number:  
MAT000416727  
GB/EN

Date of last issue: 07.06.2024  
Date of first issue: 23.07.2021

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Skin Sens. 1      | H317 |
| STOT SE 3         | H336 |
| STOT SE 3         | H335 |
| Aquatic Chronic 3 | H412 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.