

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

### SECTION 1: IDENTIFICATION

Product name : MOBIHEL 4:1 HS KOMPAKTPRIMER

#### Details of the supplier of the safety data sheet

Company : Helios Coatings Australia Pty Ltd  
50 Clapham Road  
SEFTON NSW 2162  
Australia

Telephone : 61 2 9645 3188  
E-mail address Responsible/issuing person : 61 2 9645 3188  
info@helioscoatings.com.au

#### Emergency telephone number

112 (mobile) Ambulance 000, Poisons Information Centre: 131 126

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 3  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 2A  
Specific target organ toxicity - repeated exposure : Category 2

#### GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equip-

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

ment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

| Chemical name   | CAS-No.      | Concentration (% w/w) |
|---|--------------|-----------------------|
| barium sulphate, natural                                | 7727-43-7    | >= 10 -< 30           |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | Not Assigned | >= 10 -< 20           |
| calcium carbonate                                       | 471-34-1     | < 10                  |
| n-butyl acetate   | 123-86-4     | < 10                  |
| talc  | 14807-96-6   | < 10                  |
| titanium dioxide  | 13463-67-7   | < 10                  |
| 2-methoxy-1-methylethyl acetate                         | 108-65-6     | < 10                  |
| Quartz (SiO <sub>2</sub> )                              | 14808-60-7   | < 10                  |
| Hydrocarbons, C9 aromatics                              | 128601-23-0  | >= 1 -< 10            |
| Hexanoic acid, 2-ethyl-, zinc salt, basic               | 85203-81-2   | < 3                   |

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3Y

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

## MOBIHEL 4:1 HS KOMPAKTPRIMER

Version  
1.2Revision Date:  
12.02.2026SDS Number:  
MAT0GA05\_022  
AU / ENDate of last issue: 23.04.2024  
Date of first issue: 16.11.2023

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

| Components  | CAS-No.    | Value type<br>(Form of exposure)  | Control parameters / Permissible concentration | Basis  |
|---|------------|---|--|--------|
| barium sulfate  | 7727-43-7  | TWA   | 10 mg/m <sup>3</sup>                           | AU OEL |
|   |            | TWA (Inhalable particulate matter)  | 5 mg/m <sup>3</sup>                            | ACGIH  |
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7  | TWA   | 80 ppm<br>350 mg/m <sup>3</sup>                | AU OEL |
|   |            | STEL  | 150 ppm<br>655 mg/m <sup>3</sup>               | AU OEL |
| Calcium carbonate                                       | 471-34-1   | TWA   | 20 ppm   | ACGIH  |
|   |            | TWA   | 10 mg/m <sup>3</sup><br>(Calcium carbonate)    | AU OEL |
| n-butyl acetate   | 123-86-4   | TWA   | 150 ppm<br>713 mg/m <sup>3</sup>               | AU OEL |
|   |            | STEL  | 200 ppm<br>950 mg/m <sup>3</sup>               | AU OEL |
| Talc  | 14807-96-6 | TWA   | 50 ppm   | ACGIH  |
|   |            | STEL  | 150 ppm  | ACGIH  |
| titanium dioxide  | 13463-67-7 | TWA   | 2.5 mg/m <sup>3</sup>                          | AU OEL |
|   |            | TWA (Respirable particulate matter)   | 2 mg/m <sup>3</sup>                            | ACGIH  |
| 2-methoxy-1-methylethyl acetate                         | 108-65-6   | TWA   | 10 mg/m <sup>3</sup>                           | AU OEL |
|   |            | TWA (Respirable particulate matter)   | 0.2 mg/m <sup>3</sup><br>(Titanium dioxide)    | ACGIH  |
|   |            | TWA (Respirable particulate matter)   | 2.5 mg/m <sup>3</sup><br>(Titanium dioxide)    | ACGIH  |
|   |            | Further information: Skin absorption  |  |        |
|   |            | STEL  | 100 ppm<br>548 mg/m <sup>3</sup>               | AU OEL |
| Quartz (SiO <sub>2</sub> )                              | 14808-60-7 | Further information: Skin absorption  |  |        |
|   |            | TWA (Respirable dust)   | 0.05 mg/m <sup>3</sup>                         | AU OEL |
|   |            | Further information: Category 1A (Carc. 1A) Known to have carcinogenic potential for humans |  |        |
|   |            | TWA (Respirable particulate matter)   | 0.025 mg/m <sup>3</sup><br>(Silica)            | ACGIH  |

## MOBIHEL 4:1 HS KOMPAKTPRIMER

Version 1.2      Revision Date: 12.02.2026      SDS Number: MAT0GA05\_022 AU / EN      Date of last issue: 23.04.2024      Date of first issue: 16.11.2023

**Biological occupational exposure limits**

| Components  | CAS-No.   | Control parameters   | Biological specimen | Sampling time  | Permissible concentration | Basis     |
|---|-----------|----------------------|---------------------|--|---------------------------|-----------|
| reaction mixture of ethylbenzene, m-xylene and p-xylene | 1330-20-7 | Methylhippuric acids | Urine               | End of shift (As soon as possible after exposure ceases) | 0.3 g/g creatinine        | ACGIH BEI |

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : in accordance with the product description

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Flash point : 30 °C  
Method: ISO 3679, closed cup

Flammability (solid, gas) : Static-accumulating flammable liquid., Combustible Solids

Relative vapour density : No data available

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
| AU / EN |                |              |                                 |

---

|  |   |   |
|--|---|---|
| Relative density                       | : | No data available   |
| Density                                | : | 1.460 - 1.600 g/cm <sup>3</sup>   |
| Solubility(ies)                        | : |   |
| Water solubility                       | : | immiscible, partly soluble  |
| Solubility in other solvents           | : | Description: miscible with most organic solvents  |
| Partition coefficient: n-octanol/water | : | No data available   |
| Decomposition temperature              | : | No decomposition if stored and applied as directed.<br>Hazardous decomposition products formed under fire conditions. |
| Viscosity                              | : |   |
| Viscosity, kinematic                   | : | > 20.5 mm <sup>2</sup> /s ( 40 °C)  |
| Explosive properties                   | : | Not applicable  |
| Oxidizing properties                   | : | Sustains combustion   |
| VOC                                    | : | (Directive 2004/42/EC)<br>540 g/l   |

---

**SECTION 10. STABILITY AND REACTIVITY**

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | No decomposition if stored and applied as directed.   |
| Chemical stability                 | : | No decomposition if stored and applied as directed.   |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed.<br>Vapours may form explosive mixture with air. |
| Conditions to avoid                | : | Heat, flames and sparks.  |
| Incompatible materials             | : | Incompatible with strong acids and bases.   |
| Hazardous decomposition products   | : | No hazardous decomposition products are known.  |

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

|                           |   |   |
|---------------------------|---|---|
| Acute inhalation toxicity | : | Acute toxicity estimate: > 20 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour<br>Method: Calculation method |
| Acute dermal toxicity     | : | Acute toxicity estimate: > 2,000 mg/kg<br>Method: Calculation method  |

**MOBIHEL 4:1 HS KOMPAKTPRIMER**

|         |                |                         |                                 |
|---------|----------------|-------------------------|---------------------------------|
| Version | Revision Date: | SDS Number:             | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022<br>AU / EN | Date of first issue: 16.11.2023 |

---

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 8,700$  mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

**n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 10,760$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq 5,000$  mg/kg

**2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $> > 2,000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 5$  mg/l  
Test atmosphere: vapour

LC0 (Rat): 2000 ppm  
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit):  $> > 2,000$  mg/kg

**Hydrocarbons, C9 aromatics:**

Acute dermal toxicity : LD50 (Rabbit):  $> 3,160$  mg/kg

**Skin corrosion/irritation****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

**Serious eye damage/eye irritation****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

**Hexanoic acid, 2-ethyl-, zinc salt, basic:**

Result : Eye irritation

## MOBIHEL 4:1 HS KOMPAKTPRIMER

Version  
1.2Revision Date:  
12.02.2026SDS Number:  
MAT0GA05\_022  
AU / ENDate of last issue: 23.04.2024  
Date of first issue: 16.11.2023**Chronic toxicity****Reproductive toxicity****Components:****Hexanoic acid, 2-ethyl-, zinc salt, basic:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

**n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**STOT - repeated exposure****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
| AU / EN |                |              |                                 |

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)):  $> 200$  mg/l

EC50 (Desmodesmus subspicatus (green algae)):  $\geq 647.7$  mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

**2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l

Exposure time: 96 h

NOEC : 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50: 408 mg/l

Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47.5 mg/l

**Hydrocarbons, C9 aromatics:**

Toxicity to fish : LC50 (Fish):  $\geq 9.2$  mg/l

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 3.2$  mg/l

Exposure time: 48 h

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

---

**Hexanoic acid, 2-ethyl-, zinc salt, basic:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**n-butyl acetate:**Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301DStability in water : Degradation half life: 78 d pH: 8  
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**2-methoxy-1-methylethyl acetate:**

Biodegradability : Remarks: Readily biodegradable.

**Bioaccumulative potential****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Remarks: Bioaccumulation is unlikely.Partition coefficient: n-  
octanol/water : log Pow: 2.77 - 3.15**n-butyl acetate:**Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.Partition coefficient: n-  
octanol/water : log Pow: 1.81**2-methoxy-1-methylethyl acetate:**Partition coefficient: n-  
octanol/water : log Pow: 1.2 (20 °C)  
pH: 6.8**Hydrocarbons, C9 aromatics:**

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

Partition coefficient: n-octanol/water : log Pow: < 4

**Mobility in soil****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

**Hydrocarbons, C9 aromatics:**

Mobility : Medium: Air  
Content: 92.9 %

Medium: Water  
Content: 3.5 %

Medium: Soil  
Content: 1.9 %

Medium: Sediment  
Content: 1.8 %

Distribution among environmental compartments : Koc: 1.71 - 14.70  
Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**Endocrine disrupting properties**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

**IATA-DGR**

UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •3Y  
Environmentally hazardous : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

## SECTION 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard) Instrument : Schedule 7

Prohibition/Licensing Requirements : Quartz (SiO<sub>2</sub>)  
Refer to model WHS Act and Regulations for prohibition, authorisation and restricted use.

National Code of Practice for Chemicals of Security Concern : Not listed

## SECTION 16: ANY OTHER RELEVANT INFORMATION

Revision Date : 12.02.2026  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006

## MOBIHEL 4:1 HS KOMPAKTPRIMER

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 23.04.2024  |
| 1.2     | 12.02.2026     | MAT0GA05_022 | Date of first issue: 16.11.2023 |
|         |                | AU / EN      |                                 |

---

of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Material codes (bulk) for 417938 , 419580, 419581  
which the SDS is valid

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.