

**MOBIHEL 2K HARDENER 700**Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : MOBIHEL 2K HARDENER 700

Product code : 41825621

**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-  
stance/Mixture : PC9a: Coatings and paints, thinners, paint removersRecommended restrictions  
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si**1.4 Emergency telephone number**

Emergency telephone number: 911

Access code: 13586 +1 760 476 3959

---

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Acute toxicity, Category 4 H312: Harmful in contact with skin.

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory system  
Specific target organ toxicity - repeated exposure, Category 2

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H226 Flammable liquid and vapour.  
 H312 + H332 Harmful in contact with skin or if inhaled.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P260 Do not breathe mist or vapours.  
 P264 Wash skin thoroughly after handling.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

**Response:**

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

reaction mixture of ethylbenzene, m-xylene and p-xylene  
Hexamethylene-di-isocyanate, polymer  
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified

**Additional Labelling**

EUH204      Contains isocyanates. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
reaction mixture of ethylbenzene, m-xylene and p-xylene	-  905-562-9 01-2119555267-33, 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 50 - < 70
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
solvent naphtha (petroleum), light	64742-95-6	Flam. Liq. 3; H226	>= 1 - < 2.5

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

aromatic	265-199-0 649-356-00-4 01-2119455851-35	STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411
----------	---	---

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.

**MOBIHEL 2K HARDENER 700**

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

---

Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment : Treat symptomatically.

---

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

**5.2 Special hazards arising from the substance or mixture**

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

**5.3 Advice for firefighters**

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.

---

**MOBIHEL 2K HARDENER 700**Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from moisture.

Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Hexamethylene-diisocyanate, polymer	28182-81-2	TWA	0.01 mg/m <sup>3</sup> (NCO)	98/24/EC I
		STEL	0.02 mg/m <sup>3</sup> (NCO)	98/24/EC I
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006**

Substance name	End Use	Exposure routes	Potential health effects	Value

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65.3 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Hexamethylene-diisocyanate, polymer	Workers	Inhalation	Long-term local effects	0.5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	32 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006**

Substance name	Environmental Compartment	Value
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
	Intermittent use/release	0.327 mg/l
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
	Fresh water	0.1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
n-butyl acetate	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l

## MOBIHEL 2K HARDENER 700

Version 3.0	Revision Date: 22.04.2026	SDS Number: MAT000418256 JO/EN	Date of last issue: 06.05.2024 Date of first issue: 28.11.2023
----------------	------------------------------	--------------------------------------	---

---

**8.2 Exposure controls****Individual protection measures, such as personal protective equipment (PPE)**

Eye/face protection	:	Equipment should conform to EN 166 Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection	:	
Gloves	:	Viton® (> 0,6 mm; < 240 min); ISO EN374   PE laminate (> 0,1 mm; < 240 min); ISO EN374
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic vapour type (A)

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Physical state	:	liquid
Form	:	liquid
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	ca. -70 - -28 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	138 - 141.4 °C (calculation method (principal components, lowest value))
Flash point	:	26 °C
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	6.6 %(V) (calculation method (principal components, highest value))

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

---

Lower explosion limit / Lower flammability limit	:	1.1 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	8.21 hPa (calculation method (principal components, highest value))  (20 °C)
Relative vapour density	:	No data available
Relative density	:	0.92 (calculation method (principal components, highest value))
Density	:	0.963 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	partly miscible
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 2.77 - 3.15 (calculation method (principal components, highest value))
Ignition temperature	:	460 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity		
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion

**9.2 Other information**No data available  
VOC

: (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

---

60.35 %

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful in contact with skin or if inhaled.

Harmful in contact with skin or if inhaled.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: 11.57 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 1,978 mg/kg  
Method: Calculation method

#### Components:

reaction mixture of ethylbenzene, m-xylene and p-xylene:

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023

Acute oral toxicity : LD50 Oral (Rat):  $\geq 8,700$  mg/kg

Acute inhalation toxicity : LC50 (Rat): 27.14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

**Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

**n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq 10,760$  mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq 5,000$  mg/kg

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat):  $> 2,000$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $> 5$  mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit):  $> 2,000$  mg/kg

**Skin corrosion/irritation**

Causes skin irritation.  
Causes skin irritation.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

**Serious eye damage/eye irritation**

Causes serious eye irritation.  
Causes serious eye irritation.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

---

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified due to lack of data.

**Product:**

Remarks : Causes sensitisation.

**Components:****Hexamethylene-di-isocyanate, polymer:**

Result : Probability or evidence of skin sensitisation in humans

**Germ cell mutagenicity**

Not classified based on available information.

Not classified due to lack of data.

**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

**Carcinogenicity**

Not classified based on available information.

Not classified due to lack of data.

**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

## MOBIHEL 2K HARDENER 700

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

---

### **Reproductive toxicity**

Not classified based on available information.  
Not classified due to lack of data.

### **STOT - single exposure**

May cause respiratory irritation.  
May cause respiratory irritation.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

#### **Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.  
May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

Not classified based on available information.  
Not classified due to lack of data.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

#### **Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023**Further information****Product:**

Remarks : Solvents may degrease the skin.

**SECTION 12: Ecological information****12.1 Toxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/lToxicity to daphnia and other : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l  
aquatic invertebratesToxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): 91.2 mg/l  
plants Exposure time: 72 hToxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**n-butyl acetate:**Toxicity to algae/aquatic : NOEC (Desmodesmus subspicatus (green algae)):  $> 200$  mg/l  
plantsEC50 (Desmodesmus subspicatus (green algae)):  $\geq 647.7$   
mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**Toxicity to fish : LC50 (Fish):  $> 1 - 10$  mg/lToxicity to daphnia and other : LC50 (Daphnia (water flea)):  $> 1 - 10$  mg/l  
aquatic invertebratesToxicity to microorganisms : EC50 (Bacteria):  $> 1 - 10$  mg/l**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023**12.2 Persistence and degradability****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Readily biodegradable.

Photodegradation : Decomposes rapidly in contact with light.

**n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

**12.3 Bioaccumulative potential****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Bioaccumulation is unlikely.

Partition coefficient: n-  
octanol/water : log Pow: 2.77 - 3.15

**n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-  
octanol/water : log Pow: 1.81

**12.4 Mobility in soil****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environ-  
mental compartments : Koc: 537, log Koc: 2.73  
Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

## MOBIHEL 2K HARDENER 700

Version  
3.0Revision Date:  
22.04.2026SDS Number:  
MAT000418256  
JO/ENDate of last issue: 06.05.2024  
Date of first issue: 28.11.2023**12.5 Results of PBT and vPvB assessment****Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects****Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information****14.1 UN number**

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

## 14.2 UN proper shipping name

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

## 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

## 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

**IATA (Passenger)**

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**14.5 Environmental hazards****ADN**

Environmentally hazardous : no

**ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

---

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this substance.

---

**SECTION 16: Other information****Full text of H-Statements**

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.

## MOBIHEL 2K HARDENER 700

Version	Revision Date:	SDS Number:	Date of last issue: 06.05.2024
3.0	22.04.2026	MAT000418256 JO/EN	Date of first issue: 28.11.2023

H332 : Harmful if inhaled.  
 H335 : May cause respiratory irritation.  
 H336 : May cause drowsiness or dizziness.  
 H373 : May cause damage to organs through prolonged or repeated exposure.  
 H411 : Toxic to aquatic life with long lasting effects.  
 H412 : Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox. : Acute toxicity  
 Aquatic Chronic : Long-term (chronic) aquatic hazard  
 Asp. Tox. : Aspiration hazard  
 Eye Irrit. : Eye irritation  
 Flam. Liq. : Flammable liquids  
 Skin Irrit. : Skin irritation  
 Skin Sens. : Skin sensitisation  
 STOT RE : Specific target organ toxicity - repeated exposure  
 STOT SE : Specific target organ toxicity - single exposure  
 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
 2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
 98/24/EC I : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values  
 2000/39/EC / TWA : Limit Value - eight hours  
 2000/39/EC / STEL : Short term exposure limit  
 2019/1831/EU / TWA : Limit Value - eight hours  
 2019/1831/EU / STEL : Short term exposure limit  
 98/24/EC I / STEL : Limit values Short-term  
 98/24/EC I / TWA : Limit values 8 hours

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

## MOBIHEL 2K HARDENER 700

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000418256  
JO/EN

Date of last issue: 06.05.2024  
Date of first issue: 28.11.2023

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information****Classification of the mixture:**

Flam. Liq. 3	H226
Acute Tox. 4	H332
Acute Tox. 4	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.