

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL 2K fade out thinner 2400 VOC

Product code : 470173

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Call 999 (or 112) for emergency medical attention

professionals only: National Poison Information Service (NPIS) 24h national number 0844 892  
0111

consumer: National Health Service (NHS) 24h national number, England & Scotland 111

Access code: 13586 +44 20 3514 7487

Access code: 13586 +44 800 680 0425

Access code: 13586 +44 808 189 0979

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version 3.0	Revision Date: 22.04.2026	SDS Number: MAT000470173 GB/EN	Date of last issue: 27.06.2025 Date of first issue: 26.08.2021
----------------	------------------------------	--------------------------------------	---

### SECTION 2: Hazards identification




#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

Precautionary statements	:	<b>Prevention:</b>
		P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P260 Do not breathe mist or vapours.
		P264 Wash skin thoroughly after handling.
		<b>Response:</b>
		P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
		P331 Do NOT induce vomiting.
		P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

n-butyl acetate  
2-methoxy-1-methylethyl acetate  
reaction mixture of ethylbenzene, m-xylene and p-xylene  
Hydrocarbons, C9 aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4  204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
2-methoxy-1-methylethyl acetate	108-65-6  203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
reaction mixture of ethylbenzene, m-	-	Flam. Liq. 3; H226	>= 10 - < 20

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

xylene and p-xylene	905-562-9 01-2119555267-33, 01-2119488216-32	Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
2-butoxyethyl acetate	112-07-2  203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312	>= 2,5 - < 10
Hydrocarbons, C9 aromatics	64742-95-6  918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 1 - < 2,5

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the ap-

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000470173 GB/EN      Date of last issue: 27.06.2025      Date of first issue: 26.08.2021

- plication area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m <sup>3</sup>	GB EH40
		STEL	200 ppm 966 mg/m <sup>3</sup>	GB EH40
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

	Further information: Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 332 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	20 ppm 133 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 333 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT

### Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
		Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
		Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
		Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
		Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3,4 mg/kg bw/day
			Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
			Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	550 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14,8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	333 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	86 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	169 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	120 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	72 mg/kg

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

			fects	bw/day
	Consumers	Oral	Acute systemic effects	36 mg/kg bw/day
Hydrocarbons, C9 aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Oral	Long-term systemic effects	150 mg/m3
	Consumers	Inhalation	Long-term exposure	32 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day

### Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
n-butyl acetate	Soil	0,0903 mg/kg dry weight (d.w.)
	Marine water	0,018 mg/l
	Fresh water	0,18 mg/l
	Marine sediment	0,0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35,6 mg/l
	Intermittent use/release	0,36 mg/l
2-methoxy-1-methylethyl acetate	Soil	0,29 mg/kg dry weight (d.w.)
	Marine water	0,0635 mg/l
	Fresh water	0,635 mg/l
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0,00635 mg/l
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2,31 mg/kg dry weight (d.w.)
	Marine water	0,327 mg/l
	Fresh water	0,327 mg/l
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6,58 mg/l
	Intermittent use/release	0,327 mg/l
2-butoxyethyl acetate	Soil	0,415 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version 3.0      Revision Date: 22.04.2026      SDS Number: MAT000470173 GB/EN      Date of last issue: 27.06.2025      Date of first issue: 26.08.2021

	Marine water	0,0304 mg/l
	Fresh water	0,304 mg/l
	Marine sediment	0,203 mg/kg dry weight (d.w.)
	Fresh water sediment	2,03 mg/kg dry weight (d.w.)
	Sewage treatment plant	90 mg/l
	Intermittent use/release	0,56 mg/l

### 8.2 Exposure controls

#### Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles
- Hand protection  
Gloves : Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic vapour type (A)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid  
Colour : in accordance with the product description  
Odour : none  
Odour Threshold : No data available
- pH : Not applicable
- Melting point/freezing point : -78,0 °C  
(calculation method (principal components, lowest value))
- Boiling point/boiling range : 126 °C (calculation method (principal components, lowest value))

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

Flash point : 37 °C

Evaporation rate : No data available

Flammability : Static-accumulating flammable liquid., Combustible Solids

Upper explosion limit / Upper flammability limit : 8,4 %(V)  
(calculation method (principal components, highest value))

Lower explosion limit / Lower flammability limit : 1,1 %(V)  
(calculation method (principal components, highest value))

Vapour pressure : < 1.100 hPa (calculation method (principal components, highest value))  
(50 °C)

Relative vapour density : 5,5 (calculation method (principal components, highest value))  
(Air = 1.0)

Relative density : 0,91 (calculation method (principal components, highest value))

Density : 0,913 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : immiscible, partly soluble  
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15 (calculation method (principal components, highest value))

Ignition temperature : 280 °C (calculation method (principal components, highest value))

Decomposition temperature : No decomposition if used as directed.  
Hazardous decomposition products formed under fire conditions.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

Viscosity  
Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not applicable

Oxidizing properties : Sustains combustion

### 9.2 Other information

No data available  
VOC : (Directive 2010/75/EU of 24 November 2010 on industrial and  
livestock rearing emissions (integrated pollution prevention  
and control))  
99,82 %

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version 3.0	Revision Date: 22.04.2026	SDS Number: MAT000470173 GB/EN	Date of last issue: 27.06.2025 Date of first issue: 26.08.2021
----------------	------------------------------	--------------------------------------	---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified due to lack of data.

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): >= 10.760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5.000 mg/kg

##### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour  
  
LC0 (Rat): 2000 ppm  
Exposure time: 3 h

Acute dermal toxicity : LD50 (Rabbit): > > 2.000 mg/kg

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat): >= 8.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): 27,14 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

### 2-butoxyethyl acetate:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat):  $\geq 2.400$  mg/kg

Acute inhalation toxicity : LC50 (Rat):  $\geq 50$  mg/l

Exposure time: 2 h

Test atmosphere: vapour

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

LD50 (Rabbit):  $\geq 1.500$  mg/kg

### Hydrocarbons, C9 aromatics:

Acute dermal toxicity : LD50 (Rabbit):  $> 3.160$  mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : irritating

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Result : Eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

---

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **2-methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

#### **Hydrocarbons, C9 aromatics:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### **Components:**

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C9 aromatics:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

### Endocrine disrupting properties

#### Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f), at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l  
EC50 (Desmodesmus subspicatus (green algae)): >= 647,7 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

##### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h  
NOEC : 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 : 408 mg/l  
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : EC10: 47,5 mg/l

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

### reaction mixture of ethylbenzene, m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/l

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 91,2 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l

### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### 2-butoxyethyl acetate:

Toxicity to fish : LC50 (Fish):  $\geq 31$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 142,5$  mg/l  
Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria):  $\geq 2.800$  mg/l

### Hydrocarbons, C9 aromatics:

Toxicity to fish : LC50 (Fish):  $\geq 9,2$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 3,2$  mg/l  
Exposure time: 48 h

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### Components:

#### n-butyl acetate:

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Remarks: Readily biodegradable.

### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

### **2-butoxyethyl acetate:**

Biodegradability : Result: Biodegradable

## 12.3 Bioaccumulative potential

### Components:

#### **n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1,81

#### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8

#### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

#### **2-butoxyethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,51

#### **Hydrocarbons, C9 aromatics:**

Partition coefficient: n-octanol/water : log Pow: < 4

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

### 12.4 Mobility in soil

#### Components:

##### **reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2,73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

#### **Hydrocarbons, C9 aromatics:**

Mobility : Medium: Air  
Content: 92,9 %

: Medium: Water  
Content: 3,5 %

: Medium: Soil  
Content: 1,9 %

: Medium: Sediment  
Content: 1,8 %

Distribution among environmental compartments : Koc: 1,71 - 14,70  
Remarks: Mobile in soils

Remarks: The product is insoluble and floats on water.

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version  
3.0

Revision Date:  
22.04.2026

SDS Number:  
MAT000470173  
GB/EN

Date of last issue: 27.06.2025  
Date of first issue: 26.08.2021

### Endocrine disrupting properties

#### Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL  
ADR : PAINT RELATED MATERIAL  
RID : PAINT RELATED MATERIAL  
IMDG : PAINT RELATED MATERIAL  
IATA : Paint related material

### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173	Date of first issue: 26.08.2021
		GB/EN	

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

#### ADN

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### ADR

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

#### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

#### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3  Number on list 40 This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable
Control of Major Accident Hazards Regulations P5c	:	FLAMMABLE LIQUIDS

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173	Date of first issue: 26.08.2021
		GB/EN	

2015 (COMAH)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 99,82 %

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by  
UK REACH Regulations SI 2019/758



## MOBIHEL 2K fade out thinner 2400 VOC

Version	Revision Date:	SDS Number:	Date of last issue: 27.06.2025
3.0	22.04.2026	MAT000470173 GB/EN	Date of first issue: 26.08.2021

---

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.