

## MOBIHEL PRIMER

Version 2.0	Revision Date: 22.04.2026	SDS Number: MAT0GA05_028 JO/EN	Date of last issue: 28.11.2023 Date of first issue: 28.11.2023
----------------	------------------------------	--------------------------------------	---

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : MOBIHEL PRIMER

Product code : Please see section 16 for detailed data

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions  
on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

#### 1.4 Emergency telephone number

Emergency telephone number: 911

Access code: 13586 +1 760 476 3959

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger

Hazard statements

H226 H315 H318 H335 H336 H412	Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
--	--

Precautionary statements

**Prevention:**

P210 P261 P264 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist or vapours. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
------------------------------	---

**Response:**

P305 + P351 + P338 + P310 P370 + P378	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
--	--

Hazardous components which must be listed on the label:

2-methylpropan-1-ol  
propan-2-ol  
butan-1-ol

**Additional Labelling**

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

EUH208 Contains Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine, Bisphenol F (all isomers) as an oligomer; part of a polymer, formaldehyde. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-methylpropan-1-ol	78-83-1 201-148-0 603-108-00-1 01-2119484609-23	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
1-butanol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 3 - < 10
Urea P/W	68002-18-6	Aquatic Chronic 4; H413	>= 1 - < 2.5

## SAFETY DATA SHEET



## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0.25 - < 1$
phenol, pure	108-95-2 203-632-7 604-001-00-2 01-2119471329-32	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Muta. 2; H341 STOT RE 2; H373 Aquatic Chronic 2; H411	$\geq 0.25 - < 1$
zinc 5-nitroisophthalate	60580-61-2	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	$\geq 0.1 - < 0.25$
Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine	85586-38-5 287-840-3 01-2119976294-27	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	$\geq 0.1 - < 0.25$
Bisphenol F (all isomers) as an oligomer; part of a polymer	1333-16-0	Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	$\geq 0.025 - < 0.1$
formaldehyde	50-00-0 200-001-8 605-001-00-5 01-2119488953-20	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Muta. 2; H341 Carc. 1B; H350	$< 0.1$
Substances with a workplace exposure limit :			
talc	14807-96-6 238-877-9 01-2120140278-58		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

## MOBIHEL PRIMER

Version  
2.0

Revision Date:  
22.04.2026

SDS Number:  
MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.
- Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

## MOBIHEL PRIMER

Version  
2.0

Revision Date:  
22.04.2026

SDS Number:  
MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

**MOBIHEL PRIMER**

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	22.04.2026	MAT0GA05_028 JO/EN	Date of first issue: 28.11.2023

---

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	TWA (Respirable dust)	0.1 mg/m <sup>3</sup>	2004/37/EC
phenol	108-95-2	TWA	2 ppm 8 mg/m <sup>3</sup>	2009/161/EU
		STEL	4 ppm 16 mg/m <sup>3</sup>	2009/161/EU
formaldehyde	50-00-0	TWA	0.3 ppm 0.37 mg/m <sup>3</sup>	2004/37/EC
		STEL	0.6 ppm 0.74 mg/m <sup>3</sup>	2004/37/EC

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006**

Substance name	End Use	Exposure routes	Potential health effects	Value
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	89 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	888 mg/kg bw/day
butan-1-ol	Consumers	Dermal	Long-term systemic effects	319 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	26 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	310 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	55.357 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	155 mg/m <sup>3</sup>

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

	Consumers	Dermal	Long-term systemic effects	3.125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.562 mg/kg bw/day
Talc	Workers	Inhalation	Acute systemic effects	2.16 mg/m3
	Workers	Inhalation	Acute local effects	3.6 mg/m3
	Consumers	Inhalation	Acute systemic effects	1.08 mg/m3
	Consumers	Inhalation	Acute local effects	1.8 mg/m3
	Consumers	Dermal	Long-term local effects	2.27 mg/cm2
	Workers	Dermal	Long-term local effects	4.54 mg/cm2
	Consumers	Oral	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	160 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	43.2 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	21.6 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local effects	0.5 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2.5 mg/m3
	Workers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.83 mg/kg bw/day
phenol	Workers	Inhalation	Long-term systemic effects	8 mg/m3
	Workers	Inhalation	Acute local effects	16 mg/m3
	Workers	Dermal	Long-term systemic effects	1.23 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.32 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.4 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.4 mg/kg bw/day

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

formaldehyde	Workers	Inhalation	Long-term systemic effects	9 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0.75 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	240 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	0.037 mg/cm <sup>2</sup>
	Consumers	Inhalation	Long-term systemic effects	3.2 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	0.1 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0.012 mg/cm <sup>2</sup>
	Consumers	Ingestion	Long-term systemic effects	4.1 mg/kg bw/day

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006**

Substance name	Environmental Compartment	Value
2-methylpropan-1-ol	Soil	0.0765 mg/kg dry weight (d.w.)
	Marine water	0.04 mg/l
	Fresh water	0.4 mg/l
	Marine sediment	0.156 mg/kg dry weight (d.w.)
	Fresh water sediment	1.56 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	11 mg/l
propan-2-ol	Soil	28 mg/kg
	Marine water	140.9 mg/l
	Fresh water	140.9 mg/l
	Fresh water sediment	552 mg/kg dry weight (d.w.)
	Sewage treatment plant	2251 mg/l
butan-1-ol	Intermittent use/release	140.9 mg/l
	Soil	0.0166 mg/kg dry weight (d.w.)
	Marine water	0.0082 mg/l
	Fresh water	0.082 mg/l
	Marine sediment	0.0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0.324 mg/kg dry weight (d.w.)
Talc	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2.25 mg/l
	Marine water	141.26 mg/l

# SAFETY DATA SHEET



## MOBIHEL PRIMER

Version  
2.0

Revision Date:  
22.04.2026

SDS Number:  
MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

	Fresh water	597.97 mg/l
	Marine sediment	3.13 mg/kg dry weight (d.w.)
	Fresh water sediment	31.33 mg/kg dry weight (d.w.)
	Intermittent use/release	597.97 mg/l
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
zinc oxide	Soil	35.6 mg/kg dry weight (d.w.)
	Marine water	0.0061 mg/l
	Fresh water	0.0206 mg/l
	Marine sediment	56.5 mg/kg dry weight (d.w.)
	Fresh water sediment	117.8 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.1 mg/l
phenol	Marine water	0.77 mg/l
	Fresh water	0.0077 mg/l
	Marine sediment	0.00915 mg/kg dry weight (d.w.)
	Marine sediment	0.136 mg/kg dry weight (d.w.)
	Fresh water sediment	0.0915 mg/kg dry weight (d.w.)
	Sewage treatment plant	2.1 mg/l
	Intermittent use/release	0.031 mg/l
zinc 5-nitroisophthalate	Fresh water	0.0206 - 0.0808 mg/l
	Marine water	0.0061 - 0.0239 mg/l
	Sewage treatment plant	0.100 - 0.3922 mg/l
	Fresh water sediment	117.8 - 462 mg/kg dry weight (d.w.)
	Marine sediment	56.5 - 221 mg/kg dry weight (d.w.)
	Soil	56.5 - 221 mg/kg dry weight (d.w.)

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine	Fresh water	0.022 mg/l
	Intermittent use/release	0.291 mg/l
	Sewage treatment plant	1.35 mg/l
	Fresh water sediment	0.244 mg/kg dry weight (d.w.)
	Marine sediment	0.0244 mg/kg dry weight (d.w.)
	Soil	0.123 mg/kg dry weight (d.w.)
formaldehyde	Fresh water	0.44 mg/l
	Marine water	0.44 mg/l
	Intermittent use/release	4.44 mg/l
	Sewage treatment plant	0.19 mg/l
	Fresh water sediment	2.3 mg/kg
	Marine sediment	2.3 mg/kg
	Soil	0.2 mg/kg

## 8.2 Exposure controls

## Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection  
Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |  
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |  
Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapour type (A-P)

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Physical state	:	liquid
Form	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Flash point	:	23 °C Method: ISO 3679, closed cup
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.920 - 1.095 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity		
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (40 °C)
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion

## MOBIHEL PRIMER

Version 2.0	Revision Date: 22.04.2026	SDS Number: MAT0GA05_028 JO/EN	Date of last issue: 28.11.2023 Date of first issue: 28.11.2023
----------------	------------------------------	--------------------------------------	---

---

**9.2 Other information**

No data available  
VOC : (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))  
70.16 %

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid : Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Incompatible with strong acids and bases.

**10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Not classified based on available information.  
Not classified due to lack of data.

**Product:**

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

---

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method**Components:****2-methylpropan-1-ol:**Acute oral toxicity : LD50 Oral (Rat):  $\geq$  2,460 mg/kgAcute dermal toxicity : LD50 (Rabbit):  $\geq$  3,400 mg/kg**propan-2-ol:**Acute oral toxicity : LD50 Oral (Rat):  $\geq$  5,840 mg/kgAcute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapourAcute dermal toxicity : LD50 (Rabbit):  $\geq$  13,900 mg/kg**butan-1-ol:**

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

LD50 Oral (Rat): &gt; 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): &gt; 2,000 mg/kg

**phenol:**

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: dust/mist  
Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

**Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine:**

Acute oral toxicity : LD50 (Rat): 2000

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**formaldehyde:**

- Acute oral toxicity : 100 mg/kg  
Assessment: The component/mixture is toxic after single ingestion.
- Acute inhalation toxicity : 100 ppm  
Test atmosphere: vapour  
Assessment: The component/mixture is highly toxic after short term inhalation.
- Acute dermal toxicity : 270 mg/kg  
Assessment: The component/mixture is toxic after single contact with skin.

**Skin corrosion/irritation**

Causes skin irritation.  
Causes skin irritation.

**Product:**

Remarks : Extremely corrosive and destructive to tissue.

**Components:****2-methylpropan-1-ol:**

Result : irritating

**butan-1-ol:**

Result : irritating

**phenol:**

Result : Corrosive after 3 minutes to 1 hour of exposure

**Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine:**

Result : irritating

**formaldehyde:**

Result : Corrosive after 3 minutes to 1 hour of exposure

**Serious eye damage/eye irritation**

Causes serious eye damage.  
Causes serious eye damage.

**Product:**

Remarks : May cause irreversible eye damage.

## MOBIHEL PRIMER

Version  
2.0

Revision Date:  
22.04.2026

SDS Number:  
MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

### Components:

#### **2-methylpropan-1-ol:**

Result : Corrosive

#### **propan-2-ol:**

Result : Eye irritation

#### **butan-1-ol:**

Result : Corrosive

#### **Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine:**

Result : Blindness

#### **Bisphenol F (all isomers) as an oligomer; part of a polymer:**

Result : Blindness

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Skin sensitisation**

Not classified due to lack of data.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified due to lack of data.

### Product:

Remarks : Causes sensitisation.

### Components:

#### **Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine:**

Result : May cause sensitisation by skin contact.

#### **Bisphenol F (all isomers) as an oligomer; part of a polymer:**

Result : The product is a skin sensitizer, sub-category 1A.

#### **formaldehyde:**

Result : Probability or evidence of skin sensitisation in humans

## MOBIHEL PRIMER

Version  
2.0

Revision Date:  
22.04.2026

SDS Number:  
MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

### **Germ cell mutagenicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **Components:**

##### **phenol:**

Germ cell mutagenicity- Assessment : In vitro tests showed mutagenic effects

##### **formaldehyde:**

Germ cell mutagenicity- Assessment : In vitro tests showed mutagenic effects

### **Carcinogenicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **Components:**

##### **formaldehyde:**

Carcinogenicity - Assessment : Possible human carcinogen

### **Reproductive toxicity**

Not classified based on available information.  
Not classified due to lack of data.

#### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

#### **Components:**

##### **2-methylpropan-1-ol:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

##### **propan-2-ol:**

Assessment : May cause drowsiness or dizziness.

##### **butan-1-ol:**

Assessment : May cause drowsiness or dizziness.

**MOBIHEL PRIMER**Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

Assessment : May cause respiratory irritation.

**STOT - repeated exposure**Not classified based on available information.  
Not classified due to lack of data.**Components:****phenol:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard**Not classified based on available information.  
Not classified due to lack of data.**Further information****Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:****2-methylpropan-1-ol:**Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h**propan-2-ol:**Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 48 hToxicity to daphnia and other : LC50 (Daphnia (water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria): &gt; 1,000 mg/l

**butan-1-ol:**

Toxicity to fish : LC50 (Fish): &gt; 1,000 mg/l

## MOBIHEL PRIMER

Version 2.0      Revision Date: 22.04.2026      SDS Number: MAT0GA05\_028  
JO/EN      Date of last issue: 28.11.2023      Date of first issue: 28.11.2023

---

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

### **Urea P/W:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

### **zinc oxide:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)):  $\geq 1.793$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)):  $\geq 2.6$  mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : IC50 (Desmodesmus subspicatus (green algae)):  $\geq 0.136$  mg/l  
Exposure time: 72 h

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### **phenol:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### **zinc 5-nitroisophthalate:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### **Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine:**

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

**Bisphenol F (all isomers) as an oligomer; part of a polymer:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability****Components:****2-methylpropan-1-ol:**

Biodegradability : Result: Biodegradable

**zinc oxide:**

Biodegradability : Result: Biodegradable

**12.3 Bioaccumulative potential****Components:****2-methylpropan-1-ol:**Partition coefficient: n-  
octanol/water : log Pow: 0.79**propan-2-ol:**Partition coefficient: n-  
octanol/water : log Pow: 0.05**butan-1-ol:**Partition coefficient: n-  
octanol/water : log Pow: 0.785**phenol:**Partition coefficient: n-  
octanol/water : log Pow: 1.47**Sulfuric acid, mono-C8-18-alkyl esters, magnesium salts, compds. with triethanolamine:**Partition coefficient: n-  
octanol/water : log Pow: -0.62 (20 °C)**formaldehyde:**Partition coefficient: n-  
octanol/water : log Pow: 0.35

## MOBIHEL PRIMER

Version 2.0	Revision Date: 22.04.2026	SDS Number: MAT0GA05_028 JO/EN	Date of last issue: 28.11.2023 Date of first issue: 28.11.2023
----------------	------------------------------	--------------------------------------	---

---

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1263  
ADR : UN 1263

## MOBIHEL PRIMER

Version 2.0      Revision Date: 22.04.2026      SDS Number: MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

**RID** : UN 1263  
**IMDG** : UN 1263  
**IATA** : UN 1263

**14.2 UN proper shipping name**

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

**14.3 Transport hazard class(es)**

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

**14.4 Packing group**

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

## MOBIHEL PRIMER

Version 2.0      Revision Date: 22.04.2026      SDS Number: MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### **14.5 Environmental hazards**

#### **ADN**

Environmentally hazardous : no

#### **ADR**

Environmentally hazardous : no

#### **RID**

Environmentally hazardous : no

#### **IMDG**

Marine pollutant : no

### **14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

---

## **SECTION 15: Regulatory information**

### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

### **15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this substance.

## MOBIHEL PRIMER

Version  
2.0Revision Date:  
22.04.2026SDS Number:  
MAT0GA05\_028  
JO/ENDate of last issue: 28.11.2023  
Date of first issue: 28.11.2023

## SECTION 16: Other information

## Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H341	: Suspected of causing genetic defects.
H350	: May cause cancer.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

## Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Muta.	: Germ cell mutagenicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III
2009/161/EU	: Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
2004/37/EC / STEL	: Short term exposure limit

## MOBIHEL PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: 28.11.2023
2.0	22.04.2026	MAT0GA05_028	Date of first issue: 28.11.2023
		JO/EN	

2004/37/EC / TWA : Long term exposure limit  
 2009/161/EU / TWA : Limit Value - eight hours  
 2009/161/EU / STEL : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information****Classification of the mixture:**

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
STOT SE 3	H335
Aquatic Chronic 3	H412

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

# SAFETY DATA SHEET



## MOBIHEL PRIMER

Version  
2.0

Revision Date:  
22.04.2026

SDS Number:  
MAT0GA05\_028  
JO/EN

Date of last issue: 28.11.2023  
Date of first issue: 28.11.2023

---

Material codes (bulk) for which the SDS is valid : 407071; 409264; 480792; 480793

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.