

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL HYDRO Base MIX

Product code : Please see section 16 for detailed data

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : PC9a: Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healthcare Professionals 01 809 2566

01 809 2566 Healthcare Professionals 01 809 2566

Access code: 13586 +1 760 476 3962

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.

Reproductive toxicity, Category 1B H360D: May damage the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 Causes serious eye damage.
H360D May damage the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

butan-1-ol
N-methyl-2-pyrrolidone

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1,200 mg/kg Acute inhalation toxicity (vapour): 3 mg/l	>= 1 - < 10
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 3 - < 10
N-methyl-2-pyrrolidone	872-50-4 212-828-1 606-021-00-7 01-2119472430-46	Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 10 %	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

		Acute toxicity estimate Acute inhalation toxicity (vapour): 5.1 mg/l	
2-dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 5 %	>= 0.1 - < 1
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 >= 0.036 % Acute toxicity estimate Acute oral toxicity: 450 mg/kg Acute inhalation toxicity (dust/mist): 0.21 mg/l	>= 0.0025 - < 0.025
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6	Acute Tox. 3; H301 Acute Tox. 2; H330	>= 0.0002 - < 0.0015

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

	613-326-00-9 01-2120764690-50	Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
		specific concentration limit Skin Sens. 1A; H317 >= 0.0015 %	
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0.0002 - < 0.0015
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Corr. 1C; H314 >= 0.6 % Skin Irrit. 2; H315 0.06 - < 0.6 % Eye Irrit. 2; H319 0.06 - < 0.6 % Skin Sens. 1A; H317 >= 0.0015 % Eye Dam. 1; H318	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

		>= 0.6 %	
--	--	----------	--

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye damage.
May damage the unborn child.
- Causes serious eye damage.
May damage the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

		of exposure)		
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		OELV - 8 hrs (TWA)	20 ppm 98 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	50 ppm 246 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
butan-1-ol	71-36-3	OELV - 8 hrs (TWA)	20 ppm	IE OEL
aluminium	7429-90-5	OELV - 8 hrs (TWA) (Respira- ble dust)	1 mg/m ³	IE OEL
N-methyl-2- pyrrolidone	872-50-4	TWA	10 ppm 40 mg/m ³	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	20 ppm 80 mg/m ³	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	10 ppm 40 mg/m ³	2004/37/EC
	Further information: Skin, Carcinogens or mutagens			
		STEL	20 ppm 80 mg/m ³	2004/37/EC
	Further information: Skin, Carcinogens or mutagens			
		OELV - 8 hrs (TWA)	10 ppm 40 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	20 ppm 80 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respira- ble dust)	4 mg/m ³	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m ³	IE OEL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Inhalation	Acute local effects	246 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	59 mg/m ³
	Consumers	Inhalation	Acute systemic effects	426 mg/m ³
	Consumers	Inhalation	Acute local effects	147 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	125 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	75 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	89 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	6.3 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	26.7 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	55.357 mg/m ³
	Consumers	Inhalation	Long-term local effects	155 mg/m ³
	Consumers	Dermal	Long-term systemic effects	3.125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.562 mg/kg bw/day
aluminium	Workers	Inhalation	Long-term systemic effects	3.72 mg/m ³
	Workers	Inhalation	Long-term local effects	3.72 mg/m ³
	Consumers	Oral	Long-term systemic effects	3.95 mg/kg bw/day
N-methyl-2-pyrrolidone	Workers	Inhalation	Long-term local effects	40 mg/m ³
	Workers	Inhalation	Long-term systemic effects	14.4 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	3.6 mg/m ³
	Workers	Dermal	Long-term systemic effects	4.8 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef-	4.5 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

			fects	
	Consumers	Dermal	Long-term systemic effects	2.4 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.85 mg/kg bw/day
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m ³
	Consumers	Oral	Long-term systemic effects	700 mg/kg bw/day
2-dimethylaminoethanol	Workers	Inhalation	Long-term systemic effects	7.4 mg/m ³
	Workers	Inhalation	Acute local effects	22 mg/m ³
	Workers	Dermal	Acute local effects	0.08 mg/cm ²
	Workers	Dermal	Long-term systemic effects	1.04 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	5 mg/kg bw/day
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m ³
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg bw/day
reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H - isothiazol-3- one (3:1)	Consumers	Inhalation	Acute local effects	0.04 mg/m ³
	Workers	Inhalation	Long-term local effects	0.02 mg/m ³
	Workers	Inhalation	Acute local effects	0.04 mg/m ³
	Consumers	Inhalation	Long-term local effects	0.02 mg/m ³
	Consumers	Oral	Long-term systemic effects	0.09 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	0.11 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2-butoxyethanol	Soil	2.33 mg/kg dry weight (d.w.)
	Marine water	0.88 mg/l
	Fresh water	8.8 mg/l
	Fresh water sediment	34.6 mg/kg dry weight (d.w.)
	Sewage treatment plant	463 mg/l
	Intermittent use/release	9.1 mg/l
butan-1-ol	Soil	0.0166 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

		weight (d.w.)
	Marine water	0.0082 mg/l
	Fresh water	0.082 mg/l
	Marine sediment	0.0324 mg/kg dry weight (d.w.)
	Fresh water sediment	0.324 mg/kg dry weight (d.w.)
	Sewage treatment plant	2476 mg/l
	Intermittent use/release	2.25 mg/l
aluminium	Sewage treatment plant	20 mg/l
N-methyl-2-pyrrolidone	Soil	0.07 mg/kg dry weight (d.w.)
	Marine water	0.025 mg/l
	Fresh water	0.25 mg/l
	Fresh water sediment	1.09 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	5 mg/l
	Marine sediment	0.109 mg/kg dry weight (d.w.)
titanium dioxide	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0.0184 mg/l
	Fresh water	0.184 mg/l
	Marine sediment	100 mg/kg dry weight (d.w.)
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	0.193 mg/l
2-dimethylaminoethanol	Soil	0.0177 mg/kg dry weight (d.w.)
	Marine water	0.00661 mg/l
	Fresh water	0.0661 mg/l
	Fresh water sediment	0.0529 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	0.0661 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0.00403 mg/l
	Intermittent use/release	0.0011 mg/l
	Marine water	0.000403 mg/l
	Sewage treatment plant	1.03 mg/l
	Fresh water sediment	0.0499 mg/kg dry weight (d.w.)
	Marine sediment	0.00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3- one	Soil	0.01 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

(3:1)		
	Marine water	0.00339 mg/l
	Fresh water	0.00339 mg/l
	Marine sediment	0.027 mg/kg dry weight (d.w.)
	Fresh water sediment	0.027 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.23 mg/l
	Intermittent use/release	0.00339 mg/l

8.2 Exposure controls

Individual protection measures, such as personal protective equipment (PPE)

- Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection
- Gloves : Nitrile rubber (> 0,1 mm; < 60 min); ISO EN374 |
butyl-rubber (> 0,6 mm; < 240 min); ISO EN374 |
Viton® (> 0,6 mm; < 240 min); ISO EN374 |
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387
- Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Form	:	liquid
Colour	:	in accordance with the product description
Odour	:	solvent-like
Odour Threshold	:	No data available
Melting point/freezing point	:	0.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	100 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Flash point	:	66 °C
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	:	Not applicable
Viscosity Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C)
Flow time	:	35 - 45 s at 20 °C Cross section: 4 mm Method: DIN4
Solubility(ies) Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Vapour pressure : 23 hPa (calculation method (principal components, highest value))
(20 °C)

Relative density : No data available

Density : 0.99 - 1.213 g/cm³

Relative vapour density : No data available

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

VOC : (Directive 2004/42/EC)
410 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1,200 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute inhalation toxicity : LC50 (Rat): 450 ppm
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is toxic after short term
inhalation.

Acute toxicity estimate: 3 mg/l
Test atmosphere: vapour

butan-1-ol:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after
single ingestion.

LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

N-methyl-2-pyrrolidone:

Acute oral toxicity : LD50 Oral (Rat): \geq 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): \geq 5.1 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rat): $\geq 5,000$ mg/kg

2-dimethylaminoethanol:

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : Acute toxicity estimate: 450 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0.21 mg/l
Test atmosphere: dust/mist
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Test atmosphere: vapour
Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

Skin corrosion/irritation

Not classified based on available information.

Not classified due to lack of data.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

2-butoxyethanol:

Result : irritating

butan-1-ol:

Result : irritating

N-methyl-2-pyrrolidone:

Result : irritating

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

1,2-benzisothiazol-3(2H)-one:

Result : irritating

2-methylisothiazol-3(2H)-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.
Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

2-butoxyethanol:

Result : Eye irritation

butan-1-ol:

Result : Corrosive

N-methyl-2-pyrrolidone:

Result : Eye irritation

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

2-methylisothiazol-3(2H)-one:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.
Not classified due to lack of data.

Carcinogenicity

Not classified based on available information.
Not classified due to lack of data.

Reproductive toxicity

May damage the unborn child.
May damage the unborn child.

Components:

N-methyl-2-pyrrolidone:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.
Not classified due to lack of data.

Components:

butan-1-ol:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

N-methyl-2-pyrrolidone:

Assessment : May cause respiratory irritation.

2-dimethylaminoethanol:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.
Not classified due to lack of data.

Aspiration hazard

Not classified based on available information.
Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-butoxyethanol:

Toxicity to fish : LC50 (Fish): \geq 1,700 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l
Exposure time: 48 h

Toxicity to microorganisms : EC50 (Bacteria): > 5,000 mg/l

butan-1-ol:

Toxicity to fish : LC50 (Fish): > 1,000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

1,2-benzisothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic toxicity) : 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

icity)

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1):

Toxicity to fish : LC50 (Salvelinus namaycush (lake trout)): ≥ 10.85 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : LC50 (algae): ≥ 0.82 mg/l
Exposure time: 48 h

LC50 (algae): 0.018 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

Components:

2-butoxyethanol:

Biodegradability : Result: Biodegradable

Stability in water : Hydrolyses slowly.

Photodegradation : Decomposes slowly in contact with light.

2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Biodegradable

12.3 Bioaccumulative potential

Components:

2-butoxyethanol:

Partition coefficient: n-octanol/water : log Pow: 0.81 (20 °C)

butan-1-ol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Partition coefficient: n-octanol/water : log Pow: 0.785

N-methyl-2-pyrrolidone:

Partition coefficient: n-octanol/water : log Pow: -0.46

2-dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0.55

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-octanol/water : log Pow: 1.3

12.4 Mobility in soil

Components:

2-butoxyethanol:

Mobility : Medium: Air
Content: 1 %
: Medium: Water
Content: 47 %
: Medium: Soil
Content: 52 %

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

2-butoxyethanol:

Assessment : Not persistent, bioaccumulative, and toxic (PBT).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

Waste Code : 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00, wastes from MFSU and removal of paint and varnish
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00, packaging (including separately collected municipal packaging waste)
15 01 10, packaging containing residues of or contaminated by hazardous substances
HP4, Irritant - skin irritation and eye damage
HP10, Toxic for reproduction

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version 2.0 Revision Date: 28.05.2026 SDS Number: MAT0GA05_010IE/EN Date of last issue: 06.09.2023
Date of first issue: 06.09.2023

IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Number on list 30: N-methyl-2-pyrrolidone

Number on list 40
This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 71: N-methyl-2-pyrrolidone

Number on list 72: N-methyl-2-pyrrolidone

Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

Number on list 78:
3906 acrylic polymers

synthetic polymer microparticles (SPM) content: 1.3 %
The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : N-methyl-2-pyrrolidone

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: 410 g/l

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H360D	: May damage the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.

Full text of other abbreviations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
STOT SE	:	Specific target organ toxicity - single exposure
Skin Sens.	:	Skin sensitisation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Eye Irrit.	:	Eye irritation
Skin Sens.	:	Skin sensitisation
Eye Dam.	:	Serious eye damage
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III
2009/161/EU	:	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
IE OEL	:	Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2009/161/EU / TWA	:	Limit Value - eight hours
2009/161/EU / STEL	:	Short term exposure limit
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good La-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL HYDRO Base MIX

Version	Revision Date:	SDS Number:	Date of last issue: 06.09.2023
2.0	28.05.2026	MAT0GA05_010IE/ EN	Date of first issue: 06.09.2023

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Eye Dam. 1	H318
Repr. 1B	H360D

Classification procedure:

Calculation method
Calculation method

Material codes (bulk) for which the SDS is valid	400929 , 400996, 401107, 401194, 401196, 402738, 402747, 402749, 470600, 470601, 470608, 470610, 470612, 470613, 470614, 470616, 470617, 470618, 470619, 470621, 470622, 470625, 470626, 470627, 470628, 470629, 470630, 470631, 470632, 470633, 470641, 470642, 470643, 470644, 470645, 470646, 470651, 470652, 470661, 470662, 470663, 470665, 470700, 470701, 470702, 470703, 470704, 470705, 470706, 470708, 470715, 470720, 470721, 470722, 470730, 470740, 470750, 470751, 470752, 470753, 470760, 470770, 470771, 470772, 470780, 470781, 470795, 470796, 470800, 470801, 470802, 470803, 470804, 470805
--	---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.