

**MOBIHEL 2K HARDENER 750W**Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : MOBIHEL 2K HARDENER 750W

Product code : 47769311

**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-  
stance/Mixture : PC9a: Coatings and paints, thinners, paint removersRecommended restrictions  
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si**1.4 Emergency telephone number**

Emergency telephone number: 911

Access code: 13586 +1 760 476 3959

---

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

## MOBIHEL 2K HARDENER 750W

Version 2.0      Revision Date: 12.06.2026      SDS Number: MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023



Specific target organ toxicity - single exposure, Category 3, Respiratory system  
Specific target organ toxicity - single exposure, Category 3, Central nervous system

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

## 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H225 H317 H319 H335 H336	Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<p><b>Prevention:</b></p> <p>P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233      Keep container tightly closed.</p> <p>P261      Avoid breathing mist or vapours.</p> <p>P280      Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.</p> <p><b>Response:</b></p> <p>P303 + P361 + P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.</p> <p>P370 + P378      In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.</p>	

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer  
ethyl acetate

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified  
4-isocyanatosulphonyltoluene

## Additional Labelling

EUH204      Contains isocyanates. May produce an allergic reaction.

## MOBIHEL 2K HARDENER 750W

Version 2.0      Revision Date: 12.06.2026      SDS Number: MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
ethylacetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 30 - < 50
isobutyl acetate	110-19-0 203-745-1 607-026-00-7 01-2119488971-22	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
solvent naphtha (petroleum), light aromatic	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2;	>= 1 - < 2.5

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

p-toluenesulphonyl isocyanate	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47	H411 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 STOT SE 3; H335 (Respiratory system)	>= 0.1 - < 1
-------------------------------	--	--	--------------

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.  
Repeated exposure may cause skin dryness or cracking.
- May cause an allergic skin reaction.

## MOBIHEL 2K HARDENER 750W

Version  
2.0

Revision Date:  
12.06.2026

SDS Number:  
MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.

**MOBIHEL 2K HARDENER 750W**Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**6.2 Environmental precautions**

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and material for containment and cleaning up**

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

See sections: 7, 8, 11, 12 and 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

## MOBIHEL 2K HARDENER 750W

Version 2.0      Revision Date: 12.06.2026      SDS Number: MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene-diisocyanate, polymer	28182-81-2	TWA	0.01 mg/m <sup>3</sup> (NCO)	98/24/EC I
		STEL	0.02 mg/m <sup>3</sup> (NCO)	98/24/EC I
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
		STEL	400 ppm 1,468 mg/m <sup>3</sup>	2017/164/EU
isobutyl acetate	110-19-0	TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

# SAFETY DATA SHEET



## MOBIHEL 2K HARDENER 750W

Version  
2.0

Revision Date:  
12.06.2026

SDS Number:  
MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene-di-isocyanate, polymer	Workers	Inhalation	Long-term local effects	0.5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1 mg/m <sup>3</sup>
ethyl acetate	Workers	Inhalation	Acute systemic effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	734 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	367 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	367 mg/m <sup>3</sup>
isobutyl acetate	Workers	Dermal	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	4.5 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	5 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	10 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	5 mg/kg

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

	Consumers	Oral	ffects	bw/day
			Long-term systemic effects	5 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	32 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
4-isocyanatosulphonyltoluene	Workers	Inhalation	Long-term systemic effects	3.24 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	0.8 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0.92 mg/kg bw/day
	Consumers	Dermal	Long-term systemic	0.46 mg/kg

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

			effects	bw/day
	Consumers	Oral	Long-term systemic effects	0.46 mg/kg bw/day

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006**

Substance name	Environmental Compartment	Value
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
	Fresh water	0.1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
ethyl acetate	Intermittent use/release	1 mg/l
	Soil	0.24 mg/kg dry weight (d.w.)
	Marine water	0.026 mg/l
	Fresh water	0.26 mg/l
	Marine sediment	0.125 mg/kg dry weight (d.w.)
	Fresh water sediment	1.25 mg/kg dry weight (d.w.)
isobutyl acetate	Sewage treatment plant	650 mg/l
	Intermittent use/release	1.65 mg/l
	Soil	0.0755 mg/kg dry weight (d.w.)
	Marine water	0.017 mg/l
	Fresh water	0.17 mg/l
	Marine sediment	0.0877 mg/kg dry weight (d.w.)
n-butyl acetate	Fresh water sediment	0.877 mg/kg dry weight (d.w.)
	Sewage treatment plant	200 mg/l
	Intermittent use/release	0.34 mg/l
	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
4-isocyanatosulphonyltoluene	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
	Soil	0.0168 mg/kg dry weight (d.w.)

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

	Marine water	0.003 mg/l
	Fresh water	0.03 mg/l
	Marine sediment	0.0172 mg/kg dry weight (d.w.)
	Fresh water sediment	0.172 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.4 mg/l
	Intermittent use/release	0.3 mg/l

**8.2 Exposure controls****Individual protection measures, such as personal protective equipment (PPE)**

- Eye/face protection : Equipment should conform to EN 166  
Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection  
Gloves : Viton® (> 0,6 mm; < 240 min); ISO EN374 |  
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic vapour type (A)

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- Physical state : liquid
- Form : liquid

**MOBIHEL 2K HARDENER 750W**Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

---

Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	-95.0 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	77 °C (calculation method (principal components, lowest value))
Flash point	:	-4 °C (calculation method (principal components, lowest value))
Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	11.5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1.2 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	< 1,100 hPa (calculation method (principal components, highest value))  (50 °C)
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.950 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	immiscible, partly soluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 2.65 (calculation method (principal components, highest value))
Ignition temperature	:	404 °C (calculation method (principal components, highest value))

**MOBIHEL 2K HARDENER 750W**Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

---

- Decomposition temperature : No decomposition if stored and applied as directed.  
Hazardous decomposition products formed under fire conditions.
- Viscosity  
Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)
- Explosive properties : Not applicable
- Oxidizing properties : Sustains combustion

**9.2 Other information**No data available  
VOC

- : (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))  
61.48 %

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

- Hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

- Conditions to avoid : Heat, flames and sparks.

**10.5 Incompatible materials**

- Materials to avoid : Incompatible with strong acids and bases.

**10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Not classified based on available information.  
Not classified due to lack of data.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**Components:****Hexamethylene-di-isocyanate, polymer:**

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

**ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1600 ppm  
Exposure time: 8 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  20,000 mg/kg

**n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  5,000 mg/kg

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.  
Repeated exposure may cause skin dryness or cracking.

## MOBIHEL 2K HARDENER 750W

Version  
2.0

Revision Date:  
12.06.2026

SDS Number:  
MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

---

### **Product:**

Remarks : May cause skin irritation and/or dermatitis.

### **Components:**

#### **4-isocyanatosulphonyltoluene:**

Result : irritating

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

Causes serious eye irritation.

### **Product:**

Remarks : May cause irreversible eye damage.

### **Components:**

#### **ethyl acetate:**

Result : Eye irritation

#### **4-isocyanatosulphonyltoluene:**

Result : Eye irritation

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Respiratory sensitisation**

Not classified due to lack of data.

### **Product:**

Remarks : Causes sensitisation.

### **Components:**

#### **Hexamethylene-di-isocyanate, polymer:**

Result : Probability or evidence of skin sensitisation in humans

#### **4-isocyanatosulphonyltoluene:**

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

Result : Probability of respiratory sensitisation in humans based on animal testing

**Germ cell mutagenicity**

Not classified based on available information.  
Not classified due to lack of data.

**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

**Carcinogenicity**

Suspected of causing cancer.  
Not classified due to lack of data.

**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

**Reproductive toxicity**

Suspected of damaging the unborn child.  
Not classified due to lack of data.

**STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

**Components:****Hexamethylene-di-isocyanate, polymer:**

Assessment : May cause respiratory irritation.

**ethyl acetate:**

Assessment : May cause drowsiness or dizziness.

**isobutyl acetate:**

Assessment : May cause drowsiness or dizziness.

**n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

## MOBIHEL 2K HARDENER 750W

Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

**4-isocyanatosulphonyltoluene:**

Assessment : May cause respiratory irritation.

**STOT - repeated exposure**

Not classified based on available information.

Not classified due to lack of data.

**Aspiration hazard**

Not classified based on available information.

Not classified due to lack of data.

**Components:****Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

May be fatal if swallowed and enters airways.

**Further information****Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.**SECTION 12: Ecological information****12.1 Toxicity****Components:****n-butyl acetate:**

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): &gt; 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): &gt;= 647.7 mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

**MOBIHEL 2K HARDENER 750W**

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2025
2.0	12.06.2026	MAT000477693 JO/EN	Date of first issue: 01.12.2023

---

**Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified:**

Toxicity to fish : LC50 (Fish): &gt; 1 - 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): &gt; 1 - 10 mg/l

Toxicity to microorganisms : EC50 (Bacteria): &gt; 1 - 10 mg/l

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability****Components:****n-butyl acetate:**Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301DStability in water : Degradation half life: 78 d  
pH: 8  
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

**12.3 Bioaccumulative potential****Components:****ethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 0.6

**isobutyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1.72

**n-butyl acetate:**Bioaccumulation : Bioconcentration factor (BCF): 15  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

**MOBIHEL 2K HARDENER 750W**Version  
2.0Revision Date:  
12.06.2026SDS Number:  
MAT000477693  
JO/ENDate of last issue: 10.09.2025  
Date of first issue: 01.12.2023

---

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects****Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14: Transport information****14.1 UN number**

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263

## MOBIHEL 2K HARDENER 750W

Version 2.0      Revision Date: 12.06.2026      SDS Number: MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

**IATA** : UN 1263

**14.2 UN proper shipping name**

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

**14.3 Transport hazard class(es)**

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

**14.4 Packing group**

**ADN**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 364

## MOBIHEL 2K HARDENER 750W

Version 2.0      Revision Date: 12.06.2026      SDS Number: MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**IATA (Passenger)**

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**14.5 Environmental hazards****ADN**

Environmentally hazardous : no

**ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this substance.

**SECTION 16: Other information****Full text of H-Statements**

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.

## MOBIHEL 2K HARDENER 750W

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2025
2.0	12.06.2026	MAT000477693	Date of first issue: 01.12.2023
		JO/EN	

H315 : Causes skin irritation.  
 H317 : May cause an allergic skin reaction.  
 H319 : Causes serious eye irritation.  
 H332 : Harmful if inhaled.  
 H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 : May cause respiratory irritation.  
 H336 : May cause drowsiness or dizziness.  
 H411 : Toxic to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox. : Acute toxicity  
 Aquatic Chronic : Long-term (chronic) aquatic hazard  
 Asp. Tox. : Aspiration hazard  
 Eye Irrit. : Eye irritation  
 Flam. Liq. : Flammable liquids  
 Resp. Sens. : Respiratory sensitisation  
 Skin Irrit. : Skin irritation  
 Skin Sens. : Skin sensitisation  
 STOT SE : Specific target organ toxicity - single exposure  
 2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values  
 2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
 98/24/EC I : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values  
 2017/164/EU / STEL : Short term exposure limit  
 2017/164/EU / TWA : Limit Value - eight hours  
 2019/1831/EU / TWA : Limit Value - eight hours  
 2019/1831/EU / STEL : Short term exposure limit  
 98/24/EC I / STEL : Limit values Short-term  
 98/24/EC I / TWA : Limit values 8 hours

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula-

## MOBIHEL 2K HARDENER 750W

Version 2.0      Revision Date: 12.06.2026      SDS Number: MAT000477693  
JO/EN

Date of last issue: 10.09.2025  
Date of first issue: 01.12.2023

tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information****Classification of the mixture:**

Flam. Liq. 2	H225
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
STOT SE 3	H336

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.