

**MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name : MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Product code : 40026404

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Use of the Sub-stance/Mixture : Coatings and paints, thinners, paint removers

Recommended restrictions on use : Reserved for industrial and professional use.

**1.3 Details of the supplier of the safety data sheet**

Company : KANSAI HELIOS Slovenija d.o.o.  
Količevo 65  
1230 Domžale  
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383  
productsafety@kansai-helios.si

**1.4 Emergency telephone number**

Ambulance (972) 101

Israel Poison Information Center +972 4 854 19 00

Access code: 13586 +1 760 476 3959

---

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P260 Do not breathe mist or vapours.
- P264 Wash skin thoroughly after handling.
- P273 Avoid release to the environment.

**Response:**

- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:  
 reaction mixture of ethylbenzene, m-xylene and p-xylene  
 acetone  
 n-butyl acetate

**Additional Labelling**

EUH208 Contains mixture of benzotriazole, mixture of sterically composed sebacates.  
 May produce an allergic reaction.

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version  
1.0Revision Date:  
19.07.2023SDS Number:  
MAT000400264  
IL/ENDate of last issue: -  
Date of first issue: 19.07.2023**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
reaction mixture of ethylbenzene, m-xylene and p-xylene	-  905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 30 - < 50
acetone	67-64-1  200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 10 - < 20
n-butyl acetate	123-86-4  204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
mixture of benzotriazole	104810-48-2  400-830-7 607-176-00-3 01-0000015075-76	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0.25 - < 1
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5  915-687-0 01-2119491304-40	Skin Sens. 1; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - < 1

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

Do not breathe vapours/dust.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Container may be opened only under exhaust ventilation hood.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Specific use(s) : For further information, refer to the product technical data sheet.

Consult the technical guidelines for the use of this substance/mixture.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version  
1.0Revision Date:  
19.07.2023SDS Number:  
MAT000400264  
IL/ENDate of last issue: -  
Date of first issue: 19.07.2023

reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	TLV-TWA	100 ppm	IL OEL
		TLV-C	150 mg/m <sup>3</sup>	IL OEL
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	20 ppm	ACGIH
acetone	67-64-1	TWA	500 ppm 1,210 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

**Biological occupational exposure limits**

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mixture of ethylbenzene, m-xylene and p-xylene	1330-20-7	methyl hippuric acid: 1.5 g/g creatinine (Urine)		IL BEI
		Methylhippuric acids: 1.5 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
acetone	67-64-1	Acetone: 25 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

**Derived No Effect Level (DNEL)**

according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
reaction mixture of ethylbenzene, m-xylene and p-xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65.3 mg/m <sup>3</sup>

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version  
1.0Revision Date:  
19.07.2023SDS Number:  
MAT000400264  
IL/ENDate of last issue: -  
Date of first issue: 19.07.2023

	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	289 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	14.8 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	108 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	16 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
acetone	Consumers	Inhalation	Long-term systemic effects	200 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects	62 mg/kg
	Consumers	Dermal	Long-term systemic effects	62 mg/kg
	Workers	Dermal	Long-term systemic effects	186 mg/kg
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	48 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	12 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35.7 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version  
1.0Revision Date:  
19.07.2023SDS Number:  
MAT000400264  
IL/ENDate of last issue: -  
Date of first issue: 19.07.2023**Predicted No Effect Concentration (PNEC)**

according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
reaction mixture of ethylbenzene, m-xylene and p-xylene	Soil	2.31 mg/kg dry weight (d.w.)
	Marine water	0.327 mg/l
	Fresh water	0.327 mg/l
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Sewage treatment plant	6.58 mg/l
acetone	Intermittent use/release	0.327 mg/l
	Soil	29.5 mg/kg
	Marine water	1.06 mg/l
	Fresh water	10.6 mg/l
	Marine sediment	3.04 mg/l
	Fresh water sediment	30.4 mg/l
n-butyl acetate	Sewage treatment plant	100 mg/l
	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l

**8.2 Exposure controls****Personal protective equipment**

Eye/face protection : Equipment should conform to EN 166  
 Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); DIN EN374 |  
 PE laminate (> 0,1 mm; < 240 min); DIN EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
 Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

**MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Self-contained breathing apparatus

---

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Appearance	:	liquid
Colour	:	colourless
Odour	:	solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Melting point/freezing point	:	-94.7 °C (calculation method (principal components, lowest value))
Boiling point/boiling range	:	56 °C (calculation method (principal components, lowest value))
Flash point	:	-18 °C
Flammability (solid, gas)	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	13 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1.1 %(V) (calculation method (principal components, highest value))
Vapour pressure	:	233 hPa (calculation method (principal components, highest value)) (20 °C)
Relative vapour density	:	2 (calculation method (principal components, highest value))  (Air = 1.0)
Relative density	:	0.95 (calculation method (principal components, highest value))

**MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

Density	:	0.944 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	partly miscible
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 2.77 - 3.15 (calculation method (principal components, highest value))
Auto-ignition temperature	:	465 - 525 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
Viscosity	:	
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (40 °C)
Flow time	:	22 - 27 s at 20 °C Cross section: 4 mm Method: DIN 53211
Explosive properties	:	Not applicable
Oxidizing properties	:	Sustains combustion

**9.2 Other information**

No data available	:	
VOC	:	(Directive 2004/42/EC) 540 g/l

---

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No decomposition if stored and applied as directed.

**10.2 Chemical stability**

No decomposition if stored and applied as directed.

**10.3 Possibility of hazardous reactions**

Hazardous reactions	:	No decomposition if stored and applied as directed.
	:	Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

**MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

**10.5 Incompatible materials**

Materials to avoid : Incompatible with strong acids and bases.

**10.6 Hazardous decomposition products**

Adequate ventilation is required.  
Heating can release vapours which can be ignited.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Not classified based on available information.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  8,700 mg/kg

Acute inhalation toxicity : Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

**acetone:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat):  $\geq$  10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit):  $\geq$  5,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH**

Version 1.0      Revision Date: 19.07.2023      SDS Number: MAT000400264 IL/EN      Date of last issue: -  
Date of first issue: 19.07.2023

---

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:**

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : irritating

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks : May cause irreversible eye damage.

**Components:**

**reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Result : Eye irritation

**acetone:**

Result : Eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks : Causes sensitisation.

**Components:**

**mixture of benzotriazole:**

Result : Probability or evidence of skin sensitisation in humans

**mixture of sterically composed sebacates:**

Result : May cause sensitisation by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version  
1.0Revision Date:  
19.07.2023SDS Number:  
MAT000400264  
IL/ENDate of last issue: -  
Date of first issue: 19.07.2023**Components:****mixture of sterically composed sebacates:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

**STOT - single exposure**May cause respiratory irritation.  
May cause drowsiness or dizziness.**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

**acetone:**

Assessment : May cause drowsiness or dizziness.

**n-butyl acetate:**

Assessment : May cause drowsiness or dizziness.

**STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

**Further information****Product:**Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
Concentrations substantially above the TLV value may cause narcotic effects.  
Solvents may degrease the skin.

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version  
1.0Revision Date:  
19.07.2023SDS Number:  
MAT000400264  
IL/ENDate of last issue: -  
Date of first issue: 19.07.2023

---

**SECTION 12: Ecological information****12.1 Toxicity****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**Toxicity to fish : LC50 (Fish):  $\geq 1 - 10$  mg/lToxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $\geq 1 - 10$  mg/lToxicity to microorganisms : EC50 (Bacteria):  $\geq 1 - 100$  mg/l**acetone:**Toxicity to fish : LC50 (Fish):  $> 1,000$  mg/lToxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)):  $> 1,000$  mg/lToxicity to microorganisms : EC50 (Bacteria):  $> 1,000$  mg/l**n-butyl acetate:**Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)):  $> 200$  mg/lEC50 (Desmodesmus subspicatus (green algae)):  $\geq 647.7$  mg/l  
Exposure time: 72 hToxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h**mixture of benzotriazole:****Ecotoxicology Assessment**

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**mixture of sterically composed sebacates:****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

Biodegradability : Remarks: Readily biodegradable.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**n-butyl acetate:**

Biodegradability : Result: Biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d  
pH: 8  
Remarks: Hydrolyses slowly.

Photodegradation : Remarks: Decomposes rapidly in contact with light.

**12.3 Bioaccumulative potential****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25.9  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

**acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.24

**n-butyl acetate:**

Bioaccumulation : Bioconcentration factor (BCF): 15  
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

**mixture of sterically composed sebacates:**

Partition coefficient: n-octanol/water : log Pow: 2.37 - 2.77  
pH: 7

**12.4 Mobility in soil****Components:****reaction mixture of ethylbenzene, m-xylene and p-xylene:**

Distribution among environmental compartments : Koc: 537, log Koc: 2.73  
Remarks: Moderately mobile in soils  
The product evaporates from soil.

**MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

---

Stability in soil : Dissipation time: 23 d  
Percentage dissipation: 50 % (DT50)

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects****Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14: Transport information****14.1 UN number**

ADN	: UN 1263
ADR	: UN 1263
RID	: UN 1263
IMDG	: UN 1263

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version 1.0      Revision Date: 19.07.2023      SDS Number: MAT000400264  
IL/EN

Date of last issue: -  
Date of first issue: 19.07.2023

**IATA** : UN 1263

**14.2 UN proper shipping name**

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

**14.3 Transport hazard class(es)**

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

**14.4 Packing group**

**ADN**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 353

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**14.5 Environmental hazards****ADN**

Environmentally hazardous : no

**ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: 540 g/l

**15.2 Chemical safety assessment**

A Chemical Safety Assessment is not required for this substance.

**SECTION 16: Other information****Full text of H-Statements**

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H361f : Suspected of damaging fertility.  
H373 : May cause damage to organs through prolonged or repeated

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

H411 : Toxic to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

IL BEI : Israel. Safety at Work Regulations - Annex III Biological Exposure Indices

IL OEL : Israel. Safety at Work Regulations (Environmental monitoring and biological monitoring of workers)

2000/39/EC / TWA : Limit Value - eight hours

2000/39/EC / STEL : Short term exposure limit

2019/1831/EU / TWA : Limit Value - eight hours

2019/1831/EU / STEL : Short term exposure limit

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

IL OEL / TLV-TWA : Threshold Limit Value - Time Weighted (TLV-TWA)

IL OEL / TLV-C : Threshold Limit Value - Ceiling (TLV-C)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

## MOBIHEL 2:1 CLEARCOAT V5 ANTI SCRATCH

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	19.07.2023	MAT000400264 IL/EN	Date of first issue: 19.07.2023

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information****Classification of the mixture:**

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IL / EN