

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOBIHEL 2K TRDILEC 750 PLUS

Product code : 402168

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : PC9a: Coatings and paints, thinners, paint removers
stance/Mixture

Recommended restrictions : Reserved for industrial and professional use.
on use

1.3 Details of the supplier of the safety data sheet

Company : KANSAI HELIOS Slovenija d.o.o.
Količevo 65
1230 Domžale
Slovenia

Telephone Company : 386 (1) 722 4383

Telefax Company : 386 (1) 722 4310

Responsible/issuing person : 386 (1) 722 4383
productsafety@kansai-helios.si

1.4 Emergency telephone number

01 809 2166 National Poisons Information Centre 01 809 2166

01 809 2566 Healthcare Professionals 01 809 2566

01 809 2566 Healthcare Professionals 01 809 2566

Access code: 13586 +1 760 476 3962

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Serious eye damage, Category 1 H318: Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements	:	H225	Highly flammable liquid and vapour.
		H317	May cause an allergic skin reaction.
		H318	Causes serious eye damage.
		H335	May cause respiratory irritation.
		H336	May cause drowsiness or dizziness.

Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
--------------------------------	---	--------	---

Precautionary statements	:	Prevention:		
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
		P233	Keep container tightly closed.	
		P261	Avoid breathing mist or vapours.	
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.	
		Response:		
		P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.	
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.	

Hazardous components which must be listed on the label:

Hexamethylene-di-isocyanate, polymer
ethyl acetate
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
4-isocyanatosulphonyltoluene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

hexamethylene-di-isocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene-di-isocyanate, polymer	28182-81-2 500-060-2 01-2119485796-17	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 30 - < 50
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 30
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version 2.1 Revision Date: 13.08.2026 SDS Number: MAT000402168IE/E N Date of last issue: 19.11.2025 Date of first issue: 19.09.2023

[3-(2,3-epoxypropyl)trimethoxysilane	2530-83-8 219-784-2 01-2119513212-58	Eye Dam. 1; H318 Aquatic Chronic 3; H412	$\geq 3 - < 10$
4-isocyanatosulphonyltoluene	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 STOT SE 3; H335 (Respiratory system) EUH014 specific concentration limit Skin Irrit. 2; H315 $\geq 5\%$ STOT SE 3; H335 $\geq 5\%$ Eye Irrit. 2; H319 $\geq 5\%$	$\geq 0.1 - < 1$
hexamethylene-di-isocyanate	822-06-0 212-485-8 615-011-00-1 01-2119457571-37	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) specific concentration limit Skin Sens. 1; H317 $\geq 0.5\%$ Resp. Sens. 1; H334 $\geq 0.5\%$	$\geq 0.1 - < 0.5$

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

- | | |
|-------------------------|---|
| In case of skin contact | : If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|--|
| Risks | : May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking. |
| | : May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : For further information, refer to the product technical data sheet.
- Consult the technical guidelines for the use of this substance/mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version 2.1 Revision Date: 13.08.2026 SDS Number: MAT000402168IE/E
Date of last issue: 19.11.2025 Date of first issue: 19.09.2023
N

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hexamethylene-diisocyanate, polymer	28182-81-2	STEL	0.02 mg/m ³ (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		TWA	0.01 mg/m ³ (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		OELV - 15 min (STEL)	0.07 mg/m ³ (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 8 hrs (TWA)	0.02 mg/m ³ (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
ethyl acetate	141-78-6	OELV - 15 min (STEL)	400 ppm 1,468 mg/m ³	IE OEL
		OELV - 8 hrs (TWA)	200 ppm 734 mg/m ³	IE OEL
		STEL	400 ppm 1,468 mg/m ³	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU
	Further information: Indicative			
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
	Further information: Indicative			
		OELV - 15 min (STEL)	150 ppm 723 mg/m ³	IE OEL
		OELV - 8 hrs (TWA)	50 ppm 241 mg/m ³	IE OEL
butanone	78-93-3	OELV - 15 min (STEL)	300 ppm 900 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 8 hrs (TWA)	200 ppm 600 mg/m ³	IE OEL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version 2.1 Revision Date: 13.08.2026 SDS Number: MAT000402168IE/E Date of last issue: 19.11.2025
N Date of first issue: 19.09.2023

	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		STEL	300 ppm 900 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	200 ppm 600 mg/m3	2000/39/EC
	Further information: Indicative			
4-isocyanatosulphonyltoluene	4083-64-1	OELV - 15 min (STEL)	0.07 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 8 hrs (TWA)	0.02 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
hexamethylene-diisocyanate	822-06-0	STEL	0.02 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		TWA	0.01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		OELV - 8 hrs (TWA)	0.005 ppm (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Hexamethylene-diisocyanate, polymer	Workers	Inhalation	Long-term local effects	0.5 mg/m3
	Workers	Inhalation	Long-term systemic effects	1 mg/m3
ethyl acetate	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Workers	Inhalation	Long-term local effects	1468 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Consumers	Inhalation	Acute systemic effects	734 mg/m3
	Consumers	Inhalation	Acute local effects	734 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version 2.1 Revision Date: 13.08.2026 SDS Number: MAT000402168IE/E
N Date of last issue: 19.11.2025 Date of first issue: 19.09.2023

	Consumers	Inhalation	Long-term local effects	367 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	4.5 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	48 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	12 mg/m3
	Consumers	Inhalation	Long-term local effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	3.4 mg/kg bw/day
	Consumers	Dermal	Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Oral	Acute systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	7 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	11 mg/kg bw/day
butanone	Consumers	Inhalation	Long-term systemic effects	106 mg/m3
	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Dermal	Long-term systemic effects	1161 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	412 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	31 mg/kg bw/day
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Workers	Inhalation	Long-term systemic effects	147 mg/m3
	Workers	Dermal	Long-term systemic effects	21 mg/kg bw/day
	Consumers	Dermal	Long-term systemic	12.5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version 2.1 Revision Date: 13.08.2026 SDS Number: MAT000402168IE/E
Date of last issue: 19.11.2025 Date of first issue: 19.09.2023
N

			effects	bw/day
	Consumers	Oral	Long-term systemic effects	12.5 mg/kg bw/day
4-isocyanatosulphonyltoluene	Workers	Inhalation	Long-term systemic effects	3.24 mg/m3
	Consumers	Inhalation	Long-term systemic effects	0.8 mg/m3
	Workers	Dermal	Long-term systemic effects	0.92 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	0.46 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.46 mg/kg bw/day
hexamethylene-di-isocyanate	Workers	Inhalation	Long-term systemic effects	0.035 mg/m3
	Workers	Inhalation	Acute systemic effects	0.07 mg/m3
	Workers	Inhalation	Long-term local effects	0.035 mg/m3
	Workers	Inhalation	Acute local effects	0.07 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Hexamethylene-di-isocyanate, polymer	Soil	505 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
	Fresh water	0.1 mg/l
	Marine sediment	253 mg/kg dry weight (d.w.)
	Fresh water sediment	2530 mg/kg dry weight (d.w.)
	Sewage treatment plant	100 mg/l
	Intermittent use/release	1 mg/l
ethyl acetate	Soil	0.24 mg/kg dry weight (d.w.)
	Marine water	0.026 mg/l
	Fresh water	0.26 mg/l
	Marine sediment	0.125 mg/kg dry weight (d.w.)
	Fresh water sediment	1.25 mg/kg dry weight (d.w.)
	Sewage treatment plant	650 mg/l
	Intermittent use/release	1.65 mg/l
n-butyl acetate	Soil	0.0903 mg/kg dry weight (d.w.)
	Marine water	0.018 mg/l
	Fresh water	0.18 mg/l
	Marine sediment	0.0981 mg/kg dry weight (d.w.)
	Fresh water sediment	0.981 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version 2.1 Revision Date: 13.08.2026 SDS Number: MAT000402168IE/E Date of last issue: 19.11.2025
N Date of first issue: 19.09.2023

		weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Intermittent use/release	0.36 mg/l
butanone	Soil	22.5 mg/kg dry weight (d.w.)
	Marine water	55.8 mg/l
	Fresh water	55.8 mg/l
	Marine sediment	284.7 mg/kg dry weight (d.w.)
	Fresh water sediment	284.74 mg/kg dry weight (d.w.)
	Sewage treatment plant	709 mg/l
[3-(2,3-epoxypropyl)trimethoxysilane	Soil	0.14 mg/kg dry weight (d.w.)
	Marine water	0.1 mg/l
	Fresh water	1 mg/l
	Marine sediment	0.36 mg/kg dry weight (d.w.)
	Fresh water sediment	3.6 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Intermittent use/release	1 mg/l
4-isocyanatosulphonyltoluene	Soil	0.0168 mg/kg dry weight (d.w.)
	Marine water	0.003 mg/l
	Fresh water	0.03 mg/l
	Marine sediment	0.0172 mg/kg dry weight (d.w.)
	Fresh water sediment	0.172 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.4 mg/l
	Intermittent use/release	0.3 mg/l
hexamethylene-di-isocyanate	Soil	0.0026 mg/kg dry weight (d.w.)
	Marine water	0.00774 mg/l
	Fresh water	0.0774 mg/l
	Marine sediment	0.001344 mg/kg dry weight (d.w.)
	Fresh water sediment	0.01334 mg/kg dry weight (d.w.)
	Sewage treatment plant	8.42 mg/l
	Intermittent use/release	0.774 mg/l

8.2 Exposure controls

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Equipment should conform to EN 166
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

problems.

Hand protection

Gloves : Viton® (> 0,6 mm; < 240 min); ISO EN374 |
PE laminate (> 0,1 mm; < 240 min); ISO EN374 |

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Equipment should conform to EN 14387

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Form : liquid

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

Melting point/freezing point : -86.4 °C (calculation method (principal components, lowest value))

Boiling point/boiling range : 77 °C (calculation method (principal components, lowest value))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Flammability	:	Static-accumulating flammable liquid., Combustible Solids
Upper explosion limit / Upper flammability limit	:	11.5 %(V) (calculation method (principal components, highest value))
Lower explosion limit / Lower flammability limit	:	1.2 %(V) (calculation method (principal components, highest value))
Flash point	:	-4 °C (calculation method (principal components, lowest value))
Ignition temperature	:	404 °C (calculation method (principal components, highest value))
Decomposition temperature	:	No decomposition if stored and applied as directed. Hazardous decomposition products formed under fire conditions.
pH	:	Not applicable
		substance/mixture is non-polar/aprotic
Viscosity		
Viscosity, kinematic	:	20.5 mm ² /s (40 °C)
Solubility(ies)		
Water solubility	:	immiscible
		partly soluble
Solubility in other solvents	:	Description: miscible with most organic solvents
Partition coefficient: n-octanol/water	:	log Pow: 1.81 (calculation method (principal components, highest value))
Vapour pressure	:	< 1,100 hPa (calculation method (principal components, highest value))

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

(50 °C)

Relative density : 0.93 (calculation method (principal components, highest value))

Density : 0.950 g/cm³

Relative vapour density : 4 (calculation method (principal components, lowest value))

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Sustains combustion

VOC : (Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control))
49.21 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Incompatible with strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Not classified due to lack of data.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

Hexamethylene-di-isocyanate, polymer:

Acute oral toxicity : LD50 (Rat, female): > 2,500 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
The test was conducted according to guideline

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
The test was conducted according to guideline

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 5,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1600 ppm
Exposure time: 8 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): >= 20,000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): >= 10,760 mg/kg

Acute dermal toxicity : LD50 (Rabbit): >= 5,000 mg/kg

butanone:

Acute oral toxicity : LD50 Oral (Rat): > > 2,000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > > 2,000 mg/kg

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Acute oral toxicity : LD50 (Rat): 8.03625 g/kg
Method: OECD Test Guideline 401
The test was conducted equivalent or similar to guideline

Acute inhalation toxicity : LC50 (Rat): > 5.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
The test was conducted equivalent or similar to guideline

Acute dermal toxicity : LD50 (Rabbit, male): 4.25 g/kg
Method: OECD Test Guideline 402
The test was conducted equivalent or similar to guideline

4-isocyanatosulphonyltoluene:

Acute oral toxicity : LD50 (Rat): 2,330 mg/kg
Method: OECD Test Guideline 401
The test was conducted equivalent or similar to guideline

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
The test was conducted according to guideline

hexamethylene-di-isocyanate:

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rat): > 7,000 mg/kg
Method: OECD Test Guideline 402
The test was conducted according to guideline

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.
Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : Extremely corrosive and destructive to tissue.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Components:

Hexamethylene-di-isocyanate, polymer:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation
Remarks	: The test was conducted according to guideline

ethyl acetate:

Assessment	: Repeated exposure may cause skin dryness or cracking.
------------	---

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Mild skin irritation
Remarks	: The test was conducted equivalent or similar to guideline

n-butyl acetate:

Assessment	: Repeated exposure may cause skin dryness or cracking.
------------	---

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation
Remarks	: The test was conducted equivalent or similar to guideline

butanone:

Assessment	: Repeated exposure may cause skin dryness or cracking.
------------	---

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation
Remarks	: The test was conducted according to guideline

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation
Remarks	: The test was conducted equivalent or similar to guideline

4-isocyanatosulphonyltoluene:

Result	: irritating
--------	--------------

hexamethylene-di-isocyanate:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Corrosive after 4 hours or less of exposure
Remarks	: The test was conducted according to guideline

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Serious eye damage/eye irritation

Causes serious eye damage.
Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

Hexamethylene-di-isocyanate, polymer:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation
Remarks	: The test was conducted according to guideline

ethyl acetate:

Result : Eye irritation

n-butyl acetate:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation
Remarks	: The test was conducted according to guideline

butanone:

Result : Eye irritation

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Result : Corrosive

4-isocyanatosulphonyltoluene:

Result : Eye irritation

hexamethylene-di-isocyanate:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: Irreversible effects on the eye
Remarks	: The test was conducted according to guideline

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Skin sensitisation

May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Respiratory sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified due to lack of data.

Product:

Remarks : Causes sensitisation.

Components:

Hexamethylene-di-isocyanate, polymer:

Result : Probability or evidence of skin sensitisation in humans

ethyl acetate:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: The test was conducted according to guideline

Assessment : Not classified due to data which are conclusive although insufficient for classification.

n-butyl acetate:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

Assessment : Not classified due to data which are conclusive although insufficient for classification.

butanone:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: The test was conducted according to guideline

Assessment : Not classified due to data which are conclusive although insufficient for classification.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline

Assessment : Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Result : Probability of respiratory sensitisation in humans based on animal testing

hexamethylene-di-isocyanate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive
Remarks : The test was conducted equivalent or similar to guideline

Exposure routes : Inhalation
Species : Mouse
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Assessment : May cause sensitisation by inhalation.

Germ cell mutagenicity

Not classified based on available information.
Not classified due to lack of data.

Components:

Hexamethylene-di-isocyanate, polymer:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
The test was conducted according to guideline

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
The test was conducted according to guideline

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
The test was conducted according to guideline

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
The test was conducted equivalent or similar to guideline

ethyl acetate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
The test was conducted equivalent or similar to guideline

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
The test was conducted equivalent or similar to guideline

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Hamster
Application Route: oral (gavage)
Method: OECD Test Guideline 474
Result: negative
The test was conducted equivalent or similar to guideline

Germ cell mutagenicity- Assessment : Not classified due to data which are conclusive although insufficient for classification.

n-butyl acetate:

Genotoxicity in vitro : Test Type: in vitro micronucleus test
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
The test was conducted according to guideline

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Result: negative
The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Application Route: oral (gavage)
Method: OECD Test Guideline 474
Result: negative
The test was conducted according to guideline

Germ cell mutagenicity- Assessment : Not classified due to data which are conclusive although insufficient for classification.

butanone:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
The test was conducted equivalent or similar to guideline

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
The test was conducted equivalent or similar to guideline

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Application Route: Intraperitoneal
Method: OECD Test Guideline 474
Result: negative
The test was conducted equivalent or similar to guideline

Germ cell mutagenicity- Assessment : Not classified due to data which are conclusive although insufficient for classification.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive
The test was conducted equivalent or similar to guideline

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive
The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: comet assay

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Species: Rat
Application Route: oral (gavage)
Method: OECD Test Guideline 489
Result: positive
The test was conducted according to guideline

Germ cell mutagenicity- Assessment : Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive
The test was conducted according to guideline

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
The test was conducted according to guideline

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Application Route: oral (gavage)
Method: OECD Test Guideline 474
Result: negative
The test was conducted according to guideline

Germ cell mutagenicity- Assessment : Not classified due to data which are conclusive although insufficient for classification.

hexamethylene-di-isocyanate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Application Route: inhalation (vapour)
Method: OECD Test Guideline 474
Result: negative
The test was conducted equivalent or similar to guideline

Germ cell mutagenicity- Assessment : Not classified due to data which are conclusive although insufficient for classification.

Carcinogenicity

Not classified based on available information.
Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Components:

ethyl acetate:

Species	: Mouse
Application Route	: Intraperitoneal
Exposure time	: 1.846154 Months
Result	: negative

Carcinogenicity - Assessment : Not classified due to lack of data.

n-butyl acetate:

Carcinogenicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

butanone:

Carcinogenicity - Assessment : Not classified due to lack of data.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Species	: Mouse, male
Application Route	: Dermal
Result	: negative
Remarks	: No test guideline followed

Carcinogenicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Carcinogenicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

hexamethylene-di-isocyanate:

Species	: Rat
Application Route	: inhalation (vapour)
Exposure time	: 2 yr
Method	: OECD Test Guideline 453
Result	: negative
Remarks	: The test was conducted according to guideline

Carcinogenicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

Reproductive toxicity

Not classified based on available information.
Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Components:

ethyl acetate:

Effects on fertility	:	Test Type: Reproduction Test Species: Rat, male Application Route: inhalation (vapour) Result: negative Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: oral (drinking water) Method: OECD Test Guideline 416 Result: negative The test was conducted equivalent or similar to guideline
----------------------	---	---

Effects on foetal development	:	Test Type: Developmental Toxicity Species: Rat Application Route: Inhalation Result: negative The test was conducted equivalent or similar to guideline Test Type: Developmental Toxicity Species: Mouse Application Route: oral (feed) Result: positive The test was conducted equivalent or similar to guideline
-------------------------------	---	---

Reproductive toxicity - Assessment	:	Not classified due to data which are conclusive although insufficient for classification. Not classified due to lack of data.
------------------------------------	---	--

n-butyl acetate:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapour) Method: OECD Test Guideline 416 Result: negative The test was conducted according to guideline
Effects on foetal development	:	Test Type: Developmental Toxicity Species: Rat Application Route: inhalation (vapour) Result: positive The test was conducted equivalent or similar to guideline

Reproductive toxicity - Assessment	:	Not classified due to data which are conclusive although insufficient for classification. Not classified due to data which are conclusive although insufficient for classification.
------------------------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
The test was conducted equivalent or similar to guideline

Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: oral (drinking water)
Method: OECD Test Guideline 416
Result: negative
The test was conducted equivalent or similar to guideline

Effects on foetal development : Test Type: Developmental Toxicity
Species: Mouse
Application Route: inhalation (vapour)
Result: positive

Reproductive toxicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

Not classified due to data which are conclusive although insufficient for classification.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: oral (gavage)
Method: OECD Test Guideline 415
Result: negative
The test was conducted according to guideline

Effects on foetal development : Test Type: Developmental Toxicity
Species: Rabbit
Application Route: oral (gavage)
Result: negative
The test was conducted equivalent or similar to guideline

Reproductive toxicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Application Route: oral (feed)
Method: OECD Test Guideline 416
Result: negative
The test was conducted according to guideline

Reproductive toxicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

Not classified due to data which are conclusive although insufficient for classification.

hexamethylene-di-isocyanate:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 422
Result: negative
The test was conducted according to guideline

Effects on foetal development : Test Type: Developmental Toxicity
Species: Rat
Application Route: inhalation (vapour)
Result: negative
The test was conducted according to guideline

Reproductive toxicity - Assessment : Not classified due to data which are conclusive although insufficient for classification.

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Components:

Hexamethylene-di-isocyanate, polymer:

Assessment : May cause respiratory irritation.

ethyl acetate:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

butanone:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.
Not classified due to lack of data.

Components:

ethyl acetate:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

n-butyl acetate:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

butanone:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

hexamethylene-di-isocyanate:

Assessment : Not classified due to data which are conclusive although insufficient for classification.

Aspiration hazard

Not classified based on available information.
Not classified due to lack of data.

Components:

ethyl acetate:

Not classified due to data which are conclusive although insufficient for classification.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

n-butyl acetate:

Not classified due to data which are conclusive although insufficient for classification.

butanone:

Not classified due to data which are conclusive although insufficient for classification.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Not classified due to data which are conclusive although insufficient for classification.

4-isocyanatosulphonyltoluene:

Not classified due to data which are conclusive although insufficient for classification.

hexamethylene-di-isocyanate:

Not classified due to data which are conclusive although insufficient for classification.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hexamethylene-di-isocyanate, polymer:

Toxicity to algae/aquatic : EL50 (Desmodesmus subspicatus (green algae)): > 1,000

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted equivalent or similar to guideline

EL10 (Desmodesmus subspicatus (green algae)): 370 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted equivalent or similar to guideline

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted according to guideline

Toxicity to microorganisms : EC10 (Photobacterium phosphoreum): 1,650 mg/l
Exposure time: 15 min

EC50 (Photobacterium phosphoreum): 5,870 mg/l
Exposure time: 15 min

Toxicity to fish (Chronic toxicity) : NOEC: > 75.6 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210
The test was conducted equivalent or similar to guideline

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2.4 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
The test was conducted equivalent or similar to guideline

n-butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
The test was conducted equivalent or similar to guideline

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (water flea)): 44 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Method: OECD Test Guideline 202

The test was conducted equivalent or similar to guideline

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 200 mg/l

EC50 (Desmodesmus subspicatus (green algae)): >= 647.7 mg/l

Exposure time: 72 h

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23.2 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
The test was conducted according to guideline

butanone:

Toxicity to fish : LC50 (Fish): > 1,000 mg/l

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): > 1,000 mg/l

Toxicity to algae/aquatic plants : EC10 (Pseudokirchneriella subcapitata (green algae)): 1,010 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
The test was conducted according to guideline

EC50 (Pseudokirchneriella subcapitata (green algae)): 1,240 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

The test was conducted according to guideline

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 350 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 3 h

Toxicity to daphnia and other : NOEC: 100 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d
Species: Daphnia magna (Water flea)

4-isocyanatosulphonyltoluene:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
The test was conducted according to guideline

Toxicity to algae/aquatic plants : EC10 (Pseudokirchneriella subcapitata (green algae)): 23 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted according to guideline

EC50 (Pseudokirchneriella subcapitata (green algae)): 30 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted according to guideline

hexamethylene-di-isocyanate:

Toxicity to algae/aquatic plants : EC10 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted equivalent or similar to guideline

EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
The test was conducted equivalent or similar to guideline

Toxicity to microorganisms : EC10 (activated sludge): 299 mg/l
Exposure time: 3 h

EC50 (activated sludge): 842 mg/l
Exposure time: 3 h

12.2 Persistence and degradability

Components:

Hexamethylene-di-isocyanate, polymer:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.E.
The test was conducted according to guideline

ethyl acetate:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Biodegradation: 69 %

Exposure time: 20 d

n-butyl acetate:

Biodegradability : Result: Biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Stability in water : Degradation half life: 78 d
pH: 8
Hydrolyses slowly.

Photodegradation : Decomposes rapidly in contact with light.

butanone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 98 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
The test was conducted according to guideline

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 37 %
Exposure time: 28 d
Method: Regulation (EC) No. 440/2008, Annex, C.4-A
The test was conducted according to guideline

4-isocyanatosulphonyltoluene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 45 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
The test was conducted according to guideline

hexamethylene-di-isocyanate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 42 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
The test was conducted equivalent or similar to guideline

12.3 Bioaccumulative potential

Components:

Hexamethylene-di-isocyanate, polymer:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Partition coefficient: n-octanol/water : log Pow: > 4
Calculation method

ethyl acetate:

Bioaccumulation : Species: Leuciscus idus melanotus (Ide)
Bioconcentration factor (BCF): 30
No test guideline followed

Partition coefficient: n-octanol/water : log Pow: 0.6

n-butyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 15
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.81

butanone:

Partition coefficient: n-octanol/water : log Pow: 0.29

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Partition coefficient: n-octanol/water : log Pow: 0.5 (20 °C)
pH: 7

4-isocyanatosulphonyltoluene:

Partition coefficient: n-octanol/water : log Pow: 0.6
Method: OECD Test Guideline 117
The test was conducted according to guideline

hexamethylene-di-isocyanate:

Partition coefficient: n-octanol/water : log Pow: 3.2

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
Waste Code	: 08 00 00, WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 00, wastes from MFSU and removal of paint and varnish 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances 15 00 00, WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED 15 01 00, packaging (including separately collected municipal packaging waste) 15 01 10, packaging containing residues of or contaminated by hazardous substances HP3, Flammable HP4, Irritant - skin irritation and eye damage HP13, Sensitising

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

14.2 UN proper shipping name

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT
IATA	:	Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
ADR	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33
Labels	: 3
Tunnel restriction code	: (D/E)
RID	
Packing group	: II
Classification Code	: F1
Hazard Identification Number	: 33

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 74: hexamethylene-di-isocyanate

Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 49.21 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H412	: Harmful to aquatic life with long lasting effects.
EUH014	: Reacts violently with water.
EUH066	: Repeated exposure may cause skin dryness or cracking.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
Eye Irrit.	: Eye irritation
Skin Sens.	: Skin sensitisation
Resp. Sens.	: Respiratory sensitisation
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
98/24/EC I	: Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
IE OEL	: Ireland. List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

	and 2
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
98/24/EC I / STEL	: Limit values Short-term
98/24/EC I / TWA	: Limit values 8 hours
IE OEL / OELV - 8 hrs (TWA)	: Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	: Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Eye Dam. 1	H318

Classification procedure:

Based on product data or assessment
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



MOBIHEL 2K TRDILEC 750 PLUS

Version	Revision Date:	SDS Number:	Date of last issue: 19.11.2025
2.1	13.08.2026	MAT000402168IE/E	Date of first issue: 19.09.2023
		N	

Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.